Dynasonde and VIPIR Ionosonde

Field Site Requirements

Dr. Terry Bullett
University of Colorado
with
NOAA
National Geophysical Data Center
Terence.Bullett@colorado.edu

May 2015

VIPIR is the Hardware

SNR Ionograms



Fixed Frequency



Spectrum Analysis



Daily Spectrogram



Dynasonde is the Software



- Echo Detection
- Trace Classification
- Ionogram Scaling
- 3D echo-location
- Electron Density Profile
- Tilt Profile

Vertical Incidence Pulsed Ionospheric Radar

Very high interference immunity: IP3 > 45 dBm

High Dynamic Range: 115(I) +30(V) dB

Direct RF sampling 14 bits at 80 MHz

Fully digital conversion, receiver and exciter

Waveform Agility: 2 µs to 2 ms pulse/chip width

USB-2 Data and Command/Control Interfaces

8 coherent receive channels; Frequency: 0.3 – 26 MHz

4 kW class AB pulse amplifier: 3^{rd} harmonic < -30 dBc

Precise GPS timing possible for bi-static operation

Radar software Open Source C code; runs under Linux

Upgrades for the VIPIR Mark II

- FPGA based digital receiver
- 16 bit, 120 MHz ADC
- USB3 data transfer
- Improved analog front end
- Improved receive antenna pre-amplifiers
- Contemporary computers and data storage
- Options:
    - High power low pass transmit harmonic filter
    - Rubidium oscillator for oblique phase measurements

VIPIR Mark II

Jang Bogo Antarctic Research Station
Korean Polar Research Institute

Wallops Island VIPIR hardware

Power Conditioner

4kW RF Amplifier

KVM

Exciter

Reference

Receiver

Front End

Balun

Control Computer

Analysis Computer

UPS

Standard 19” rack, 46” tall

Installation “classes”

- Research
  - Major research facility for plasma physics, propagation research and ionosphere discovery. Performance is primary, cost and footprint are secondary concerns.
- Average
  - Ionosphere monitoring and geophysical research. A compromise between of cost and capability.
- Small
  - Ionospheric monitoring. Cost and footprint are primary concerns and limitations.
- Transportable
  - Ionospheric measurements from various locations. Mobility is the primary concern.

There is approximately a factor of 10 in performance between these classes

World Class VIPIR Field Site



8 channel HF radar

8 or 10 element Rx array

Log-periodic Tx antenna

35m steel towers (4)

5 to 10 acre footprint



Intermediate VIPIR Field Site



8 channel HF radar

8 element Rx array

Inverted Delta Tx antenna

25m Tx Towers (2)

5m Rx towers (8)

3.5 acre footprint



Reduced VIPIR Field Site





4 channel HF radar

4 element Rx array

Inverted Delta Tx antenna

15m Tx poles (2)

5m Rx poles (4)

< 1 acre footprint

Virtual walk-through:
http://www.ionosonde.com/images/Ionosonde_Tour.avi

Transportable VIPIR

Photographs of VIPIR prototype antennas designed for use on a 40 ft fishing boat.



Portability is key

Antennas engineered for temporary install & transport

4 or 8 channel HF radar

2-8 element Rx array

Mini-Delta Tx antenna or custom

Facilities

Climate Controlled Shelter

- 3mx3m minimum
- Larger space enhances research

25,000 BTU Air Conditioner (Large window model)

220v x 15A or 110Vx30A power

Internet connection

- 128kbps minimum ; 1Mbps recommended

Absence of:

- High Voltage Power Lines
- Industrial electrical noise
- Other HF users (receive and transmit)
- MF transmitters (AM Broadcast or NDB)

Local Construction

Shelter

Receive anchors

Receive poles

Transmit anchors

Transmit towers

RF Cable conduit

Cable Vault

Local Parts (Optional)

19” equipment rack

Rack Slides

Power Conditioner

UPS

Keyboard

Mouse

Monitor

KVM switch

Boulder Site Photos



Wallops Shelter



Wallops VIPIR Field Site



Long Term "World Class Observatory" being provided by NASA for continued research and routine observations

Wallops Island: September 2006

Inverted Delta Transmit Antenna

San Juan Observatory
“Small” : 15m tall x 45m long

Receive Antennas

2m crossed dipoles



Antennas at locations -9 -3 -1 0 +4
Gives separations of 1 2 3 4 5 6 7 8 9 13
Units of 7m

Transmitter Technical Data

Frequency Range: 0.5 to 26 MHz

4 kW peak power, 2% duty cycle max. 80W average.

Logarithmically spaced frequencies (typical 0.5% spacing)

4 to 16 pulses per frequency, 100 Hz rate

70 microsecond (15 kHz bandwidth) pulses

Raised cosine pulse: Low out-of-band emission

Very low harmonics

Typical 0.1 second channel use per frequency

1 to 5 minute repeat rate

Total channel use: 0.1%: Low probability of RFI

Transmit Antenna Performance



Typical ZZLPA Pattern



Ionogram Analysis: Dynasonde21

Jicamarca, Peru : VIPIR ionogram : Dynasonde21 Analysis



Courtesy JRO and DSL

Dynasonde21

Dynasonde Ionogram Analysis



3D Echolocation



Structure Functions



EDP Time History



Dynasonde21 ©

Classical URSI scaled characteristics



Vector Velocities



Dynasonde is the name for methodology of ionospheric radio sounding based on the physical notion of radio echo and on a comprehensive use of phase information in it.

Echo is a physical object characterized by 7 physical parameters (two angles of arrival, group range, Doppler, polarization, phase range, amplitude) plus their uncertainties. Processing the list of the echoes instead of traditional amplitude-based image analysis is the distinctive property of a Dynasonde system. This technique turns radar into a measuring system, not merely imaging system.

Feature important for Acoustic Gravity Wave studies:

Precision measurements of the range and the angles of arrival for every echo.

NeXtYZ (“Next Wise”), 3-D Plasma Density Inversion Procedure

provides parameters of the Wedge Stratified Ionospheric Model. [Zabotin et al., Radio Sci., 2006]











Automatic Scaling Options





Autoscala from INGV

ESIR from SEC

Contact these vendors for terms and conditions of use for this software

Frequency Allocation

- Ionosonde is an active transmitting system
  - RF License needed
- Ionosonde frequency use is non-standard
  - Regulatory agencies used to HF comms allocations
  - Exclusive use of narrow band channels
- Antenna radiation pattern is Vertical Incidence
  - Little RFI beyond a few km
- Some 200 ionosondes have operated since 1930
  - Precedents exist

A bad frequency allocation can cripple the instrument

Frequency Allocation Issues

Ionosondes do not fit into standard frequency allocations

- 20 kHz bandwidth vs 5 kHz allocations

Exclusive Use vs Temporary Access

- Occupies any 5 kHz channel 1 second every minute

Complete MF-HF Spectrum coverage required

- At least 1-16 MHz

A few specific narrowband channels can be excluded

- Standard time frequencies (2.5, 5.0, 10.0, 15.0, 25.0 MHz)

Exclusion of whole bands is disastrous

- Aeronautical, Marine, Land Mobile, Fixed Terrestrial

Site-Specific allocations that address specific RFI issues are required!

Success: Wallops Island



Frequency Restrictions

Minor restrictions mitigate RFI while maintaining data integrity

Failure: Millstone Hill





Major restrictions destroy the integrity of the data

Results: Boulder Digisonde vs VIPIR



Improved Measurement Clarity

Boulder 1-minute Data



High Time Resolution Data

VIPIR can comfortably make 1 ionogram per min



arly

Plot of foF2 for 17 hours from the Millstone Hill Digisonde (Blue) and Hanscom VIPIR (Red)

Data courtesy of U.Mass Lowell and Boston College

How to optimally use these data?

Meteor Trails at 5.8 MHz



Plasma Turbulence



Structured E- layer

Smooth E- layer



Very Fast Sweeps

Ionogram sweeps < 10 seconds long



possible

VIPIR Facilities



Current (16)

Planned (7)

Updated May 2015

Internet Resources

- World Data Center A, Boulder: http://www.ngdc.noaa.gov/stp/IONO/ionohome.html
- Digisondes and ARTIST : http://ulcar.uml.edu/ http://www.digisonde.com/
- Autoscala: http://roma2.rm.ingv.it/en/facilities/software/18/autoscala
- ESIR : http://www.spacenv.com/
- Low-latitude Ionospheric Sensing System: http://jro.igp.gob.pe/lisn/
- Vertical Incidence Pulsed Ionosphere Radar (VIPIR): Terry.Bullett@noaa.gov
- Canadian Advanced Digital Ionosonde (CADI): http://cadiweb.physics.uwo.ca/
- Ionospheric Prediction Services (IPS): http://www.ips.gov.au/
- Ionosonde Network Advisory Group (INAG) http://www.ips.gov.au/IPSHosted/INAG/
- SPIDR: http://spidr.ngdc.noaa.gov/spidr/index.jsp
- Gravity Waves: http://surf.colorado.edu