

Appendix E. FORTRAN Language Program To Read an Archive Record

```
program testRead(arcfile,outfile)

    ! The program takes two arguments, specifying the
input    ! filename and the output filename (including paths.)
    ! The output file is written in the current working
directory ! unless a path is included as part of the filename.

    integer*2 j
    integer*4 rec,eof,hr,min,sec
    character*80 arcfile,outfile

    ! Common block /rec/ variables:
    integer*4 cSum,ihd(6,4)
    integer*2
cSumFlag,major,status(10),qual(16),minor(16),mdf(40,16)
    real*4
analog(17),head(27,4),ssLoc(2,16),mep0(9,16),mep90(9,16),
+
mepOmni(4,16),ted0(8,16),ted30(8,16),ted0s(8,4),ted30s(8,4),
+    tedback(2,4),tedfx(7,16)

    common /rec/cSum,ihd,cSumFlag,major,status,qual,minor,
+
mdf,analog,head,ssLoc,mep0,mep90,mepOmni,ted0,ted30,
+    ted0s,ted30s,tedback,tedfx

    eof = 0
    open(unit=7,access='direct',recl=2544,file =
arcfile,status='old')
    open(unit=11,access='sequential',file = outfile,
+        status='unknown',form='formatted')

    do rec = 1,3
        call readArcSub(7,rec,eof)
        if(eof.eq.1) goto 100
        do j=1,4
            hr = ihd(4,j)/3600000
            min = (ihd(4,j) - hr*3600000)/60000
            sec = (ihd(4,j) - hr*3600000 - min*60000)/1000
            write(11,200),ihd(2,j),ihd(3,j),hr,min,sec,
+                head(2,j),head(3,j),ihd(6,j)
        enddo
        write(11,300)"mep0:"
```

```

do j=1,16

write(11,220)j,mep0(1,j),mep0(2,j),mep0(3,j),mep0(4,j),
+
mep0(5,j),mep0(6,j),mep0(7,j),mep0(8,j),mep0(9,j)
enddo
write(11,300)"mep90:"
do j=1,16

write(11,220)j,mep90(1,j),mep90(2,j),mep90(3,j),
+
mep90(4,j),mep90(5,j),mep90(6,j),mep90(7,j),mep90(8,j),
+
mep90(9,j)
enddo
write(11,300)"mepOmni:"
do j=1,16

write(11,220)j,mepOmni(1,j),mepOmni(2,j),mepOmni(3,j),
+
mepOmni(4,j)
enddo
write(11,300)"ted0:"
do j=1,16

write(11,220)j,ted0(1,j),ted0(2,j),ted0(3,j),ted0(4,j),
+
ted0(5,j),ted0(6,j),ted0(7,j),ted0(8,j)
enddo
write(11,300)"ted30:"
do j=1,16

write(11,220)j,ted30(1,j),ted30(2,j),ted30(3,j),
+
ted30(4,j),ted30(5,j),ted30(6,j),ted30(7,j),
+
ted30(8,j)
enddo
write(11,300)"ted0s:"
do j=1,4

write(11,220)j,ted0s(1,j),ted0s(2,j),ted0s(3,j),
+
ted0s(4,j),ted0s(5,j),ted0s(6,j),ted0s(7,j),ted0s(8,j)
enddo
write(11,300)"ted30s:"
do j=1,4

write(11,220)j,ted30s(1,j),ted30s(2,j),ted30s(3,j),
+
ted30s(4,j),ted30s(5,j),ted30s(6,j),ted30s(7,j),
+
ted30s(8,j)

```

```

        enddo
        write(11,300)"tedback:"
        do j=1,4
            write(11,220)j,tedback(1,j),tedback(2,j)
        enddo
        write(11,300)"tedfx:"
        do j=1,16
write(11,220)j,tedfx(1,j),tedfx(2,j),tedfx(3,j),
+         tedfx(4,j),tedfx(5,j),tedfx(6,j),tedfx(7,j)
        enddo

        write(11,300)"-----
-----"

        enddo

200 format(i4,1x,i3,3(1x,i2),1x,f8.3,1x,f8.3,1x,i7)
220 format(i4,9(1x,f8.2))
300 format(A)
100 close(7)
    close(11)
end

```

```

subroutine readArcSub (unit,rnum,eof)

```

```

! -----
!
!   readArcSub.f returns a NOAA POES SEM2 data record
from an
!           already opened file in packed binary
format.
!
!   Calling from C:  It is recommended that C users
use the
!           C routine: unpackSem2.c instead.
!
!   Compilation: f77 -c readArcSub.f
!
!   Programmer:  Sue Greer
! -----
-----
byte arcBytes(2544)
integer*4 unit,rnum,eof,ios

```

```

integer*4 arc(2544),i,j,jj,k,m,mf,mo,mp0,mp90,qf,tf
integer*4 b1,b2,b3,b4
integer*2 onebyte
real*4 cf ! Conversion factor (.0001)
real*4 cnvrt(256)

! Common block /rec/ variables:
integer*4 cSum,ihd(6,4)
integer*2
cSumFlag,major,status(10),qual(16),minor(16),mdf(40,16)
real*4
analog(17),head(27,4),ssLoc(2,16),mep0(9,16),mep90(9,16),
+
mepOmni(4,16),ted0(8,16),ted30(8,16),ted0s(8,4),ted30s(8,4),
+
tedback(2,4),tedfx(7,16)

common /rec/cSum,ihd,cSumFlag,major,status,qual,minor,
+
mdf,analog,head,ssLoc,mep0,mep90,mepOmni,ted0,ted30,
+
ted0s,ted30s,tedback,tedfx

cf = 0.0001
b1=256*256*256
b2=256*256
b3=256
b4=1

data cnvrt
/0.0,1.0,2.0,3.0,4.0,5.0,6.0,7.0,8.0,9.0,10.0,11.0,
+12.0,13.0,14.0,15.0,16.0,17.0,18.0,19.0,20.0,21.0,22.0,23.0
,24.0,
+25.0,26.0,27.0,28.0,29.0,30.0,31.0,32.0,34.5,36.5,38.5,40.5
,42.5,
+44.5,46.5,48.5,50.5,53.0,56.0,59.0,62.0,65.5,69.5,73.5,77.5
,81.5,
+85.5,89.5,93.5,97.5,101.5,106.5,112.5,118.5,124.5,131.5,139
.5,
+147.5,155.5,163.5,171.5,179.5,187.5,195.5,203.5,213.5,225.5
,
+237.5,249.5,263.5,279.5,295.5,311.5,327.5,343.5,359.5,375.5
,

```

+391.5, 407.5, 427.5, 451.5, 475.5, 499.5, 527.5, 559.5, 591.5, 623.5
,
+655.5, 687.5, 719.5, 751.5, 783.5, 815.5, 855.5, 903.5, 951.5, 999.5
,
+1055.5, 1119.5, 1183.5, 1247.5, 1311.5, 1375.5, 1439.5, 1503.5, 156
7.5,
+1631.5, 1711.5, 1807.5, 1903.5, 1999.5, 2111.5, 2239.5, 2367.5, 249
5.5,
+2623.5, 2751.5, 2879.5, 3007.5, 3135.5, 3263.5, 3423.5, 3615.5, 380
7.5,
+3999.5, 4223.5, 4479.5, 4735.5, 4991.5, 5247.5, 5503.5, 5759.5, 601
5.5,
+6271.5, 6527.5, 6847.5, 7231.5, 7615.5, 7999.5, 8447.5, 8959.5, 947
1.5,
+9983.5, 10495.5, 11007.5, 11519.5, 12031.5, 12543.5, 13055.5, 1369
5.5,
+14463.5, 15231.5, 15999.5, 16895.5, 17919.5, 18943.5, 19967.5, 209
91.5,
+22015.5, 23039.5, 24063.5, 25087.5, 26111.5, 27391.5, 28927.5, 304
63.5,
+31999.5, 33791.5, 35839.5, 37887.5, 39935.5, 41983.5, 44031.5, 460
79.5,
+48127.5, 50175.5, 52223.5, 54783.5, 57855.5, 60927.5, 63999.5, 675
83.5,
+71679.5, 75775.5, 79871.5, 83967.5, 88063.5, 92159.5, 96255.5, 100
351.5,
+104447.5, 109567.5, 115711.5, 121855.5, 127999.5, 135167.5, 14335
9.5,
+151551.5, 159743.5, 167935.5, 176127.5, 184319.5, 192511.5, 20070
3.5,

```

+208895.5, 219135.5, 231423.5, 243711.5, 255999.5, 270335.5, 28671
9.5,

+303103.5, 319487.5, 335871.5, 352255.5, 368639.5, 385023.5, 40140
7.5,

+417791.5, 438271.5, 462847.5, 487423.5, 511999.5, 540671.5, 57343
9.5,

+606207.5, 638975.5, 671743.5, 704511.5, 737279.5, 770047.5, 80281
5.5,

+835583.5, 876543.5, 925695.5, 974847.5, 1023999.5, 1081343.5,

+1146879.5, 1212415.5, 1277951.5, 1343487.5, 1409023.5, 1474559.5
,

+1540095.5, 1605631.5, 1671167.5, 1753087.5, 1851391.5, 1949695.5
,

+1998848.0/

```

```

    eof = 0
    if (rnum.lt.1) goto 100

10 read(unit,rec=rnum,iostat=ios) arcBytes
    if(ios.ne.0) then
        eof = 1
        goto 100
    endif
    do i=1,2544
        ! Byte type goes from -128 to +127
        ! Convert to 8-bit integer
        onebyte = arcBytes(i)
        arc(i) = onebyte
        if(onebyte.lt.0) arc(i) = onebyte+256
    enddo

* -----
* -----
*      ! Parse the data in arc()
* -----
* -----

    ! Checksum flag
    cSumFlag = arc(1)*b1 + arc(2)*b2 + arc(3)*b3 + arc(4)
    ! Checksum

```

```

cSum = arc(5)*b1 + arc(6)*b2 + arc(7)*b3 + arc(8)
! Major frame number
major = arc(9)*b3 + arc(10)*b4
!print *, 'cSumFlag, cSum, MF ', cSumFlag, cSum, major

! Status: instrument on/off, ifc, etc.
do i = 1,10
    status(i) = arc(i+10)
    !print *, i, status(i)
enddo

! Analog data, etc. 4-byte integers converted to reals

do i = 1,68,4
    k = (i+1)/4 + 1
    analog(k) =
(arc(i+20)*b1+arc(i+21)*b2+arc(i+22)*b3+
+      arc(i+23))*cf
    !print *, k, analog(k)
enddo

! Sub-satellite location, 4-byte integers converted to
reals
k = 1
ssLoc(1,1) = (arc(k+88)*b1+arc(k+89)*b2+arc(k+90)*b3+
+      arc(k+91))*cf
ssLoc(1,2) = (arc(k+92)*b1+arc(k+93)*b2+arc(k+94)*b3+
+      arc(k+95))*cf
ssLoc(1,3) = (arc(k+96)*b1+arc(k+97)*b2+arc(k+98)*b3+
+      arc(k+99))*cf
ssLoc(1,4) =
(arc(k+100)*b1+arc(k+101)*b2+arc(k+102)*b3+
+      arc(k+103))*cf
ssLoc(2,1)
=(arc(k+104)*b1+arc(k+105)*b2+arc(k+106)*b3+
+      arc(k+107))*cf
ssLoc(2,2)
=(arc(k+108)*b1+arc(k+109)*b2+arc(k+110)*b3+
+      arc(k+111))*cf
ssLoc(2,3)
=(arc(k+112)*b1+arc(k+113)*b2+arc(k+114)*b3+
+      arc(k+115))*cf
ssLoc(2,4)
=(arc(k+116)*b1+arc(k+117)*b2+arc(k+118)*b3+
+      arc(k+119))*cf
ssLoc(1,5) =
(arc(k+120)*b1+arc(k+121)*b2+arc(k+122)*b3+

```

```

+      arc(k+123))*cf
  ssLoc(1,6) =
(arc(k+124)*b1+arc(k+125)*b2+arc(k+126)*b3+
+      arc(k+127))*cf
  ssLoc(1,7) =
(arc(k+128)*b1+arc(k+129)*b2+arc(k+130)*b3+
+      arc(k+131))*cf
  ssLoc(1,8) =
(arc(k+132)*b1+arc(k+133)*b2+arc(k+134)*b3+
+      arc(k+135))*cf
  ssLoc(2,5)
=(arc(k+136)*b1+arc(k+137)*b2+arc(k+138)*b3+
+      arc(k+139))*cf
  ssLoc(2,6)
=(arc(k+140)*b1+arc(k+141)*b2+arc(k+142)*b3+
+      arc(k+143))*cf
  ssLoc(2,7)
=(arc(k+144)*b1+arc(k+145)*b2+arc(k+146)*b3+
+      arc(k+147))*cf
  ssLoc(2,8)
=(arc(k+148)*b1+arc(k+149)*b2+arc(k+150)*b3+
+      arc(k+151))*cf
  ssLoc(1,9) =
(arc(k+152)*b1+arc(k+153)*b2+arc(k+154)*b3+
+      arc(k+155))*cf
  ssLoc(1,10) =
(arc(k+156)*b1+arc(k+157)*b2+arc(k+158)*b3+
+      arc(k+159))*cf
  ssLoc(1,11) =
(arc(k+160)*b1+arc(k+161)*b2+arc(k+162)*b3+
+      arc(k+163))*cf
  ssLoc(1,12) =
(arc(k+164)*b1+arc(k+165)*b2+arc(k+166)*b3+
+      arc(k+167))*cf
  ssLoc(2,9)
=(arc(k+168)*b1+arc(k+169)*b2+arc(k+170)*b3+
+      arc(k+171))*cf
  ssLoc(2,10)
=(arc(k+172)*b1+arc(k+173)*b2+arc(k+174)*b3+
+      arc(k+175))*cf
  ssLoc(2,11)
=(arc(k+176)*b1+arc(k+177)*b2+arc(k+178)*b3+
+      arc(k+179))*cf
  ssLoc(2,12)
=(arc(k+180)*b1+arc(k+181)*b2+arc(k+182)*b3+
+      arc(k+183))*cf

```

```

      ssLoc(1,13) =
(arc(k+184)*b1+arc(k+185)*b2+arc(k+186)*b3+
+      arc(k+187))*cf
      ssLoc(1,14) =
(arc(k+188)*b1+arc(k+189)*b2+arc(k+190)*b3+
+      arc(k+191))*cf
      ssLoc(1,15) =
(arc(k+192)*b1+arc(k+193)*b2+arc(k+194)*b3+
+      arc(k+195))*cf
      ssLoc(1,16) =
(arc(k+196)*b1+arc(k+197)*b2+arc(k+198)*b3+
+      arc(k+199))*cf
      ssLoc(2,13)
=(arc(k+200)*b1+arc(k+201)*b2+arc(k+202)*b3+
+      arc(k+203))*cf
      ssLoc(2,14)
=(arc(k+204)*b1+arc(k+205)*b2+arc(k+206)*b3+
+      arc(k+207))*cf
      ssLoc(2,15)
=(arc(k+208)*b1+arc(k+209)*b2+arc(k+210)*b3+
+      arc(k+211))*cf
      ssLoc(2,16)
=(arc(k+212)*b1+arc(k+213)*b2+arc(k+214)*b3+
+      arc(k+215))*cf

```

```

* -----
*      ! Header information
* -----
      ! Subsatellite latitude and longitude
      head(2,1) = ssLoc(1,1)
      head(2,2) = ssLoc(1,5)
      head(2,3) = ssLoc(1,9)
      head(2,4) = ssLoc(1,13)
      head(3,1) = ssLoc(2,1)
      head(3,2) = ssLoc(2,5)
      head(3,3) = ssLoc(2,9)
      head(3,4) = ssLoc(2,13)

      do j = 1,4
        m = 3
        i = 1640+(j-1)*96
        do k = 4,96,4
          m = m+1
          head(m,j) = (arc(i+1+k-4)*b1 + arc(i+2+k-4)*b2
+
+      arc(i+3+k-4)*b3 + arc(i+4+k-4))*cf

```

```

        enddo
    enddo

    j = 1      ! Index for 8-second records
    ! ihd info, 4-byte integers (1..5,1)
    do i=1,20,4
        k = (i+1)/4 +1
        ihd(k,j) =
(arc(i+216)*b1+arc(i+217)*b2+arc(i+218)*b3+
+      arc(i+219))
        enddo
        ! Inclination (head(1,1))
        head(1,j) = (arc(237)*b1+arc(238)*b2+arc(239)*b3+
+      arc(240))*cf/10.
        ! Orbit number (6,1)
        ihd(6,j) = (arc(241)*b1+arc(242)*b2+arc(243)*b3+
+      arc(244))
        ! Quality, 2-byte integer (1..4)
        qf = 1
        do i=1,7,2
            qual(qf) = arc(i+244)*b3+arc(i+245)
            qf = qf + 1
        enddo
        ! Minor frame numbers (1..4)
        mf = 1
        do i = 1,7,2
            minor(mf) = arc(i+252)*b3+arc(i+253)
            mf = mf+1
        enddo
        ! Missing data flags (1..40,1..4)
        do i = 1,4
            do n = 1,40
                mdf(n,i) = arc(n-1+40*(i-1)+261)
            enddo
        enddo

    j = 2
    ! ihd info, 4-byte integers (1..5,2)
    do i=1,20,4
        k = (i+1)/4 +1
        ihd(k,j) =
(arc(i+420)*b1+arc(i+421)*b2+arc(i+422)*b3+
+      arc(i+423))
        enddo
        ! Inclination (head(1,2))
        head(1,j) = (arc(441)*b1+arc(442)*b2+arc(443)*b3+
+      arc(444))*cf/10.

```

```

! Orbit number (ihd(6,2))
ihd(6,j) = (arc(445)*b1+arc(446)*b2+arc(447)*b3+
+         arc(448))
! Quality, 2-byte integer (5..8)
do i=1,7,2
    qual(qf) = arc(i+448)*b3+arc(i+449)
    qf = qf + 1
enddo
! Minor frame numbers (5..8)
do i = 1,7,2
    minor(mf) = arc(i+456)*b3+arc(i+457)
    mf = mf+1
enddo
! Missing data flags (1..40,5..8)
do i = 5,8
    do n = 1,40
        mdf(n,i) = arc(n-1+40*(i-5)+465)
    enddo
enddo

j = 3
! ihd info, 4-byte integers (1..5,3)
do i=1,20,4
    k = (i+1)/4 +1
    ihd(k,j) =
(arc(i+624)*b1+arc(i+625)*b2+arc(i+626)*b3+
+         arc(i+627))
enddo
! Inclination (head(1,3))
head(1,j) = (arc(645)*b1+arc(646)*b2+arc(647)*b3+
+         arc(648))*cf/10.
! Orbit number (ihd(6,3))
ihd(6,j) = (arc(649)*b1+arc(650)*b2+arc(651)*b3+
+         arc(652))
! Quality, 2-byte integer (9..12)
do i=1,7,2
    qual(qf) = arc(i+652)*b3+arc(i+653)
    qf = qf + 1
enddo
! Minor frame numbers (9..12)
do i = 1,7,2
    minor(mf) = arc(i+660)*b3+arc(i+661)
    mf = mf+1
enddo
! Missing data flags (1..40,9..12)
do i = 9,12
    do n = 1,40

```

```

        mdf(n,i) = arc(n-1+40*(i-9)+669)
    enddo
enddo

j = 4
! ihd info, 4-byte integers (1..5,4)
do i=1,20,4
    k = (i+1)/4 +1
    ihd(k,j) =
(arc(i+828)*b1+arc(i+829)*b2+arc(i+830)*b3+
+      arc(i+831))
    enddo
! Inclination (head(1,4))
head(1,j) = (arc(849)*b1+arc(850)*b2+arc(851)*b3+
+      arc(852))*cf/10.
! Orbit number (ihd(6,4))
ihd(6,j) = (arc(853)*b1+arc(854)*b2+arc(855)*b3+
+      arc(856))
! Quality, 2-byte integer (13..16)
do i=1,7,2
    qual(qf) = arc(i+856)*b3+arc(i+857)
    qf = qf + 1
enddo
! Minor frame numbers (13..16)
do i = 1,7,2
    minor(mf) = arc(i+864)*b3+arc(i+865)
    mf = mf+1
enddo
! Missing data flags (1..40,13..16)
do i = 13,16
    do n = 1,40
        mdf(n,i) = arc(n-1+40*(i-13)+873)
    enddo
enddo

```

```

* -----
*      ! MEPED sensor data
* -----

j = 1
mp0 = 1
! Meped 0-deg telescope (1..9,1..4)
do i = 1,4
    jj = (j-1)*4+i
    do k = 1,9
        if(mdf(k+1,jj).eq.1) then
            mep0(k,jj) = -999.
        else

```

```

        mep0(k,jj) = cnvrt(1+arc(mp0+1032))
    endif
    mp0 = mp0+1
enddo
enddo
! Meped 90-deg telescope (1..9,1..4)
mp90 = 1
do i = 1,4
    jj = (j-1)*4+i
    do k = 1,9
        if(mdf(k+10,jj).eq.1) then
            mep90(k,jj) = -999.
        else
            mep90(k,jj) = cnvrt(1+arc(mp90+1068))
        endif
        mp90 = mp90+1
    enddo
enddo
! Meped omnidirectional (1..4,1..4)
mo = 1
do i = 1,4
    jj = (j-1)*4+i
    do k = 1,4
        mepOmni(k,jj) = cnvrt(1+arc(mo+1104))
        mo = mo+1
    enddo
    if(mdf(20,jj).eq.1) mepOmni(1,jj) = -999.
    if(mdf(21,jj).eq.1) mepOmni(2,jj) = -999.
    if(mod(jj,2).eq.1.AND.mdf(22,jj).eq.1)
mepOmni(3,jj) = -999.
    if(mod(jj,2).eq.0.AND.mdf(22,jj).eq.1)
mepOmni(4,jj) = -999.
    enddo

j = 2
mp0 = 1
! Meped 0-deg telescope (1..9,5..8)
do i = 1,4
    jj = (j-1)*4+i
    do k = 1,9
        if(mdf(k+1,jj).eq.1) then
            mep0(k,jj) = -999.
        else
            mep0(k,jj) = cnvrt(1+arc(mp0+1184))
        endif
        mp0 = mp0+1
    enddo

```

```

        enddo
        ! Meped 90-deg telescope (1..9,5..8)
        mp90 = 1
        do i = 1,4
            jj = (j-1)*4+i
            do k = 1,9
                if(mdf(k+10,jj).eq.1) then
                    mep90(k,jj) = -999.
                else
                    mep90(k,jj) = cnvrt(1+arc(mp90+1220))
                endif
                mp90 = mp90+1
            enddo
        enddo
        ! Meped omnidirectional (1..4,5..8)
        mo = 1
        do i = 1,4
            jj = (j-1)*4+i
            do k = 1,4
                mepOmni(k,jj) = cnvrt(1+arc(mo+1256))
                mo = mo+1
            enddo
            if(mdf(20,jj).eq.1) mepOmni(1,jj) = -999.
            if(mdf(21,jj).eq.1) mepOmni(2,jj) = -999.
            if(mod(jj,2).eq.1.AND.mdf(22,jj).eq.1)
mepOmni(3,jj) = -999.
            if(mod(jj,2).eq.0.AND.mdf(22,jj).eq.1)
mepOmni(4,jj) = -999.
        enddo

        j = 3
        mp0 = 1
        ! Meped 0-deg telescope (1..9,9..12)
        do i = 1,4
            jj = (j-1)*4+i
            do k = 1,9
                if(mdf(k+1,jj).eq.1) then
                    mep0(k,jj) = -999.
                else
                    mep0(k,jj) = cnvrt(1+arc(mp0+1336))
                endif
                mp0 = mp0+1
            enddo
        enddo
        ! Meped 90-deg telescope (1..9,9..12)
        mp90 = 1
        do i = 1,4

```

```

        jj = (j-1)*4+i
        do k = 1,9
            if(mdf(k+10,jj).eq.1) then
                mep90(k,jj) = -999.
            else
                mep90(k,jj) = cnvrt(1+arc(mp90+1372))
            endif
            mp90 = mp90+1
        enddo
    enddo
! Meped omnidirectional (1..4,9..12)
mo = 1
do i = 1,4
    jj = (j-1)*4+i
    do k = 1,4
        mepOmni(k,jj) = cnvrt(1+arc(mo+1408))
        mo = mo+1
    enddo
    if(mdf(20,jj).eq.1) mepOmni(1,jj) = -999.
    if(mdf(21,jj).eq.1) mepOmni(2,jj) = -999.
    if(mod(jj,2).eq.1.AND.mdf(22,jj).eq.1)
mepOmni(3,jj) = -999.
    if(mod(jj,2).eq.0.AND.mdf(22,jj).eq.1)
mepOmni(4,jj) = -999.
    enddo

j = 4
mp0 = 1
! Meped 0-deg telescope (1..9,13..16)
do i = 1,4
    jj = (j-1)*4+i
    do k = 1,9
        if(mdf(k+1,jj).eq.1) then
            mep0(k,jj) = -999.
        else
            mep0(k,jj) = cnvrt(1+arc(mp0+1488))
        endif
        mp0 = mp0+1
    enddo
enddo
! Meped 90-deg telescope (1..9,13..16)
mp90 = 1
do i = 1,4
    jj = (j-1)*4+i
    do k = 1,9
        if(mdf(k+10,jj).eq.1) then
            mep90(k,jj) = -999.

```

```

        else
            mep90(k,jj) = cnvrt(1+arc(mp90+1524))
        endif
        mp90 = mp90+1
    enddo
enddo
! Meped omnidirectional (1..4,13..16)
mo = 1
do i = 1,4
    jj = (j-1)*4+i
    do k = 1,4
        mepOmni(k,jj) = cnvrt(1+arc(mo+1560))
        mo = mo+1
    enddo
    if(mdf(20,jj).eq.1) mepOmni(1,jj) = -999.
    if(mdf(21,jj).eq.1) mepOmni(2,jj) = -999.
    if(mod(jj,2).eq.1.AND.mdf(22,jj).eq.1)
mepOmni(3,jj) = -999.
        if(mod(jj,2).eq.0.AND.mdf(22,jj).eq.1)
mepOmni(4,jj) = -999.
    enddo

* -----
*      TED uncalibrated energy flux, max channel
*      response, and max channel
* -----

! TED 0-deg and 30-deg uncalibrated energy flux
do k=1,4
    do i = 1,4
        j = (k-1)*4 + i  !(1..16)
        ted0(1,j) = cnvrt(1+arc(1121+(i-1)*4+(k-
1)*152))
        if(mdf(27,j).eq.1) ted0(1,j) = -999.
        ted0(2,j) = cnvrt(1+arc(1122+(i-1)*4+(k-
1)*152))
        if(mdf(29,j).eq.1) ted0(2,j) = -999.
        ted0(3,j) = cnvrt(1+arc(1123+(i-1)*4+(k-
1)*152))
        if(mdf(31,j).eq.1) ted0(3,j) = -999.
        ted0(4,j) = cnvrt(1+arc(1124+(i-1)*4+(k-
1)*152))
        if(mdf(33,j).eq.1) ted0(4,j) = -999.
        ted0(5,j) = 1+arc(1137+(i-1)*4+(k-1)*152)
        ted0(6,j) = 1+arc(1138+(i-1)*4+(k-1)*152)

        if(mdf(35,j).eq.1) then

```

```

        ted0(5,j) = -999.
        ted0(6,j) = -999.
    endif
    ted0(7,j) = cnvrt(1+arc(1139+(i-1)*4+(k-
1)*152))
    if(mdf(36,j).eq.1) ted0(7,j) = -999.
    ted0(8,j) = cnvrt(1+arc(1140+(i-1)*4+(k-
1)*152))
    if(mdf(37,j).eq.1) ted0(8,j) = -999.

    ted30(1,j) = cnvrt(1+arc(1153+(i-1)*4+(k-
1)*152))
    if(mdf(28,j).eq.1) ted30(1,j) = -999.
    ted30(2,j) = cnvrt(1+arc(1154+(i-1)*4+(k-
1)*152))
    if(mdf(30,j).eq.1) ted30(2,j) = -999.
    ted30(3,j) = cnvrt(1+arc(1155+(i-1)*4+(k-
1)*152))
    if(mdf(32,j).eq.1) ted30(3,j) = -999.
    ted30(4,j) = cnvrt(1+arc(1156+(i-1)*4+(k-
1)*152))
    if(mdf(34,j).eq.1) ted30(4,j) = -999.
    ted30(5,j) = 1+arc(1169+(i-1)*4+(k-1)*152)
    ted30(6,j) = 1+arc(1170+(i-1)*4+(k-1)*152)
    if(mdf(38,j).eq.1) then
        ted30(5,j) = -999.
        ted30(6,j) = -999.
    endif
    ted30(7,j) = cnvrt(1+arc(1171+(i-1)*4+(k-
1)*152))
    if(mdf(39,j).eq.1) ted30(7,j) = -999.
    ted30(8,j) = cnvrt(1+arc(1172+(i-1)*4+(k-
1)*152))
    if(mdf(40,j).eq.1) ted30(8,j) = -999.
    enddo
enddo

* -----
*      ! Ted spectra and background
* -----

    do j = 1,4
        do i=1,8
            ted0s(i,j) = cnvrt(1+arc(i+(j-1)*8+2024))
            ted30s(i,j) = cnvrt(1+arc(i+(j-1)*8+2060))
        enddo
        tedback(1,j) = cnvrt(1+arc(j+2056))
        tedback(2,j) = cnvrt(1+arc(j+2092))
    enddo

```

```

enddo
do j=1,16
  if(j.eq.1.OR.j.eq.5.OR.j.eq.9.OR.j.eq.13) then
    do i=1,4
      if(mdf(22+i,j).eq.1) then
        do k=1,4
          ted0s(i,k) = -999.
        enddo
      endif
    enddo
  endif
  if(j.eq.3.OR.j.eq.7.OR.j.eq.11) then
    do i=5,8
      if(mdf(18+i,j).eq.1)then
        do k=1,4
          ted0s(i,k) = -999.
        enddo
      endif
    enddo
  endif
  if(j.eq.2.OR.j.eq.6.OR.j.eq.10.OR.j.eq.14) then
    do i=1,4
      if(mdf(22+i,j).eq.1)then
        do k=1,4
          ted30s(i,k) = -999.
        enddo
      endif
    enddo
  endif
  if(j.eq.4.OR.j.eq.8.OR.j.eq.12) then
    do i=5,8
      if(mdf(18+i,j).eq.1)then
        do k=1,4
          ted30s(i,k) = -999.
        enddo
      endif
    enddo
  endif
  if(j.eq.15) then
    if(mdf(1,j).eq.1) tedback(1,1) = -999.
    if(mdf(23,j).eq.1) tedback(1,2) = -999.
    if(mdf(26,j).eq.1) tedback(1,3) = -999.
    if(mdf(25,j).eq.1) tedback(1,4) = -999.
    if(mdf(24,j).eq.1) tedback(2,2) = -999.
  endif
  if(j.eq.16) then
    if(mdf(1,j).eq.1) tedback(2,1) = -999.
  endif
enddo

```

```

            if(mdf(2,3).eq.1) tedback(2,3) = -999.
            if(mdf(24,j).eq.1) tedback(2,4) = -999.
        endif
    enddo
* -----
*      ! Ted flux
* -----
    tf = 1
    do i=1,4
        do n = 1,7
            do j = 1,4
                k = (i-1)*4 + j
                tedfx(n,k) = (arc(tf+2096)*b1 +
+                               arc(tf+2097)*b2 +
+                               arc(tf+2098)*b3 +
+                               arc(tf+2099))*cf
                tf = tf + 4
            !print *,n,k,tf+2096
            enddo
        enddo
    enddo
* -----
*      ! Check missing data flags
* -----

100 continue
    return
end

```

