

U.S. DEPARTMENT OF COMMERCE  
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION  
NATIONAL OCEAN SERVICE

## DATA ACQUISITION AND PROCESSING REPORT

*Type of Survey:* Navigable Area / Homeland Security

*Time Frame:* 2003 Field Season

2003

**CHIEF OF PARTY**

**LCDR P. Tod Schattgen, NOAA**

**LIBRARY & ARCHIVES**

**DATE:** \_\_\_\_\_

## **Data Acquisition and Processing Report to Accompany 2003 Hydrographic Surveys**

### **NOAA Ship RUDE (s590) LCDR Andrew L. Beaver, NOAA, Commanding**

#### **A. EQUIPMENT**

##### **A.1 Platforms**

All data are acquired from NOAA Ship RUDE (s590, EDP #9040) and NOAA Survey Launch 1419. RUDE is equipped with multi-beam, vertical beam echosounders, and side scan sonar. Launch 1419 is equipped with vertical beam echosounders and side scan sonar. RUDE is a Class V Hydrographic Survey Ship, 90 feet in length overall, with a 22-foot beam and 7-foot draft. Launch 1419 is a 23-foot SeaArk aluminum launch, with an 8.5 foot beam, and 1.5 foot draft. Refer to Appendix III for more detailed vessel descriptions and equipment positioning diagrams.

##### **A.2 Sounding Instruments**

###### Vertical Beam Echo Sounder

RUDE and Launch 1419 are equipped with Odom Echotrac DF3200 MKII Dual Frequency Vertical-Beam Echosounders (VBES) configured for 24 and 200 kHz operation. Both frequencies are digitized and recorded at 5 Hz. Actual ping rates are dependent on the depth of water. Aboard RUDE, the VBES provides soundings during side scan sonar acquisition and quality control for the ship's multi-beam echosounder system (see below). On Launch 1419, the VBES is the primary sounding instrument.

On each platform, VBES data is logged by the Hypack software package (see section A.5 below), but paper records are acquired and retained for comparison with digitized depths during processing.

The VBES data are acquired in conjunction with side scan sonar or multi-beam echo sounder acquisition. Side Scan Sonar line spacing is dictated by the acquisition requirements of the survey. Multibeam echosounder data are acquired during shoal developments with a typical line spacing of 10 meters.

###### Shallow Water Multi-Beam Echosounder

RUDE is equipped with a RESON Seabat 8125 Shallow Water Multi-Beam Sonar System (SWMB). The SWMB is a 455 kHz multi-beam sonar designed for water depths of up to 248 meters. The 8125 utilizes an integrated transmit/receive head, which is pole mounted on the port side of the vessel. The 8125 projects a single transmit pulse, which is formed on receive into 240

beams, each  $0.5^\circ$  (across track) by  $1.0^\circ$  (along track). Due to incomplete water column characterization and shallow grazing angles the outer beams, (beams 1-22 and 225-240) are rejected during post-acquisition processing. The ping rate for the 8125 is 40.05 Hz to 3.02 Hz, depending on range scale. The 8125 transmit power level and Time Varied Gain (TVG) receiver gain controls are adjusted to minimize returns from water column clutter and surface reflection. The 8125 Depth filters are adjusted to remove aberrant shallow and deep returns during acquisition. During SWMB data acquisition, the ship is operated at speeds resulting in a minimum of 3.2 pings / 3 meters along track bottom coverage. The 8125 generates digital sounding data and backscatter that is logged by the ISIS software package (see section A.5 below).

A reference surface test was conducted in spring 2003 to assess the precision of the SWMB system. This test showed that under the prevailing conditions at that time and location, RUDE's sonar systems exceeded the International Hydrographic Organization "Special Order" specification. See the report attached in Appendix V for complete results. During data acquisition SWMB outer beams, and VBES or Nadir beams are continuously compared using the ISIS "Bathymetry Confidence" utility.

To achieve 100% MultiBeam Echosounder (MBES) coverage, lines are run parallel to bottom contours at spacing of approximately  $2\frac{1}{2}$  times the water depth. After initial acquisition, coverage plots are generated and reviewed, and additional lines are planned to fill any gaps.

#### Side Scan Sonar

RUDE and Launch 1419 carry Klein 5000 High Speed High Resolution Side Scan Sonar (HSHRSSH) towfish and Klein 3000 dual frequency towfish, respectively. All Klein 5000 side-scan sonar data are recorded digitally from the Transceiver and Processing Unit 5105 (TPU) using the ISIS software and archived in the Extended Triton Format (\*.XTF) files (see section A.5). All Klein 3000 side-scan sonar data are recorded digitally from the TPU using the SonarPro software and archived in the SonarPro Data Format (\*.SDF). KLEIN 5000 towfish transmits at 500 kHz. KLEIN 3000 towfish transmits at 100 kHz and 500 kHz.

RUDE's ship wake turbulence limits SSS acquisition by RUDE to depths greater than approximately 8 meters. SSS from Launch 1419 is similarly limited to depths greater than roughly 4 meters.

Side scan sonar lines are planned to run parallel to bottom contours, spaced according to the range scale appropriate for the water depth. Range scale of 75 meters is selected based on the Homeland Security project instructions. Lines are planned with 15m of overlap with adjacent swaths on either side.

Vessel speed is adjusted to ensure that an object one meter in characteristic size would be detected and clearly imaged across the sonar swath. Confidence checks are performed and noted frequently to ensure this standard of resolution is met.

#### Lead Line

A lead line was used to confirm the calibration of RUDE's VBES and SWMB systems in the spring of 2003. This test showed that under the conditions at the time of the calibration, RUDE's sonar systems exceed the IHO "Special Order" specification. See the report attached in Appendix V for complete results.

#### Diver Least Depth Gauge

RUDE divers were equipped with a diver least depth gauge for item investigations. The calibration report is included in Appendix V. The accuracy of RUDE's diver least depth gauge was also assessed as part of the Lead Line comparison test mentioned above.

### **A.3 Positioning and Attitude Instruments**

#### **RUDE**

##### POS/MV 320

RUDE's primary positioning and attitude sensor is a POS/MV Model 320 Ver. 3. This system combines data from an inertial attitude sensor and carrier-phase GPS receivers to compute position, heading, heave, pitch, and roll to the accuracy required for shallow water multibeam sonar surveys. The three major components of the POS/MV are: an Inertial Measurement Unit (IMU) mounted at the ship's center of motion; two GPS antennas on the ship's mast mounted perpendicular to the line of the ship; and a Pos Computer System (PCS) processing unit on the bridge.

Differential GPS corrector input from an external source is required. These correctors are brought in with GPS data from the Trimble GPS system. The GPS receivers in the POS/MV processor compute RUDE's position and heading by measuring the phase difference of the GPS signals arriving at the two antennas and computing the vector between them. The resulting GPS position is corrected for the lever arm from the antennas to the center of motion. The GPS heading data and linear and angular acceleration values from the IMU are processed through Kalman filtering. This filter is designed to produce output that reflects high frequency changes in vessel position and attitude as measured by the IMU while constraining the drift of this sensor with the long-term stability of GPS.

Heave is computed by double integration of acceleration in the vertical axis as measured by the IMU. Since this measurement is subject to long term drift, the

data are high pass filtered with a rolloff frequency and damping coefficient selected to stabilize the measurement while preserving the phase and amplitude of the ship's vertical position in sea states anticipated in RUDE's area of operations.

All data are corrected to the position of the IMU. The final position, heave, and attitude data are output to the Hypack and Isis data acquisition systems via RS-232 serial. This correction data is stored within the Hypack and Isis output data files. The POS/MV system is configured for 20 Hz output of the "TSS" Heave / Roll / Pitch message and 5 Hz output of the NMEA-0183 GGA and HDT messages. (See POS/MV settings Appendix II).

#### Trimble DSM-212L

RUDE's auxiliary positioning system is a Trimble DSM-212L DGPS receiver. The DSM-212L is an integrated unit combining a 12 channel L1 C/A code receiver with a 2 channel Differential Beacon receiver. This unit is used primarily to receive USCG Differential Beacon messages, which are passed with GPS data to the POS/MV auxiliary input. Although the DSM-212L has the ability to automatically select stations based on signal strength or geographic proximity, the receiver is manually tuned to avoid unexpected and undocumented changes in the differential beacon in use.

Position, time, and velocity data from the Trimble is available in a 1 Hz NMEA message as an auxiliary input to the POS/MV. The DSM-212L is configured using the "TSIP Talker" software to suspend output in the event NOS Hydrographic Position Control specifications are not met.

#### Magnavox MX-50

The MX-50 is a manually tuned single channel differential beacon receiver that is carried as a backup to the Trimble DSM-212L

#### Yokogawa CMZ700S Gyrocompass

RUDE is equipped with a Yokogawa CMZ700S gyrocompass. This instrument serves primarily as a heading reference for navigation.

### **LAUNCH 1419**

#### Starlink DNAV-212

Launch 1419 is equipped with primary and backup Starlink DNAV-212 DGPS receivers, which provide position, timing, velocity, and course. The Starlink is an integrated 12 Channel L1 C/A code and 2 Channel Differential Beacon receiver. The Starlink receivers are configured with the "Starinit" software to suspend output in the event NOS Hydrographic Position Control specifications are not met, and manually tune the differential beacon receiver to the desired

frequency. The Starlink receivers produce the NMEA-0183 GGA and VTG messages at 1 Hz.

#### S.G. Brown Meridian Surveyor Gyrocompass

Launch 1419 is equipped with an S.G. Brown Meridian Surveyor gyrocompass. This instrument serves as a heading reference for navigation and its output is fed to the hydrographic survey systems as well. The Meridian Surveyor is configured to deliver the NMEA-0183 HDT message at 10 Hz.

#### Heave and Attitude

Launch 1419's primary positioning and attitude sensor is a TSS Dynamic Motion Sensor DMS05. This system combines data from an inertial attitude sensor and carrier-phase GPS receivers to compute position, heading, heave, pitch, and roll to the accuracy required for shallow water vertical beam sonar surveys. The major component of the DMS05 is a Linear Accelerometer Array mounted amidships on the boat's port side.

GPS speed and vessel track information from the DNAV-212 GPS receiver is utilized by the DMS05 for calculations during vessel turns. The GPS speed is used in the calculation to determine the value for centripetal acceleration. The GPS vessel track information provides a reference for the vertical rate sensors to eliminate the affects of drift or accumulative errors in the measurement of the rate of turn ( $\omega$ ) and allows a more accurate assessment of the magnitude of centripetal acceleration. The GPS input becomes ineffective if the vessel speed falls below 1 meter/sec.

Heave is computed by double integration of the output from the linear accelerometer array. A filtering action takes place after each integration to limit the low frequency response of the system and to allow recovery from the erroneous effects of random noise and horizontal acceleration. A bandwidth period of 12 seconds was chosen to optimize the phase and amplitude of the vessel's vertical position to sea states anticipated in Launch 1419's area of operations.

The final heading, position, heave, and attitude data are output to the Hypack data acquisition system via RS-232 serial. The SonarPro system receives GPS information only.

## **A.4 Ancillary Instruments**

#### Sound Velocity

Conductivity, temperature, and depth profiles are acquired using two Seabird Seacat SBE-19 Conductivity, Temperature, and Depth (CTD) profilers. The SBE-19 is a self-contained, battery-powered unit with a serial interface for

configuration and data download. RUDE's SBE-19's are equipped with a 300 psi pressure gauge to provide high resolution data in the relatively shallow water typical of RUDE's areas of operations. Sound velocity files in CARIS format are computed using the "Velociwin" software described in section A.5.

During MBES data acquisition, CTD casts are conducted when starting work in an area and every 4 hours thereafter, or when the surface sound velocity is observed to have drifted outside accepted limits as discussed below. For VBES data, casts are conducted weekly or when survey personnel suspect a significant change in the properties of the water column. The calibration records are included in the Appendix V.

Surface sound velocity is continuously monitored during acquisition with an Odom Hydrographic Digibar Pro sound velocimeter. The velocimeter is mounted just above the multibeam transducer head. During MBES data acquisition, a new CTD cast is taken if the surface sound velocity is observed to have changed more than +/-2 m/s from its value at the last CTD cast. The calibration records for this instrument are included in Appendix V.

Monthly comparisons of the two Seacat CTDs and weekly comparisons between the CTD in use and the Digibar Pro are conducted to monitor data quality from these instruments.

#### Cable Counter

RUDE is equipped with an MD Totco Cable counter that measures the side scan towfish tow cable by counting revolutions of the towing block on the A-frame. The length of cable deployed is computed automatically and output to Hypack.

Launch 1419 cable counter is a Dynapar Max. The counter measures towfish cable out by counting revolutions of the towing block on the J-arm. The output is sent to Hypack through serial connection and read by the operator to be manually input into the SonarPro software.

#### Bottom Sampler

Where required by project instructions, RUDE personnel acquire sediment samples from the sea floor in the survey area. The primary tool for this operation is a "clamshell" style gravity-closed sediment sampler, which penetrates approximately 0.05m into the bottom.

### **A.5 Data Acquisition and Processing Software**

Coastal Oceanographics Hypack Max is used for survey navigation, Detached Positioning (DP), and VBES data logging. Hypack is also used for overall data acquisition control, and passes file names, line start and end messages, and fix numbers to ISIS via a serial link. In addition, during side scan sonar operations,

Hypack collects cable out data and computes towfish position, which, along with raw water depth from the VBES, is also passed to ISIS.

Shallow Water Multibeam and Side Scan Sonar data are collected in the Triton Elics International ISIS software package (v5.84) and logged in the “eXtended Triton Format (.xtf) file format. Because of improved timing precision, vessel position is logged to the “sensor” field of the XTF data structure, and towfish position, if present, is recorded in the “ship” position. Water depth, required for recomputation of towfish position, is stored in “Aux 1”. Cable count is recorded in the “cable out” field.

The PCs running Hypack and Isis are automatically synchronized to UTC time from the NMEA-0183 GPS messages. The time update occurs during the start and stop logging messages on the Hypack computer and during the start logging message on the Isis computer.

CTD casts are downloaded and processed in the Velociwin program supplied by the Hydrographic Systems and Technology Program (HSTP). This software is also used to process diver’s least depth gauge readings.

Preliminary tide data is either directly collected from the Center for Operational Oceanographic Products and Services’ web site, or sent to RUDE via the “Tidebot” automated tides email system. Verified tides are downloaded from the CO-OPS web site as they become available. All tide data is zone corrected using either MapInfo’s ZDF file creation utility or HSTP’s “HP Tools” software.

All sonar data is processed in the CARIS HIPS system.

Processed soundings, side scan sonar contacts, dives, and DPs are inserted and analyzed in HSTP’s “Pydro” software. This system is used for all feature assessment and bathymetry excessing.

Final plots are generated in the Mapinfo Professional GIS. Bathymetry gridding and difference mapping for surface analysis in Mapinfo is accomplished using Northwood Geosciences “Vertical Mapper”.

Please refer to Appendix II for tables listing data acquisition and processing hardware serial numbers and software versions.



## **B. QUALITY CONTROL**

Please refer to Appendix III for detailed Data Acquisition and Processing Flow Diagrams

### **B.1 Bathymetry Data**

#### Vertical Beam Sonar Data

Vertical Beam sonar data are converted from Hypack format to CARIS format using the CARIS “Hypack” data converter (See Conversion Parameters Appendix II).

After conversion, the data are opened in CARIS Navigation Editor, Attitude Editor, and Single Beam Editor. Vessel navigation data is manually checked for speed jumps greater than 2 knots, which are rejected with interpolation. Attitude data (if present) are checked for errors or gaps. Sounding data are checked for aberrant pings.

Survey personnel scan raw VBES soundings in CARIS Single Beam Editor. The digital data is compared with analog paper records to ensure no valid depths are missed by the bottom detection algorithm or aberrant pings are accepted. Low frequency soundings found to be more shoal than the corresponding high frequency depths can be manually “selected”.

#### Multibeam Sonar Data

Multibeam sonar data are converted from XTF format to CARIS format using the CARIS converter (See Conversion Parameters Appendix II)

After conversion, the data are opened in CARIS Navigation Editor, Attitude Editor, Swath Editor, and Subset Editor. Attitude data is checked for errors or gaps. Vessel navigation data is manually checked for speed jumps greater than 2 kts, which are rejected with interpolation. Raw MBES soundings are first observed in CARIS Swath Editor. Occasionally, bottom type of the survey area or sea state during acquisition cause aberrant pings. These “fliers” are rejected. In main scheme areas, survey personnel employ the CARIS depth filter to facilitate cleaning. The filter is configured as a window with appropriate lateral, upper, and lower constraints chosen based on the expected mean depth and the variability of bathymetry. After applying the filter, survey personnel review the data to ensure that only those soundings that are clearly incorrect are rejected (See Conversion Parameters Appendix II).

Soundings are then examined in CARIS Subset Editor. Survey personnel examine questionable soundings on a case by case basis, with consideration given to any side scan sonar features in the area, the receive strength of the echo,

and surrounding soundings. All soundings that remained ambiguous after this process are identified for further investigation and left in the data set.

#### Final Processing of Sounding Data

After the initial scan of VBES and MBES soundings, the data are sound velocity corrected. The sound velocity profiles that are nearest in time are applied to the sounding data.

Zoned tides are applied in the field to all bathymetry data. Preliminary observed water levels obtained from either the CO-OPS web site or through Tidebot email are used. The tide Zone Definition File (ZDF) is either supplied with the project information or created through MapInfo's export tide region to CARIS HIPS ZDF format utility supplied by HSTP. The resulting zone file and tide files are applied to the corresponding data in CARIS, and merged. When Verified Tides become available, these data are downloaded from the CO-OPS site and applied to the bathymetric data through a re-merge.

Once data acquisition and processing is complete for a particular area, survey personnel check scanned all soundings in CARIS subset mode. Subset mode is used for check scanning because it provides an opportunity to examine data in three dimensions and in the context of surrounding lines, therefore highlighting errors which may have affected only a specific line or day. In areas of 100% MBES coverage, overlap also allows many of the ambiguous soundings identified during the initial scan to be resolved.

After final data cleaning and correction is complete, survey personnel create a CARIS field sheet. The data is gridded with a 0.33 - 5m resolution, from which digital terrain models and sun-illuminated images are generated. These products are analyzed to assess coverage and highlight remaining data problems.

## **B.2 Side Scan Sonar Imagery**

All side scan sonar imagery is converted from SDF or XTF formats to CARIS format using CARIS converters (See conversion parameters Appendix II).

After conversion, the data are opened in CARIS Navigation Editor, Attitude Editor, and Side Scan Editor. Survey personnel check vessel attitude (if present), cable out, Gyro, and sonar height. Vessel navigation data is manually checked for speed jumps greater than 2 kts. Data showing these speed jumps are rejected with interpolation.

After confirming the validity of the vessel navigation, cable out, and towfish depth values, survey personnel then use the "recompute towfish navigation" function to calculate towfish position. The CARIS towfish positioning is based on a smoothed course made good value from the towing vessel.

Side scan sonar data are scanned in CARIS Side Scan Editor. Survey personnel correct errors in bottom tracking, slant range correct the imagery at default resolution (0.1m), and scanned the data for significant contacts. Contacts deemed “significant” include, but are not limited to, contacts with a shadow indicating a contact height of 1 m or greater in water depths of 20m or less or contact heights 10% of the water depth in water deeper than 20m. Other contacts considered significant by RUDE personnel include smaller contacts in particularly shoal areas or channels, cables and pipelines, large sand wave ridges, and contacts of possible historical significance.

Point feature contacts are picked using CARIS “single point contacts”. Larger and line features are picked using CARIS “multipoint contacts”. All contacts are descriptively labeled and feature codes selected if conclusive identification is possible. Tif images of all contacts are saved. After the initial SSS imagery scan, a check scan of all data is conducted.

Survey personnel assess SSS coverage by using CARIS to mosaic side scan data. These mosaics are drawn at 1 - 5m resolution, using the “interpolation” and “autoseam” options.

### **B.3 Data Analysis**

HSTP’s Pydro software package is the primary tool for sounding and feature integration and assessment. Side scan contacts and detached positions are inserted into the Pydro Preliminary Smooth Sheet (PSS). Bathymetry is imported into Pydro at a 15m by 15m shoal-biased grid. Survey sheet officers use Pydro to assess and categorize contacts, and suppress soundings to produce a shoal biased bathymetry data set at the scale of the survey.

Pydro provides four flags for categorizing features: “Significant”, “Chart”, “Investigate”, and “DTON”. In addition, pydro provides “Primary” and “Secondary” flags for grouping correlated features.

After insertion, SSS features are first categorized by significance. Contacts that meet the standard of significance described in section B.2. are marked as such; those contacts which are deemed insignificant are marked “Resolved” and not investigated further. Also, multiple contacts representing the same physical feature are grouped. The contact that the hydrographer believes best represents the feature (typically, the most clear SSS image) is selected as the “Primary” contact, while the rest are flagged as “Secondary.”

Significant contacts are then reassessed to determine if additional investigation (typically SWMB development) is required. Using the “bathymetry grid” feature of pydro, the hydrographer checks the bathymetry coverage of the contact in question. If additional bathymetry is required, the “investigate” flag is checked.

This can then be queried in Mapinfo to select only those contacts requiring development for line planning.

After contacts are sufficiently investigated, they are further assessed to determine whether they require charting. Features that the hydrographer believes should be added or retained on the chart are marked as such. Features that pose a special threat to vessel traffic have their shoal soundings marked as “DTONS”, and a Danger to Navigation Report is generated.

Using Pydro, a single physical feature selected for charting can have as many as three “Primary” features associated with it. The first is the SSS feature, which has imagery of the contact, but low positional accuracy. Second, the contact can have a significant bathymetry sounding selected, which contains the least depth and position at which the feature should be charted. Finally, if a feature is investigated by divers, the detached position from the dive may be selected as a primary feature.

Contacts and bathymetry analyzed in Pydro are opened in Mapinfo for plotting and contact development planning. Contact and sounding plots are printed at survey scale for final survey assessment.

## **C. CORRECTIONS TO ECHOSOUNDINGS**

It is OCS and RUDE policy that all data be acquired and logged in raw format without application of any corrections for vessel offsets, sensor alignment, sound velocity profile, or tides. These factors are logged separately or contained in the CARIS “Vessel Configuration File” (VCF), and applied in post-acquisition data processing.

### **C.1 Vessel Offsets and Static Draft**

#### **RUDE**

Vessel offsets for NOAA Ship RUDE include transducer positions, tow points, and GPS antenna referenced to the IMU. The RUDE gained a new A-Frame, which required measurements. In addition, GPS antenna positions were re-measured in April, 2003. These measurements are reflected in the offset drawing included in Appendix III.

On April 14, 2003 RUDE conducted patch tests to determine navigation timing and multi-beam head alignment errors for the CARIS Vessel Configuration File. The results of this operation are included in Appendix III.

### Launch 1419

Launch 1419's offsets include transducer positions, tow points, and GPS antenna referenced to the water line. See Appendix III for 1419's offset diagram

### Application

Static transducer offsets are applied to all bathymetry data during the CARIS "SVP Correct" operation. Horizontal offsets are applied during CARIS "Merge".

## **C.2 Dynamic Draft**

### RUDE

RUDE's dynamic draft was determined by traditional rod leveling methods. A report describing this operation and its results is included in Appendix III

### Launch 1419

Launch 1419's dynamic draft was determined by traditional rod leveling methods. A report describing this operation and its results is included in Appendix III

### Application

Dynamic Draft corrections are applied to all bathymetry data in the CARIS "SVP Correct" operation.

## **C.3 Attitude and Heave**

Heave, pitch, and roll corrections are applied to all bathymetry data in the CARIS "SVP Correct" operation. Yaw corrections are applied during CARIS "Merge".

## **C.4 Sound Velocity Profile**

RUDE carries two Seabird SBE-19 Conductivity, Temperature, and Depth profilers. These instruments are returned to the manufacturer yearly for calibration. Records of the latest calibrations are included in Appendix IV

RUDE personnel conduct weekly CTD data quality assessments comparing CTD readings to surface sound velocity and seawater temperature measured by the Digibar Pro and bucket thermometer. In addition, dual CTD casts are conducted monthly, and processed using the Velociwin "comparison cast" feature.

As described in Section A.4, A.5, and B.1, raw conductivity, temperature and depth data are processed to produce sound velocity files in CARIS format. These profiles are applied in CARIS “SVP Correct”.

### **C.5 Water Levels**

Soundings are corrected to Mean Lower Low Water using first Preliminary Unverified tides, and then Verified tides when available, according to the procedure described in Section B.1. All raw tide data are corrected according to the zoning provided with the relevant project instructions prior to application to bathymetry data.

During bathymetric data collection, subordinate gauges included in the project instructions are monitored via the CO-OPS web site, “Tidebot” email, and the CORMS Morning Report. When water level measurement problems are suspected, RUDE personnel bring them to the attention of CO-OPS staff before continuing bathymetric data acquisition.

Water level corrections are applied during CARIS “Merge”.

**D. APPROVAL SHEET****LETTER OF APPROVAL**

Data acquisition and processing are conducted under my direct supervision with frequent personal checks of progress and adequacy. All equipment is continuously monitored for proper operation during data acquisition and all supplemental and supporting records are reviewed in their entirety.

This Data Acquisition and Processing Report is adequate to accompany Descriptive Reports for surveys including data collected during NOAA Ship RUDE's 2003 Field Season.

Respectfully Submitted:

---

Jeff D. Kelley  
Lieutenant (junior grade), NOAA  
Field Operations Officer  
NOAA Ship RUDE

Approved:

---

P. Tod Schattgen  
Lieutenant Commander, NOAA  
Commanding Officer  
NOAA Ship RUDE