

U.S. Department of Commerce  
National Oceanic and Atmospheric Administration  
National Ocean Service

**DESCRIPTIVE REPORT**

Type of Survey: Support USCG

Registry Number: F00777

**LOCALITY**

State(s): Rhode Island

General Locality: Block Island Sound

Sub-locality: Southeast of Block Island

**2019**

CHIEF OF PARTY  
LT Dylan A. Kosten

LIBRARY & ARCHIVES

Date:

**F00777**

**HYDROGRAPHIC TITLE SHEET**

**F00777**

**INSTRUCTIONS:** The Hydrographic Sheet should be accompanied by this form, filled in as completely as possible, when the sheet is forwarded to the Office.

State(s): **Rhode Island**

General Locality: **Block Island Sound**

Sub-Locality: **Southeast of Block Island**

Scale: **5000**

Dates of Survey: **02/10/2019 to 06/20/2019**

Instructions Dated: **06/06/2019**

Project Number: **S-B902-NRT5-19**

Field Unit: **NOAA Navigation Response Team - New London**

Chief of Party: **LT Dylan A. Kosten**

Soundings by: **Multibeam Echo Sounder**

Imagery by: **Multibeam Echo Sounder**

Verification by: **Pacific Hydrographic Branch**

Soundings Acquired in: **meters at Mean Lower Low Water**

**Remarks:**

*Any revisions to the Descriptive Report (DR) applied during office processing are shown in red italic text. The DR is maintained as a field unit product, therefore all information and recommendations within this report are considered preliminary unless otherwise noted. The final disposition of survey data is represented in the NOAA nautical chart products. All pertinent records for this survey are archived at the National Centers for Environmental Information (NCEI) and can be retrieved via <https://www.ncei.noaa.gov/>. Products created during office processing were generated in NAD83 UTM 19N, MLLW. All references to other horizontal or vertical datums in this report are applicable to the processed hydrographic data provided by the field unit.*

# Table of Contents

<b>A. Area Surveyed</b> .....	1
A.1 Survey Limits.....	1
A.2 Survey Purpose.....	3
A.3 Survey Quality.....	3
A.4 Survey Coverage.....	3
A.6 Survey Statistics.....	7
<b>B. Data Acquisition and Processing</b> .....	9
B.1 Equipment and Vessels.....	9
B.1.1 Vessels.....	9
B.1.2 Equipment.....	11
B.2 Quality Control.....	11
B.2.1 Crosslines.....	11
B.2.2 Uncertainty.....	14
B.2.3 Junctions.....	17
B.2.4 Sonar QC Checks.....	22
B.2.5 Equipment Effectiveness.....	22
B.2.6 Factors Affecting Soundings.....	23
B.2.7 Sound Speed Methods.....	23
B.2.8 Coverage Equipment and Methods.....	23
B.3 Echo Sounding Corrections.....	23
B.3.1 Corrections to Echo Soundings.....	23
B.3.2 Calibrations.....	23
B.4 Backscatter.....	24
B.5 Data Processing.....	24
B.5.1 Primary Data Processing Software.....	24
B.5.2 Surfaces.....	24
<b>C. Vertical and Horizontal Control</b> .....	25
C.1 Vertical Control.....	25
C.2 Horizontal Control.....	25
C.3 Additional Horizontal or Vertical Control Issues.....	26
C.3.1 Altitude Spikes in SBET.....	26
<b>D. Results and Recommendations</b> .....	27
D.1 Chart Comparison.....	27
D.1.1 Electronic Navigational Charts.....	28
D.1.2 Shoal and Hazardous Features.....	28
D.1.3 Charted Features.....	28
D.1.4 Uncharted Features.....	28
D.1.5 Channels.....	28
D.2 Additional Results.....	28
D.2.1 Aids to Navigation.....	28
D.2.2 Maritime Boundary Points.....	30
D.2.3 Bottom Samples.....	30
D.2.4 Overhead Features.....	30

D.2.5 Submarine Features.....	30
D.2.6 Platforms.....	30
D.2.7 Ferry Routes and Terminals.....	30
D.2.8 Abnormal Seafloor or Environmental Conditions.....	30
D.2.9 Construction and Dredging.....	30
D.2.10 New Survey Recommendations.....	30
D.2.11 ENC Scale Recommendations.....	31
<b>E. Approval Sheet.....</b>	<b>32</b>
<b>F. Table of Acronyms.....</b>	<b>33</b>

## List of Tables

Table 1: Survey Limits.....	1
Table 2: Survey Coverage.....	3
Table 3: Hydrographic Survey Statistics.....	8
Table 4: Dates of Hydrography.....	9
Table 5: Vessels Used.....	9
Table 6: Major Systems Used.....	11
Table 7: Survey Specific Tide TPU Values.....	14
Table 8: Survey Specific Sound Speed TPU Values.....	15
Table 9: Junctioning Surveys.....	19
Table 10: Calibrations not discussed in the DAPR.....	23
Table 11: Primary bathymetric data processing software.....	24
Table 12: Submitted Surfaces.....	25
Table 13: ERS method and SEP file.....	25
Table 14: CORS Base Stations.....	26
Table 15: Largest Scale ENCs.....	28

## List of Figures

Figure 1: F00777 survey limits.....	2
Figure 2: Object Detection holidays caused by acoustic shadowing in boulder fields.....	4
Figure 3: Holidays within MBES coverage where sonar blowouts occurred.....	5
Figure 4: February Survey Efforts (Red) and June Survey Efforts (Blue).....	6
Figure 5: Overview of F00777 survey area MBES coverage.....	7
Figure 6: NRT5 being backed on to Point Judith to Block Island Ferry.....	10
Figure 7: Crosslines acquired over mainscheme coverage (Charts 13217 and 13218).....	12
Figure 8: Distribution Statistics.....	13
Figure 9: Statistics and distribution summary plots.....	14
Figure 10: Pydro derived histogram plot showing HSSD uncertainty standards compliance of F00777 MBES data within the finalized 0.5m CUBE surface.....	16
Figure 11: Pydro derived histogram plot showing HSSD uncertainty standards compliance of F00777 MBES data within the finalized 1m CUBE surface.....	17
Figure 12: Surveys Junctioning with F00777.....	18

Figure 13: Pydro generated graph comparing H12010 to F00777..... 20  
Figure 14: Pydro generated graph comparing H12700 to F00777..... 21  
Figure 15: Pydro generated graph comparing H12431 to F00777..... 22  
Figure 16: Offset in data caused by a spike in altitude.....27  
Figure 17: Five windmills SE of Block Island operated by Deepwater Wind, RI..... 29

## Descriptive Report to Accompany Survey F00777

Project: S-B902-NRT5-19

Locality: Block Island Sound

Sublocality: Southeast of Block Island

Scale: 1:5000

February 2019 - June 2019

**NOAA Navigation Response Team - New London**

Chief of Party: LT Dylan A. Kosten

### A. Area Surveyed

This hydrographic survey was acquired in accordance with the requirements defined in the Project Instructions S-B902-NRT5-19. The survey area F00777 extends south and east from the south easternmost point of Block Island, RI and covers approximately 7 square nautical miles.

#### A.1 Survey Limits

Data were acquired within the following survey limits:

Northwest Limit	Southeast Limit
41° 10' 19.2" N 71° 32' 31.2" W	41° 6' 3.6" N 71° 28' 40.8" W

*Table 1: Survey Limits*




Figure 1: F00777 survey limits.

Survey limits were acquired in accordance with the requirements in the Project Instructions and HSSD.

## A.2 Survey Purpose

The United States Coast Guard has requested an emergency response hydrographic survey off of Block Island to assist in locating a sunken fishing vessel.

## A.3 Survey Quality

The entire survey is adequate to supersede previous data.

## A.4 Survey Coverage

The following table lists the coverage requirements for this survey as assigned in the project instructions:

Water Depth	Coverage Required
All waters in survey area	Object Detection Coverage (Refer to HSSD Section 5.2.2.2)

*Table 2: Survey Coverage*

Survey coverage was in accordance listed above and in the HSSD with some exceptions. The following are examples of areas that do not meet the coverage requirement.


Some areas of the survey show very large boulder fields which include boulders that are flagged by flier finder. Acoustic shadowing is prevalent in the boulder fields and as a result many small object detection holidays are present.

Holidays from sonar blowouts while working in poor sea states are present across the survey. Heavy fog was present during the entire June survey period and eventually caused the cancellation of survey operations, resulting in existing holidays not being acquired over.


F00777 was acquired during two different time periods. The first time period, Feb 10th and 11th, was the initial response to the sinking of F/V Mistress. This time frame was originally planned to be 4 days but was shortened to 2 because of weather. During this initial response the objective was to cover as much area as quickly as possible, because of this, no XLs were run and very limited holiday hunting was performed.

The second time period, June 18-20th, was authorized by the Chief, Navigation Services Division, under the requirement that survey not exceed three days, all new data be of chart quality, and the area surveyed be without existing MBES data.





*Figure 2: Object Detection holidays caused by acoustic shadowing in boulder fields.*



*Figure 3: Holidays within MBES coverage where sonar blowouts occurred.*




Figure 4: February Survey Efforts (Red) and June Survey Efforts (Blue).






Figure 5: Overview of F00777 survey area MBES coverage.

### A.6 Survey Statistics

The following table lists the mainscheme and crossline acquisition mileage for this survey:

	<b>HULL ID</b>	<i>S3007</i>	<i>Total</i>
<b>LNM</b>	<b>SBES Mainscheme</b>	0	0
	<b>MBES Mainscheme</b>	173.889	173.889
	<b>Lidar Mainscheme</b>	0	0
	<b>SSS Mainscheme</b>	0	0
	<b>SBES/SSS Mainscheme</b>	0	0
	<b>MBES/SSS Mainscheme</b>	0	0
	<b>SBES/MBES Crosslines</b>	3.44	3.44
	<b>Lidar Crosslines</b>	0	0
<b>Number of Bottom Samples</b>			0
<b>Number Maritime Boundary Points Investigated</b>			0
<b>Number of DPs</b>			0
<b>Number of Items Investigated by Dive Ops</b>			0
<b>Total SNM</b>			6.901

*Table 3: Hydrographic Survey Statistics*

The following table lists the specific dates of data acquisition for this survey:

<b>Survey Dates</b>	<b>Day of the Year</b>
02/10/2019	41
02/11/2019	42

<b>Survey Dates</b>	<b>Day of the Year</b>
06/18/2019	169
06/19/2019	170
06/20/2019	171

*Table 4: Dates of Hydrography*

## **B. Data Acquisition and Processing**

### **B.1 Equipment and Vessels**

Refer to the Data Acquisition and Processing Report (DAPR) for a complete description of data acquisition and processing systems, survey vessels, quality control procedures and data processing methods. Additional information to supplement sounding and survey data, and any deviations from the DAPR are discussed in the following sections.

#### **B.1.1 Vessels**

The following vessels were used for data acquisition during this survey:

<b>Hull ID</b>	<i>S3007</i>
<b>LOA</b>	10.38 meters
<b>Draft</b>	0.6 meters

*Table 5: Vessels Used*



*Figure 6: NRT5 being backed on to Point Judith to Block Island Ferry.*

## B.1.2 Equipment

The following major systems were used for data acquisition during this survey:

<b>Manufacturer</b>	<b>Model</b>	<b>Type</b>
Kongsberg Maritime	EM 2040C	MBES
Applanix	POS MV 320 v5	Positioning and Attitude System
AML Oceanographic	MicroX SV	Sound Speed System
YSI	CastAway-CTD	Conductivity, Temperature, and Depth Sensor

*Table 6: Major Systems Used*

## B.2 Quality Control

### B.2.1 Crosslines

S3007 acquired 177.329 linear nautical miles of mainscheme bathymetry and 3.49 linear nautical miles of crosslines. 1-meter CUBE surfaces of mainscheme and crossline coverage were compared using the Pydro Compare Grids tool.

The initial response effort on DN041 and DN042 was intended solely to provide USCG support in the search for F/V Mistress. No XL's were acquired over these days of MBES data, rather, all time surveying was spent expanding the searched area. Data acquired on these two days totaled 67.042 linear nautical miles.

The remaining survey days, DNs 168, 169, 170, and 171 totaled 110.287 linear nautical miles. Data acquired on these days were intended to meet object detection requirements. XL percentage for these days is 3.16%.






Figure 7: Crosslines acquired over mainscheme coverage (Charts 13217 and 13218).

### Comparison Distribution

Per Grid: F00777\_MLLW\_NAD83\_1m-F00777\_MB\_1m\_NAD83\_XL\_fracAllowErr.csar

99.5+% nodes pass (839613), min=0.0, mode=0.1 mean=0.1 max=5.5

Percentiles: 2.5%=0.0, Q1=0.0, median=0.1, Q3=0.2, 97.5%=0.5




Figure 8: Distribution Statistics.




Figure 9: Statistics and distribution summary plots.

### B.2.2 Uncertainty

The following survey specific parameters were used for this survey:

Method	Measured	Zoning
ERS via VDATUM	0.095 meters	0 meters

Table 7: Survey Specific Tide TPU Values.

<b>Hull ID</b>	<b>Measured - CTD</b>	<b>Measured - MVP</b>	<b>Measured - XBT</b>	<b>Surface</b>
S3007	2 meters/second	0 meters/second	0 meters/second	0.5 meters/second

*Table 8: Survey Specific Sound Speed TPU Values.*


Total Propagated Uncertainty (TPU) values for F00777 were derived from a combination of fixed values for equipment and vessel characteristics, as well as field assigned values for sound speed uncertainties. The uncertainty for the VDatum model was provided to the field units in the Project Instructions. A visual inspection of the Uncertainty layer revealed the areas of higher uncertainty occur in the outer beams, and a visual inspection of the Density layer revealed the areas of lowest density are in the deepest areas of the survey. In addition to the usual a priori estimates of uncertainty, some real time and post processed uncertainty sources were also incorporated into the depth estimates of the survey. Real-time uncertainties from the Kongsberg MBES sonars were incorporated and applied during post processing. Uncertainties associated with vessel roll, pitch, gyro, navigation, and heave were applied during post-processing. All of the aforementioned uncertainties were applied in CARIS. As stated, F00777 is an ellipsoidally referenced survey (ERS) and the tidal component was accomplished with a separation model.

## Uncertainty Standards


Grid source: F00777\_MB\_.5m\_MLLW\_Final

99% pass (5,507,836 of 5,566,557 nodes), min=0.70, mode=0.73, max=3.76

Percentiles: 2.5%=0.71, Q1=0.73, median=0.75, Q3=0.77, 97.5%=0.91



*Figure 10: Pydro derived histogram plot showing HSSD uncertainty standards compliance of F00777 MBES data within the finalized 0.5m CUBE surface.*



*Figure 11: Pydro derived histogram plot showing HSSD uncertainty standards compliance of F00777 MBES data within the finalized 1m CUBE surface.*

***Concur with clarification. The correct Tide TPU values are 0.098 meters and 0.02 meters instead the 0.95 meters and 0 meters as shown in table 7.***

### B.2.3 Junctions

There are three junctions with F00777: H12010, H12700, and H12431. All junctions show acceptable agreement with F00777 when run through Pydro's Compare Grids tool.




Figure 12: Surveys Junctioning with F00777.

The following junctions were made with this survey:

Registry Number	Scale	Year	Field Unit	Relative Location
H12010	1:7500	2009	NOAA Ship THOMAS JEFFERSON	N
H12700	1:20000	2014	NOAA Ship FERDINAND R. HASSLER	E
H12431	1:20000	2012	NOAA Ship THOMAS JEFFERSON	S

*Table 9: Junctioning Surveys*

### H12010

Overlap between H12010 and F00777 averaged about 100m in width. Using the compare grids tool within Pydro, the differences in the areas of overlap were analyzed and 99% of nodes were found to meet HSSD standards.



### Comparison Distribution

Per Grid: F00777\_MLLW\_NAD83\_1m-H12010\_MB\_VR\_MLLW\_fracAllowErr.csar

99% nodes pass (541119), min=0.0, mode=0.1 mean=0.3 max=5.3

Percentiles: 2.5%=0.0, Q1=0.1, median=0.2, Q3=0.4, 97.5%=0.8




Figure 13: Pydro generated graph comparing H12010 to F00777.

### H12700

Overlap between H12700 and F00777 averaged about 100m in width. Using the compare grids tool within Pydro, the differences in the areas of overlap were analyzed and 99.5% of nodes were found to meet HSSD standards.

### Comparison Distribution

Per Grid: F00777\_MLLW\_NAD83\_1m-H12700\_MB\_2m\_MLLW\_2of3\_fracAllowErr.csar

99.5+% nodes pass (10090718), min=0.0, mode=0.2 mean=0.2 max=3.7

Percentiles: 2.5%=0.0, Q1=0.1, median=0.2, Q3=0.3, 97.5%=0.4




Figure 14: Pydro generated graph comparing H12700 to F00777.

### H12431

Overlap between H12431 and F00777 averaged about 100m in width. Using the compare grids tool within Pydro, the differences in the areas of overlap were analyzed and 99% of nodes were found to meet HSSD standards.

### Comparison Distribution

Per Grid: F00777\_MLLW\_NAD83\_1m-H12431\_MB\_VR\_MLLW\_fracAllowErr.csar

99% nodes pass (131855), min=0.0, mode=0.4 mean=0.4 max=2.7

Percentiles: 2.5%=0.1, Q1=0.3, median=0.4, Q3=0.5, 97.5%=0.9




Figure 15: Pydro generated graph comparing H12431 to F00777.

#### B.2.4 Sonar QC Checks

Sonar system quality control checks were conducted as detailed in the quality control section of the DAPR.

#### B.2.5 Equipment Effectiveness

There were no conditions or deficiencies that affected equipment operational effectiveness.

### **B.2.6 Factors Affecting Soundings**

There were no other factors that affected corrections to soundings.

### **B.2.7 Sound Speed Methods**

Sound Speed Cast Frequency: At least once every 4 hours

### **B.2.8 Coverage Equipment and Methods**

All equipment and survey methods were used as detailed in the DAPR with the exception of cast frequency as detailed in section B.2.7

## **B.3 Echo Sounding Corrections**

### **B.3.1 Corrections to Echo Soundings**

All data reduction procedures conform to those detailed in the DAPR.

### **B.3.2 Calibrations**

The following calibrations were conducted after the initial system calibration discussed in the DAPR:

Calibration Type	Date	Reason
Patch Test	2019-05-17	HSRR

*Table 10: Calibrations not discussed in the DAPR.*

All sounding systems were calibrated as detailed in the DAPR. F00777 spanned over an HSRR period. As a result slight differences are noted in offset measurements as well as patch test values.

## B.4 Backscatter

Raw Backscatter was logged in the .all file and will be sent to the Processing Branch

## B.5 Data Processing

### B.5.1 Primary Data Processing Software

The following software program was the primary program used for bathymetric data processing:

Manufacturer	Name	Version
CARIS	HIPS and SIPS	11.1
NOAA	Pydro	19.4
Applanix	POSPac	8.4

*Table 11: Primary bathymetric data processing software*

The following Feature Object Catalog was used: NOAA Profile Version 2019.

### B.5.2 Surfaces

The following surfaces and/or BAGs were submitted to the Processing Branch:

Surface Name	Surface Type	Resolution	Depth Range	Surface Parameter	Purpose
F00777_MB_50cm_MLLW	CARIS Raster Surface (CUBE)	0.5 meters	3.9 meters - 20 meters	NOAA_0.5m	Object Detection
F00777_MB_1m_MLLW	CARIS Raster Surface (CUBE)	1 meters	18 meters - 37.5 meters	NOAA_1m	Object Detection
F00777_MB_50cm_MLLW_Final	CARIS Raster Surface (CUBE)	0.5 meters	3.9 meters - 20 meters	NOAA_0.5m	Object Detection

Surface Name	Surface Type	Resolution	Depth Range	Surface Parameter	Purpose
F00777_MB_1m_MLLW_Final	CARIS Raster Surface (CUBE)	1 meters	18 meters - 37.5 meters	NOAA_1m	Object Detection

*Table 12: Submitted Surfaces*

Flier Finder was used to analyze the multibeam surfaces for data cleanliness, and all fliers have been addressed.

## C. Vertical and Horizontal Control

Field installed tide or GPS stations were not utilized for this survey, so no HVCR is included.

### C.1 Vertical Control

The vertical datum for this project is Mean Lower Low Water.

#### ERS Datum Transformation

The following ellipsoid-to-chart vertical datum transformation was used:

Method	Ellipsoid to Chart Datum Separation File
ERS via VDATUM	S-B902-NRT5-19_VDatum_100m_NAD83-MLLW_geoid12b.csar

*Table 13: ERS method and SEP file*

### C.2 Horizontal Control

The horizontal datum for this project is World Geodetic System (WGS) 1984.

The projection used for this project is Universal Transverse Mercator (UTM) Zone 19.

The following PPK methods were used for horizontal control:

- Smart Base

The following CORS Stations were used for horizontal control:

<b>HVCR Site ID</b>	<b>Base Station ID</b>
NCBI	NCBI
MOR5	MOR5
CTGR	CTGR
NPRI	NPRI
MADA	MADA
MAFA	MAFA

*Table 14: CORS Base Stations*

### **C.3 Additional Horizontal or Vertical Control Issues**

#### **C.3.1 Altitude Spikes in SBET**

Areas of the survey showed vertical disagreement between lines. Inspection of the SBET showed maximum altitude spikes of .5m with a duration of less than ten minutes. These spikes were interpolated through using Pydro's AutoQC tool.




Figure 16: Offset in data caused by a spike in altitude.

## D. Results and Recommendations

### D.1 Chart Comparison

Chart comparisons were made using CARIS sounding and contour layers derived from CUBE surfaces. The contours and soundings were overlaid on the latest ENC and compared for general agreement and to identify areas of significant change.



### D.1.1 Electronic Navigational Charts

The following are the largest scale ENC's, which cover the survey area:

ENC	Scale	Edition	Update Application Date	Issue Date
US5RI11M	1:15000	14	12/11/2017	04/08/2019
US5RI10M	1:40000	14	04/08/2019	04/08/2019

*Table 15: Largest Scale ENC's*

### D.1.2 Shoal and Hazardous Features

No shoals or potentially hazardous features exist for this survey.

### D.1.3 Charted Features

No charted features exist for this survey.

### D.1.4 Uncharted Features

No uncharted features exist for this survey.

### D.1.5 Channels

No channels exist for this survey. There are no designated anchorages, precautionary areas, safety fairways, traffic separation schemes, pilot boarding areas, or channel and range lines within the survey limits.

## D.2 Additional Results

### D.2.1 Aids to Navigation

Four lights located on windmills SE of Block Island were not investigated while on the water. These lights were seen from shore at night, but the lighting did not allow for clear photographs to be taken, therefore, no images are submitted in the multimedia folder.



*Figure 17: Five windmills SE of Block Island operated by Deepwater Wind, RI.*

**D.2.2 Maritime Boundary Points**

No Maritime Boundary Points were assigned for this survey.

**D.2.3 Bottom Samples**

No bottom samples were required for this survey.

**D.2.4 Overhead Features**

No overhead features exist for this survey.

**D.2.5 Submarine Features**

Submarine features exist for this survey, but were not investigated.

**D.2.6 Platforms**

No platforms exist for this survey.

**D.2.7 Ferry Routes and Terminals**

No ferry routes or terminals exist for this survey.

**D.2.8 Abnormal Seafloor or Environmental Conditions**

No abnormal seafloor and/or environmental conditions exist for this survey.

**D.2.9 Construction and Dredging**

No present or planned construction or dredging exist within the survey limits.

**D.2.10 New Survey Recommendations**

No new surveys or further investigations are recommended for this area.

### **D.2.11 ENC Scale Recommendations**



No new insets are recommended for this area.

## E. Approval Sheet

As Chief of Party, field operations for this hydrographic survey were conducted under my direct supervision, with frequent personal checks of progress and adequacy. I have reviewed the attached survey data and reports.

All field sheets, this Descriptive Report, and all accompanying records and data are approved. All records are forwarded for final review and processing to the Processing Branch.

The survey data meets or exceeds requirements as set forth in the NOS Hydrographic Surveys Specifications and Deliverables, Field Procedures Manual, Letter Instructions, and all HSD Technical Directives. These data are adequate to supersede charted data in their common areas. This survey is complete and no additional work is required with the exception of deficiencies noted in the Descriptive Report.

Approver Name	Approver Title	Approval Date	Signature
LT Dylan A. Kosten	Sheet Manager	03/09/2020	 <small>Digitally signed by KOSTEN.DYLAN.ANDREW.1 504527405 Date: 2020.03.09 11:29:59 -04'00'</small>
LT Dylan A. Kosten	Chief of Party	03/09/2020	 <small>Digitally signed by KOSTEN.DYLAN.ANDREW.1 504527405 Date: 2020.03.09 11:30:29 -04'00'</small>

## F. Table of Acronyms

<b>Acronym</b>	<b>Definition</b>
<b>AHB</b>	Atlantic Hydrographic Branch
<b>AST</b>	Assistant Survey Technician
<b>ATON</b>	Aid to Navigation
<b>AWOIS</b>	Automated Wreck and Obstruction Information System
<b>BAG</b>	Bathymetric Attributed Grid
<b>BASE</b>	Bathymetry Associated with Statistical Error
<b>CO</b>	Commanding Officer
<b>CO-OPS</b>	Center for Operational Products and Services
<b>CORS</b>	Continuously Operating Reference Station
<b>CTD</b>	Conductivity Temperature Depth
<b>CEF</b>	Chart Evaluation File
<b>CSF</b>	Composite Source File
<b>CST</b>	Chief Survey Technician
<b>CUBE</b>	Combined Uncertainty and Bathymetry Estimator
<b>DAPR</b>	Data Acquisition and Processing Report
<b>DGPS</b>	Differential Global Positioning System
<b>DP</b>	Detached Position
<b>DR</b>	Descriptive Report
<b>DTON</b>	Danger to Navigation
<b>ENC</b>	Electronic Navigational Chart
<b>ERS</b>	Ellipsoidal Referenced Survey
<b>ERTDM</b>	Ellipsoidally Referenced Tidal Datum Model
<b>ERZT</b>	Ellipsoidally Referenced Zoned Tides
<b>FFF</b>	Final Feature File
<b>FOO</b>	Field Operations Officer
<b>FPM</b>	Field Procedures Manual
<b>GAMS</b>	GPS Azimuth Measurement Subsystem
<b>GC</b>	Geographic Cell
<b>GPS</b>	Global Positioning System
<b>HIPS</b>	Hydrographic Information Processing System
<b>HSD</b>	Hydrographic Surveys Division

<b>Acronym</b>	<b>Definition</b>
<b>HSSD</b>	Hydrographic Survey Specifications and Deliverables
<b>HSTB</b>	Hydrographic Systems Technology Branch
<b>HSX</b>	Hypack Hysweep File Format
<b>HTD</b>	Hydrographic Surveys Technical Directive
<b>HVCR</b>	Horizontal and Vertical Control Report
<b>HVF</b>	HIPS Vessel File
<b>IHO</b>	International Hydrographic Organization
<b>IMU</b>	Inertial Motion Unit
<b>ITRF</b>	International Terrestrial Reference Frame
<b>LNM</b>	Linear Nautical Miles
<b>MBAB</b>	Multibeam Echosounder Acoustic Backscatter
<b>MCD</b>	Marine Chart Division
<b>MHW</b>	Mean High Water
<b>MLLW</b>	Mean Lower Low Water
<b>NAD 83</b>	North American Datum of 1983
<b>NALL</b>	Navigable Area Limit Line
<b>NTM</b>	Notice to Mariners
<b>NMEA</b>	National Marine Electronics Association
<b>NOAA</b>	National Oceanic and Atmospheric Administration
<b>NOS</b>	National Ocean Service
<b>NRT</b>	Navigation Response Team
<b>NSD</b>	Navigation Services Division
<b>OCS</b>	Office of Coast Survey
<b>OMAO</b>	Office of Marine and Aviation Operations (NOAA)
<b>OPS</b>	Operations Branch
<b>MBES</b>	Multibeam Echosounder
<b>NWLON</b>	National Water Level Observation Network
<b>PDBS</b>	Phase Differencing Bathymetric Sonar
<b>PHB</b>	Pacific Hydrographic Branch
<b>POS/MV</b>	Position and Orientation System for Marine Vessels
<b>PPK</b>	Post Processed Kinematic
<b>PPP</b>	Precise Point Positioning
<b>PPS</b>	Pulse per second

<b>Acronym</b>	<b>Definition</b>
<b>PRF</b>	Project Reference File
<b>PS</b>	Physical Scientist
<b>RNC</b>	Raster Navigational Chart
<b>RTK</b>	Real Time Kinematic
<b>RTX</b>	Real Time Extended
<b>SBES</b>	Singlebeam Echosounder
<b>SBET</b>	Smooth Best Estimate and Trajectory
<b>SNM</b>	Square Nautical Miles
<b>SSS</b>	Side Scan Sonar
<b>SSSAB</b>	Side Scan Sonar Acoustic Backscatter
<b>ST</b>	Survey Technician
<b>SVP</b>	Sound Velocity Profiler
<b>TCARI</b>	Tidal Constituent And Residual Interpolation
<b>TPU</b>	Total Propagated Uncertainty
<b>USACE</b>	United States Army Corps of Engineers
<b>USCG</b>	United States Coast Guard
<b>UTM</b>	Universal Transverse Mercator
<b>XO</b>	Executive Officer
<b>ZDF</b>	Zone Definition File



APPROVAL PAGE

F00777

Data meet or exceed current specifications as certified by the OCS survey acceptance review process. Descriptive Report and survey data except where noted are adequate to supersede prior surveys and nautical charts in the common area.

The following products will be sent to NCEI for archive

- Descriptive Report
- Collection of Bathymetric Attributed Grids (BAGs)
- Collection of backscatter mosaics
- Processed survey data and records
- GeoPDF of survey products

The survey evaluation and verification has been conducted according current OCS Specifications, and the survey has been approved for dissemination and usage of updating NOAA's suite of nautical charts.

Approved: \_\_\_\_\_

**Peter Holmberg**

Hydrographic Team Lead, Pacific Hydrographic Branch