Diag. Cht. No. 8502-2.

U. S. DEPARTMENT OF COMMERCE

OPR - 487

DESCRIPTIVE REPORT NOAA Ship FAIRWEATHER (MSS-20)
Type of Survey HYDROGRAPHIC
Field No.FA20-1-71 Office No. H-9227
LOCALITY
State Alanka
General locality Gulf of Alaska
LocalityController Bay
19_71_
CHIEF OF PARTY
Captain R. H. Houlder, Commanding
LIBRARY & ARCHIVES OCT 24 1974 DATE 24 1974

Charts 85/3 8500

FORM (6-66)	C&GS-537
-------------	----------

U.S. DEPARTMENT OF COMMERCE ENVIRONMENTAL SCIENCE SERVICES ADMINISTRATION COAST AND GEODETIC SURVEY

REGISTER NO.

HYDROGRAPHIC TITLE SHEET


H-9227

INSTRUCTIONS - The Hydrographic Sheet should be accompanied by this form, filled in as completely as possible, when the sheet is forwarded to the Office.

FIELD NO.

FA-20-1-71

State	Alaska
General locality_	Gulf of Alaska
Locality	Controller Bay
Scale	1:20,000 Date of survey 28 July to 6 August, 1971
Instructions dated	1 March 1971 Project No. OPR-487
Vessel	NOAA Ship FAIRWEATHER
Chief of party	CAPT. R. H. Houlder
Surveyed by	LCDR. R. V. O'Connell, LT. L. K. Nelson, LT. M. C. Grunthal, LTJG D. B. McLean, ENS. E. G. Wood, ENS. F. B. Arbusto
Soundings taken b	y echo sounder, tand look, poles Raytheon DE-723, Serial No. 529
Graphic record sc	aled byFAIRWEATHER personnel
Graphic record che	ecked byFAIRWEATHER personnel
	Automated plot by
Soundings pencile	ed by
	athoms feet at MLIV
REMARKS:	
-	
· · · · · · · · · · · · · · · · · · ·	
	applied to star 12/27/14
	- Store



Descriptive Report

to Accompany

Hydrographic Sheet H- 9227 (FA-20-1-71)

Controller Bay, Alaska

Scale 1:20,000

NOAA Ship FAIRWEATHER (MSS-20)

CAPT. R. H. Houlder, Commanding

A. PROJECT

The survey was accomplished under OPR-487 project instructions dated 1 March 1971 and supplement to instructions dated 25 March 1971, amendment to instructions dated 10 May 1971 and amendment to instructions dated 24 May 1971.

B. AREA SURVEYED

The area surveyed was in Controller Bay, Alaska, west of Kanak and Wingham Islands, and south of Fox Island. The area surveyed is bounded on the north by latitude 60°09' N., on the south by latitude 59°59' N., on the west by longitude 144°38' W., and on the east by longitude 144°26' W. The sounding lines form a 1.4 n.m. wide band stretching from the northwest to the southeast corner of the bounded area described above.

Hydrography was accomplished between 28 July and 6 August 1971. This survey junctions with contemporary surveys FA-40-1-71 and FA-10-1-71. Prior surveys applicable to the area covered by this survey are H-2768, 1:20,000, 1905, H-2868a, 1:100,000, 1898 to 1906, and H-3017, 1:20,000, 1909.

C. SOUNDING VESSELS

The ship FAIRWEATHER accomplished the hydrography, using violet colored ink to denote the position numbers.

D. SOUNDING EQUIPMENT

A Raytheon Model DE-723 echo sounding fathometer, serial number 529, was used to take the soundings. Applicable velocity corrections were determined by serial temperature and salinity observations which were made in the area covered by adjoining contemporary survey FA-40-1-71.

E. SMOOTH SHEET

The position and sounding data were recorded, logged for automated processing, and plotted on boat sheets by FAIRWEATHER personnel. The final smooth sheet is to be plotted electronically and verified at PMC.

F. CONTROL

Decca HiFix was used in the range-range mode throughout the survey. Transmitting stations were located on Middleton Island and thirteen miles southeast of Cordova, Alaska near the Cordova City Airport. The antenna on Middleton Island was set over triangulation mark SPIT 2 1967 and the antenna near the Cordova City Airport was located by a 2nd order traverse in April 1971 and adjusted in August 1971. Corrections to be applied to the positions, determined by calibration are included at the end of the report.

G. SHORELINE

Shoreline was scaled from USC&GS Chart No. 8513, 1:100,000, 9th Edition, corrected April 15, 1971.

H. CROSSLINES

Crosslines consisted of about ten percent of the total survey mileage. Agreement was satisfactory throughout.

I. JUNCTIONS

There was good agreement between this survey and contemporary surveys FA-40-1-71 and FA-10-1-71. No other contemporary survey junctions with this sheet. Here 92.05 - 92.07 - 92.08

J. COMPARISON WITH PRIOR SURVEYS

H-2768, 1:20,000, 1905. There appears to have been a datum shift since this survey was made as islands and a pre-1905 triangulation station show between a three and four minute increase in longitude and about a 20 second increase in latitude. After taking this into consideration, eight of ten random soundings were shoaler from one to three fathoms, one was unchanged and one was deeper by .3 fathoms. The average change was 1.7 fathoms shoaler on the present survey.

H-2868a, 1:100,000, 1893 to 1906. Very little change was noted from this prior survey and soundings agreed within one fathom.

H-3017, 1:20,000, 1909. Overlays with this prior survey occur only near the present survey's southeastern limits. In all cases, soundings agreed to within one fathom.

K. COMPARISON WITH THE CHART

Comparison with USC&GS Chart No. 8513, 1:100,000, 9th edition, August 9, 1969, corrected April 15, 1971, shows a consistent discrepancy of two to four fathoms throughout the survey area, the charted depths being greater in all cases. This is probably due to the area's having been uplifted during the 1964 earthquake.

L. ADEQUACY OF THE SURVEY

The survey is considered complete and adequate for charting.

M. AIDS TO NAVIGATION

There are no aids to navigation in the area of the survey.

N. STATISTICS

Number of positions 503
Sounding line (n.m.) 175.5
Total area surveyed 35.1 sq. n.m.

O. MISCELLANEOUS

None.

P. RECOMMENDATIONS

None.

Q. REFERENCES TO REPORTS

- 1. Season's Report, NOAA Ship FAIRWEATHER, 1971. (To be forwarded).
- 2. Magnetics Report, OPR-487, NOAA Ship FAIRWEATHER, 1971 (to be forwarded).
- Field Edit Report, OPR-487, NOAA Ship FAIRWEATHER, 1971 (to be forwarded).
- Fathometer Report, OPR-487, NOAA Ship FAIRWEATHER, 1971 (to be forwarded).
- Coast Pilot Report, OPR-487, NOAA Ship FAIRWEATHER 1971 (to be forwarded).
- Triangulation and Triangulation Report, OPR-487, NOAA Ship FAIR-WEATHER, 1971 (to be forwarded).
- 7. Electronic Control Calibration Report, OPR-487, NOAA Ship FAIR-WEATHER, 1971 (to be forwarded).
- 8. Oceanographic Temperature and Salinity Velocity Correction Report, NOAA Ship FAIRWEATHER, 1971.
- Chart Investigation Report, NOAA Ship FAIRWEATHER, 1971 (to be forwarded).
 Respectfully submitted,

David B. McLean LTJG, NOAA

TIDE NOTE

Four portable tide gages were installed and operated in connection with ship and launch hydrography during the survey. These were at Martin Island-Katalla Bay, Lat. 60°09.9' N., Long. 144°36.1' W.; Kanak Island, Lat. 60°06.3' N., Long. 144°19.3' W.; Cape St. Elias, Latitude 59°47.8' N., Long. 144°35.8' W.; and Port Etches-Hinchinbrook Island, Lat. 60°19.6' N., Long. 146°34.3' W. The gages at Martin Island-Katalla Bay and at Cape St. Elias were Bristol bubbler gages. Hourly heights were scanned and checked by ship's personnel and the data was forwarded to Rockville, Maryland (C33). The gages at Kanak Island and Port Etches-Hinchinbrook Island were Fisher-Porter ADR gages. These marigrams were also forwarded to Rockville for analysis.

Tide reducers applied to ship and launch soundings for boat sheet purposes were obtained from the IBM 1620 at Pacific Marine Center, Seattle, Washington, using Sitka as a reference station and Wingham Island as a substation.

	GEOGRAPHIC NAMES Survey No. H-9227		2. 40 0	Se Vo C	D WHILL D	or in or in or	Or less has	2 Carde o	Asia Wenter	J. J. John	\$\$\ \
- - F	Name on Survey	A	S. 40 0	C C fro Q		o ino	or F	Q.O.	ABUT H	\s'\K	_
	PACIFIC OCEAN										
- [
								+			1
								1		 	
				1	 	 		1.	+		
✓						 	 		+	 	-
-		-		-		<u> </u>			1		
		-	+	 					-	-	-
<u> </u>			+				 		 		1
7 1	•	-		-					-		1
-		 	-	-	<u> </u>			 		<u> </u>	1
+		 		-		 	 	 		<u> </u>	1
-		ļ	-		-			-	ļ		14
		 	+	ļ	<u> </u>				-		1
			-			 		<u> </u>	ļ ·	1.	1
		 	-	ļ	-				 		1
		 	<u> </u>	ļ	 						11
				ļ		 	ļ			ļ	19
_			ļ		ļ						2
-			-								2
_		ļ		-	<u> </u>						2:
-					-						2
_										-	2
											2
											20

Initial Corrections Controller Bay, Alaska OPR-487 1971

NOAA Ship FAIRWEATHER (MSS-20)

Captain R.H. Houlder, Comdg.

Corrections to be applied to the following sheets:

FA-20-1-71 FA-40-1-71 FA-40-2-71

SHEET	DAY	POSITIONS	CORRECTIONS	(fms)
FA-20-1-71	209 217 218	0001-0142 0143-0239 0240-0503	0.0	
FA-40-1-71	146	0001-0015 0016-0018 0019-0082 0083-0085 0086-0125	0.0 -0.1 -0.2 +0.3 0.0	
	147	0126 -0 156 0157 - 0247 0248 - 0279	0.0 -0.2 0.0	
	153 154	0280-0343 0344-0357 0358-0360 0361-0620 0621-0666	0.0 0.0 -0.2 0.0 +0.2	
	155	0667-0669 0670-0846 0847-0850 0851-0873 0874-0993 0994-1019	0.0 0.0 -0.1 -0.2 0.0 -0.2	
	156	1020-1093 1094-1241 1242-1260 1261-1365	-0.2 0.0 +0.2 0.0	
w.	161	1366-1463	0.0	• .

Velocity Corrections

Controller Bay, Alaska

OPR-487 1971

NOAA Ship FAIRWEATHER (MSS-20)

Captain R. H. Houlder, Comdg.

Corrections to be applied to the following sheets:

FA-10-1-71 FA-10-2-71 FA-10-3-71 FA-20-1-71 FA-40-1-71 FA-40-2-71

The following table will be used between the dates of May 26 (146) and June 5 (156) 1971.

(Table O1)

APPLICABLE DEPTHS (fms) CORRECTIONS (fms)

0000-1100 0.0

The following table will be used between the dates of June 10 (161) and August 11 (223) 1971.

(Table 02)

APPLICABLE DEPTHS	(fms)	CORRECTIONS	(fms)
0000-0005		0.0	
0005-0010		+0.1	
0010-0025		+0.2	
0025-0045		+0.3	
0045-0085		+0.4	
0085-0100		+0.6	
0100-0160		+0.7	
0160-0180		+0.8	
0180-0200		+0.9	
0200-0400		+1.7	
0400-0600		+3.1	

APPLICABLE DEPTHS (fms) CORRECTIONS (fms)

0600-0800 +5.2 0800-1000 +6.3 1000-1200 +12.2

Draft Corrections

Controller Bay, Alaska

OPR-487 1971

NOAA Ship FAIRWEATHER (MSS-20)

Captain R.H. Houlder, Comdg.

Corrections to be applied to the following sheets:

FA-20-1-71 FA-40-1-71 FA-40-2-71

SHEET	DATE	<u>POSITIONS</u>	CORRECTIONS	(fms)
FA-40-2-71	164-217	0001-2947 0001-2421 0001-0503	+0.3 +0.3 +0.3	

ABSTRACT OF ELECTRONIC

CONTROL CORRECTIONS

FA 20-1-71

HI-FIX (Range-Range)

Position	Numbers	Day	Pattern One	Pattern Two
From	To		Green	Red
0001	0142	209	-0.07	-0.20
0143	0445	217	-0.03	+0.20
0446	0503	218	-0.02	+0.09

	COMPUTER PARAMETERS FOR ELECTRONICALLY CONTROLLED SURVEYS
713	(RANGE - BANGE) $FA-20-1-71$ Project No. OPR-487 (2) N. No. 9206 (3) Field No. $FA-40-2-71$
(4)	Type of Control: SHORAN, RAYDIST, X HI-FIX, RADAR Frequency (for conversion of RAYDIST or HI-FIX lanes to meters)
(5)	RANGE ONE (R1) Station Name SPIT 2, 1967 Latitude 59 27 56.514
	Longitude 146 18 22.388
(6)	RANGE TWO (R2) Station Name HI-FIX mast Longitude 145 24 55.866
(7)	Azimuth from Rl to R2 203° 22'47.849"
(8)	Baseline Length in Meters 123,436.370 M
(10)	·
) if SHORAN corrections are applied by the equation, $K(X) + C = D$, where is SHORAN distance and D is true distance, enter the Constant Coefficient of the equations here:
	is SHORAN distance and D is true distance, enter the Constant Coefficie of the equations here:
(11)	is SHORAN distance and D is true distance, enter the Constant Coefficie
(11)	is SHORAN distance and D is true distance, enter the Constant Coefficie of the equations here: K(R1), C(R1), K(R2), C(R2)
	is SHORAN distance and D is true distance, enter the Constant Coefficie of the equations here: K(R1), C(R1), K(R2), C(R2) Number of Velocity Tables to be used: None, One, More than one.
	is SHORAN distance and D is true distance, enter the Constant Coefficie of the equations here: K(R1), C(R1), K(R2), C(R2) Number of Velocity Tables to be used: None, One, More than one. This form is submitted only as an aid in preparing a boat shee
	is SHORAN distance and D is true distance, enter the Constant Coefficie of the equations here: K(R1), C(R1), K(R2), C(R2) Number of Velocity Tables to be used: None, One, More than one. This form is submitted only as an aid in preparing a boat shee projection.
	is SHORAN distance and D is true distance, enter the Constant Coefficie of the equations here: K(R1), C(R1), K(R2) Number of Velocity Tables to be used: None, One, More than one. This form is submitted only as an aid in preparing a boat shee projection. X This form applies to all data on this survey.
	K(R1), C(R1), K(R2) Number of Velocity Tables to be used: None,One,More than one. This form is submitted only as an aid in preparing a boat shee projection.
	is SHORAN distance and D is true distance, enter the Constant Coefficit of the equations here: K(R1), C(R1), K(R2), C(R2) Number of Velocity Tables to be used: None, One, More than one. This form is submitted only as an aid in preparing a boat she projection. X This form applies to all data on this survey. This form applies to part of the data on this survey - Time and Date limitations: From To

SHEET	DAY	POSITIONS	CORRECTIONS	(fms)
FA-40-1-71	162 163 164 166 167 168 194 195 196 209 211 215 216	2380-2530 2431-2443 2444-2467 2468-2487 2488-2642 2643-2796 2797-2835	0.0 -0.2 0.0 -0.1 0.0 -0.3 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0	
FA-40-2-71	164 165 166 167	0001-0036 0037-0110 0111-0134 0135-0185 0186-0295 0296-0346 0347-0370 0371-0531 0532-0580 0581-0617 0618-0856 0857-0877 0878-0934 0935-1013	0.0 -0.4 -0.2 -0.2 -0.5 -0.2 -0.3 0.0 -0.2 -0.2 -0.2 -0.3	
	210 211 215	1014-1227 1228-1348 1349-1354 1355-1367 1368-1409 1410-1543 1544-1741 1742-1800 1801-1819 1820-1943 1944-2155	-0.3 0.0 0.0 -0.2 0.0 +0.2 0.0 0.0 -0.2 0.0	

-

SHEET	DAY	POSITIONS	CORRECTIONS	(fms)
FA-40-2-71		2156 - 2342 2343 - 2421	0.0	

TRANSMITTAL SHEET

FA-20-1-71 H-9227

The field work was examined daily under the supervision of this command. The boatsheet was inspected daily for completeness and no additional work is considered necessary.

R. H. Houlder CAPT., NOAA

Commanding Officer
NOAA Ship FAIRWEATHER

NOAA FORM 76-155 (11-72)	NATIONAL	OCEANIC				OMMERCE		JRYEY N	UMBER	
	GEOGRAP						\mathcal{H}	-92	27	
Name on Survey	A	OH CHART NON	PREVIOUS	JURYEY U.S. QUACE U.S. MAPS	ANTOLE ANTOLE ANTOLE ANTOLE ANTOLE O	OH MA	P.O. GUIDE	OR MAP OR MALA	S.S. Lieht	,15°
GULF OF ALA.										
									<u> </u>	1
										1
										ļ.
									-	+
					1		· · · · · · · · · · · · · · · · · · ·			
					-					+
										1
							,			-
			<u> </u>							+
		<u> </u>								ļ
										\dagger
					A	DLOVE	7			T
					ch	ag. E	Har	mel	S	
·					Sta	2+	1e051	3ple		
						March	1975	,		[
						,				
										-
NOAA FORM 76-155 SUPERSI	EDES CAGS 107	<u> </u>		L		U.S. G.P		<u> </u>		1

NOAA FORM 77-27 (9-72) (PRESC BY HYDROGRAPHIC MANUAL 20-2, 6-94, 7-13)

HYDROGRAPHIC SURVEY STATISTICS HYDROGRAPHIC SURVEY NO. H-9227

RECORDS ACC	OMPANYING SURV	EY: To	be compl	eted whe	n survey i	s registered.			
RECOR	RECORD DESCRIPTION AMOUNT			UNT	RECORD DESCRIPTION				AMOUNT
SMOOTH SHEET	SMOOTH SHEET & PNO 1				BOAT SI		1.		
DESCRIPTIVE RE	PORT		1		OVERLA	YS			3 x
DESCRIPTION	DESCRIPTION DEPTH RECORDS RECORD				гоитѕ	TAPE ROLLS	PUNCHED CA	ARDS	ABSTRACTS/ SOURCE DOCUMENTS
ENVELOPES]					
CAHIERS	1 & P/C	P/0			.				
VOLUMES	VOLUMES								
BOXES	BOXES								
T-SHEET PRINTS	(List)								
SPECIAL REPOR	TS (List)			-					
	The following st	atistics v	OFFICE	PROCES	SSING AC	TIVITIES artographer's repo	ort on the surv	vey	
				[AMC	UNTS		
PR	PROCESSING ACTIVITY				RE-	VERIFICATION	REVIEW		TQTALS
POSITIONS ON SHEET									
POSITIONS CHECKED				503					
POSITIONS REVISED				:1					
DEPTH SOUNDI	IGS REVISED					25			
DEPTH SOUNDI	NGS ERRONEOUSLY	SPACED				Ø			
SIGNALS ERROR	NEOUSLY PLOTTED	ORTRAN	ISFERRE						
						TIME (M	ANHOURS)		
Verific	eation of Cor	ntrol				Ø1			
	cation of Pos		3	T		6			
	Verification of Soundings			8					
	Smooth Sheet Compilation				11				
	ALL OTHER WORK				3				
	TOTALS					29			
PRE-VERIFICAT	ION BY					BEGINNING DATI	E E	NDING	DATE
VERIFICATION I	in Ho					BEGINNING DAT	E E	NDING	DATE
Karol M.	Hoops, Cart	ograph	ic Tec	hnicia	n	6/11/73 BEGINNING DAT		8/22/ NDING	

U.S. DEPARTMENT OF COMMERCE ESSA COAST AND GEODETIC SURVEY

VERIFIER'S REPORT HYDROGRAPHIC SURVEY, H-9227

-INSTRUCTIONS - This form serves to identify items of a check list in verification together with items which are separately reported to the Reviewer. The form is not to be forwarded to the Reviewer. A report, which is prepared for the Reviewer, should identify items by number and letter and will be filed in the Descriptive Report until the survey is reviewed.

- CL Check List Items: should be checked as having been completed during the verification processes.
- R Report Item: This column refers to those items reported to the reviewer and is used to indicate the items discussed.

R - Report frem: This column refers to those reci-	•				
Part I - DESCRIPTIVE REPORT	CL	R	Part III - JUNCTIONS (Continued)	CL	R
Mote: The verifier should first read the Descriptive Report for general information and problems.			10. Junctions with contemporary surveys were satisfactory except as follows:		
1. The Descriptive Report was consulted, paragraphs checked if found satisfactory, and notations were made in soft black pencil regarding action taken. Remarks Recuired: None	X.		Remarks Required: Consider conditions after adjustments have been made; note adjustments made. Make special notes of Butt junctions and areas which are SUPERSEDED.		X
2. Soundings originating with the survey and mentioned in the Descriptive Report have been verified and checked in soft black pencil, including latitude and longitude, together with position identification. Remarks Required:None 3. All reference to survey sheets mentioned in	Х		Port IV - VOLUMES 11. All items affecting the plotting of the survey which are entered in the remarks columns of the sounding records were noted and check marked. In all cases appropriate action was taken and exceptions noted in the volumes. Remarks Required: None	x	
the Descriptive Report should include registry number and year. Remarks Required: None	X		12. Condition of sounding records was satisfactory except as follows:		
Port II - SHORELINE AND SIGNALS 4. Source of shoreline signals Remarks Required: List all surveys			Remarks Required: Mention deficiencies in completeness of notes or actions for the follow- ing:		
 o. Give earliest and latest dates of photographs b. Field inspection date 		x	(a) rocks (b) line turns (c) position values of beginning and ending of lines	x	
e. Field Edit date d. Reviewed-Unreviewed			(d) bar check or velocity correctors		
The transfer of contemporary topographic information was carefully examined and reconciled with the hydrography. Remarks Required: Discuss remaining	х		(e) time recording (f) notes or markings on fathograms (g) was reduction of soundings accurately		
ditferences.		<u> </u>	done?		
6. The plotting of all triangulation stations, topographic stations and hydrographic signals has been checked and noted in processing stamp No. 42 on the smooth sheet. Remarks Required: None	х		(h) was scanning accurate? (i) were peaks at uneven intervals missed? (j) were stamps completed? (k) references to adjacent features		
Objects on which signals are located and which fall outside of the high-water line have been described on the sheet.	,		Port V - PROTRACTING 13. All positions verified instrumentally were check marked in color in the sounding records, and verifier initialed the processing stamp.		
Remarks Required: List those signals still unidentified.	X		Remarks Required: None	N/A	
Part III - JUNCTIONS Note: Make a cursory comparison preliminary to inking soundings in area of overlap.			14. The protracting and plotting of all unsatisfactory crossings were verified.	NI /A	
 All junctions of contemporary or overlapping sheets were transferred in colored ink and overlapping curves were made identical. Remarks Required: None 	х		Remarks Required: None	N/A	
9. The notation in slanted lettering "JOINS II (19)" was added in colored ink for all veri- fied contemporary adjoining or overlapping sheets. Those not verified are shown in pencil.	х		15. All detached positions locating critical soundings, rocks, buoys, breakers, obstructions, kelp, etc., were verified and the position numbers are legible. Remarks Required: None	x	
Remarks Required: None			Remarks Required Houe		

Part V - PROTRACTING (Continued) 16. The protracting was satisfactory except as follows:	CL	R	Port VIII - AIDS TO NAVIGATION 26. All fixed aids located together with those on the contemporary topographic sheets, have	CL	Ŕ
Remarks Required: Refets to protracting in general except for specific faults repeated	n/a		been shown on the survey. Remarks Required: Conflicts of any nature listed.	x	
17. The protractor has been checked within the last three months. Remarks Required: Date of check, type of protractor and number.	n/a		27. All floating aids listed in the Descriptive Report should be verified and checked in soft black pencil, including latitude and longitude and position identification. Remarks Required: None	x	
Part VI - SOUNDINGS 18. All soundings are clear and legible, and critical soundings are a little larger than adjacent soundings. Remarks Required: None	n/a		Port IX - BOAT SHEET 28. The boat sheet was constantly compared with the smooth sheet with reference to notes, position of sounding lines and supplemental information.		
19. Sounding line crossings were satisfactory except as follows: Remarks Required: Discuss adjustments.	х		Remarks Required: None 29. Heights of rocks awash were correctly reduced and compared with topographic infor-	X	
The spacing of soundings as recorded in the records was closely followed; Remarks Required: None	х		mation. Remarks Required: Note excessive conflicts with topographic information.	x	
21. The scanning, reduction, spacing, plotting of questionable soundings have been verified. Remarks Required: None	х		Port X - GENERAL 30. All information on the sheet is shown in accordance with figures 82 and 83 in the Hydrographic Manual (Pub. 20-2).		
22. The smooth plotting of soundings was satisfactory except as follows:			Remarks Required: None 31. Unnecessary pencil notes have been	X	
Remarks Required: Refer to legibility, errors in spacing, and errors in numbers - but not to errors in scanning.	n/a		removed from the sheet. Remarks Required: None	x	
Part VII - CURVES 23. The depth curves have been inspected before inking. Remarks Required: By whom was the penciled curves inspected.		х	32. Degree, minute values and symbols have been checked; also electronic distance arcs have been properly identified and checked on the smooth sheet.	x	
24. The low-water line and delineation of shoal areas have been properly shown in accordance with the following:			Remarks Required: - None		
a. From T-Sheet in dotted black lines b. From soundings in orange c. Approximate position of sketched curve is			33. The bottom characteristics are adequately shown. Remarks Required: None		Х
dashed oránge d. Approximate position of shoal area not sounded in black dashed	X		Part XI - NOTES TO THE REVIEWER		-
Remarks Required: None			34. Unresolved discrepancies and questionable soundings.	х	
25. Depth curves were satisfactory except as follows: (This statement should not refer to the manner in which the curves were drawn).	x		35. Notation of discrepancies with photogram- metric survey inserted in report of unreviewed photogrammetric survey or on copy.	3	
Remarks Required: Indicate areas where curves could not be drawn completely because of lack of soundings. For some inshore areas a general statement is sufficient.			36. Supplemental information.		<u>_x</u>
Verified by Karol M. Hoops, Cartograph	ic Te	echni	cian B/22,	/74	

FA-20-1-71 H-9227

This sheet was constructed and plotted at Pacific Marine Center, Seattle, Washington. Information relating to this survey will be noted under the heading by the number and letter as on Verifier's Report, C&GS Form 946A.

PART II SHORELINE AND SIGNALS

4. This survey is an off-shore sheet, therefore, no manuscripts were required.

PART III JUNCTIONS

10. This survey junctions H-9205, 1971 (1:40,000) to the Southwest; H-9207, 1971 (1:10,000) to the Northwest; H-9208, 1971 (1:10,000) to the East. The hydrography in this survey does not actually junction with the hydrography from the above surveys. H-9207 and H-9208 are incomplete and although the Descriptive Report of H-9227 indicates that the survey is complete, the failure to junction with the hydrography indicates that additional field work is required. Since there are no plans for completing this hydrography in the near future this data is submitted for chart application and may have to be replotted when the additional field work does occur.

PART VII CURVES

23. The penciled depth curves were inspected by A. E. Eichelberger, Cartographic Technician.

PART X GENERAL

33. There were no bottom samples taken within this survey.

PART XI NOTES TO THE REVIEWER

36. This survey was verified by Karol Hoops under the supervision of A. E. Eichelberger.

Respectfully submitted,

A. E. Eichelberger
Cartographic Technician

20	LUL			, ,		7//	15	10419	
(1) Project	No. 0/1	<u> </u>	1 .7/	(1,)	Raqueste	d by <u>cr</u>	44	**************************************	
(2) H No.	922	7 -		(5)	Ship or (Office _	many stage	<u> </u>	χ
(3) Field No	. <u>FA</u>	19 E 19 - 9	//	(6)	Date Requ	uired			
.(7) Visual [Ft.	(0) or Fat	homs (1)	(8)	Electroni	ic X	(fill o	at form	//3)
(10) XKN (SP or Wost	5) Distanc Edge (NYX :	o from CME = 0).	IR to East	Edge (MXX = 1)	932	1.0	_ Meters	3
(11) YKK (SP of Sheet	241) Dista: •	ice from E	quator to	South 1	Edge	664581	9.614	_ Xeters	
(12) Central :	Moridian					14402	81301	•	
(13) Survey S	cale					1:20	,000 /		
(Y Size of S	Sheot (Chec	k one)	<i>54</i> 36xá0∫	<u>× </u>	42x6	0			
(15) NYX, Orig						•		•	
	ихх = т (7	NYX = 0				
Greatest Grid	Mer			c	Mer Lowest Grid				
	•	ام ا	~ XKN		om Equato ge of She		th		
	Grid +	(00	tter Orisi rner of Sh itude &9	n neet)					
YKN From Equator	- XN -	Lon	gitude	0 18:	30 "				
Edge of She			•		Oria Idr	nits			
			Greatest L						
			lowest Lat Difference		59056:		Interval Hydro Ma (19)	- Page 4 inual)	· 11
		94. (21.) (Preatest L		144		(20)	14	<u>YSN</u>
			reatest Longowest Long				(24)	1:0) II
			ifference		00/91	7	(25)		XSX

Date Field No.

PAPAMETER CARD II

lomi major axis of the earth

Your Constant- Distance from central meri-North/south axis of sheet - to X axis - 1) of plotter Central Meridian of Projection Y Constant - Distance from equator origin of plotter SP 2/1 H Identification No. an to origin of plotter Feet/Fathom indicator Plotter Scale/Survey Scale SP 5 correspond to (Y axis ó *±0498.6876 6.378,206. fathom 0000 moters 9 C S RDA SCA 12 FOF XXX H Ħ 0 0

PARAMTTER CARD III

Lowest Lat. Intersection

Difference between Grid Lowest Long. Intersection

Interval (Long)

FOF - 1

				<u></u>	
				2 12	59
				12	13
			0	19	2
			-		10/
			0	0	a
•	1		5	0	0.0
			10	0	0
	YSN	XSN	DOOD DXY	O OOO XST	56 dodo YST
			e v	3	N
			7 0 0 0 0 0 0 0	1-1	12
			0	0	12 /3
Compu Punch Check Date			0 1	2/5	7
Computed Punched Checked			ol	74	7 6
Computed Punched Checked			Ok	0 0 4	20
			0	30	0
Story W			0	0 14	30
2.26-71			"	2 0	90
2	2		S	27 30	200

BYDRO Computes G.F.'s from Electronic Controlled Baceline ETER CARDS

, or 23 if resp. constant is negative) (when calibration correction is applied by a line Date Date X x + C)

Computed

Punched

Checked

••	COMPUTER PARAMETERS FOR ELECTRONICALLY CONTROLLED SURVEYS
(1)	(RANGE - RANGE) FA-20-1-71 Project No. <u>OPR-487</u> (2) N. No. <u>9206</u> (3) Field No. <u>FA-40-2-71</u>
	Type of Control: SHORAN, RAYDIST, X HI-FIX, RADAR Frequency (for conversion of RAYDIST or HI-FIX lanes to meters) /
(5)	RANGE ONE (R1) Station Name SPIT 2, 1967 Longitude 146 22.388
(6)	RANGE TWO (R2) Station Name HI-FIX mast Latitude 60° 28 46.866
(7)	Longitude 145
(8)	Baseline Length in Meters 123,436.370 M.
	Location of survey with respect to Electronic Baseline: CHECK ONE (To determine: imagine an observer standing at R1 and looking directly at R2 if the survey area is to the observer's LEFT then A is negative; if the survey area is to the observer's RIGHT then A is positive.)
	-A (minus) X +A (plus)
(10)	if SHORAN corrections are applied by the equation, $K(X) + C = D$, where X is SHORAN distance and D is true distance, enter the Constant Coefficients of the equations here:
•	K(R1), C(R1), K(R2), C(R2)
(11)	Number of Velocity Tables to be used:
	None,One,More than one.
(12)	This form is submitted only as an aid in preparing a boat sheet projection.
•	X This form applies to all data on this survey.
	This form applies to part of the data on this survey -
	. Time and Date limitations: From To
•	Position Number Limitations: From To
•	This is Form #3 Sheet # 1 of 1 Sheets for this survey.
(13)	Other Remarks: This form applies to all data on surveys FA-40-1-71 (H-9205), FA-40-2-71 (H-9206) and FA-20-1-71 (H-9207)

U. G. DEFARMENT OF COSTERCE. INTIONAL OCIANIC AND ACCOUNTERIC ADDITIONAL OCIAN SURVEY

5/23/74

TIDE NOTE FOR HYDROGRAPHIC SHEET

Processing Division: Pacific Parine Center

Hourly heights are approved for Form 362

Tide Station Used (NOAA Form 77-12): Martin Is. Kanak Is.

Feriod: Apr. 30 - Aug. 15, 1971

HYDROGRAPHIC SHEET: H9227

OPR: 487

Locality: Controller Bay

Martin Is. - 7.3 ft.

Plane of reference (mean lower low water): Kanak Is. - 3.2 ft.

Height of Lean High Water above Plane of Reference is 9.0 ft.

Remarks: Zone direct on Martin Is.

During time of gage malfunction, apply range

ratio of 0.95 to Kanak Is. gage.

Hermer & Hulband

	050100 174900 0300	213700	222300	ACTUAL HYDRO.	OPR-487 TIDE REQUIREMENTS
	030	–			Ę
	:		15000100-210	HOURLY HEIGHTS REQUIRED FOR ****	SURVEYS
•			A CONTRACT OF THE CONTRACT OF	REQUIRED FOR C331	H-9227
	To take a second management of the second mana	Trains to the state of the stat		C331 VERIFICATION	

The state of the s

A Administration of the Control of t

to the contract of the contrac

FAIRWEATHER
FA-20-1-71
H-9227
TIME MERIDIAN - 135
TIDE STATION - MARTIN ISLAND
YEAR - 1971
CORRECTIONS IN FATHOMS
MLLW CORRECTION - 7.3 FEET
TIME SHIFT - ZERO
RANGE RATIO - 01.00

```
133700 00 1006 0000 209 0 130000 000000
140000 00 1007.
142100 00 1008
144200 00 1009
150400 00 1010
152900 00 1011
155600 00 1012
163200 00 1013
184000 00 1014
191400 00 1013
193900 00 1012
200200 00 1011
202600 00 1010
205000 00 1009
211400 00 1008
214000 00 1007
220800 00 1006
223900 00 1005
235500 00 1004
235900 00 1003
012400 00 1004 0000 210 0 000000 000000
020000 00 1005
130000 00 1014 0000 217 0 130000 000000
140300 00 1013
143300 00 1012.
150000 00 1011
152400 00 1010
154900 00 1009
161700 00 1008
165100 00 1007
174700 00 1006
180000 00 1005
183100 00 1006
185700 00 1007
194800 00 1008
201500 00 1009
203400 00 1010
```

Smooth Wides

```
205100 00 1011
210800 00 1012
212600 00 1013
214400 00 1014
220400 00 1015
223100 00 1016
230800 00 1017
003700 00 1018 0000 218 0 000000 000000
010800 00 1017
013100 00 1016
015100 00 1015
020700 00 1014
022200 00 1013
023600 00 1012
025000 00 1011
030400 00 1010
031900 00 1009
033400 00 1008
034900 00 1007
040400 00 1006
041700 Ü0 1005
043100 00 1004
044500 00 1003
050000 00 1002
051600 00 1001
053400 00 1000
055700 00 0001
065100 00 0002
074000 00 0003
080000 00 0004
081900 00 0003
083400 00 0002
084700 00 0001
085900 00 1000
091500 00 1001
093000 00 1002
094500 00 1003
100000 00 1004
101400 00 1005
102900 00 1006
104400 00 1007
110000 00 1008
111500 00 1009
113100 00 1010
114800 00 1011
120800 90 1012
123200 00 101 .
```

```
065100 00 0002
074000 00 0003
080000.00 0004
081900 00 0003
083400 00 0002.
084700 00 0001.
085900 00 1000 -
091500 00 1001
093000 00 1002
094500 00 1003
100000 00 1004
101400 00 1005 -
102900 00 1006
104400 00 1007
110000 00 1008
114500 00 1009
113100 00 1010
114800 00 1011
120800 00 1012
123200 00 1013
131300 00 1014
135900 00 1015
144500 00 1014
151100 00 1013
```

```
153200 00 1012
155200 00 1011
161200 00 1019
163300 00 1009
165500 00 1008
171800 00 1007
174400 00 1006
182000 00 1005
194700 00 1005
204700 00 1006
210700 00 1007
212500 00 1008
214200 00 1010
```

TO/II Printout

Electronic Position Correctors

202 209 1971

173300 7 0310 0001 209 100007 100020 0000 000 000 170900 7 0305 0143 217 100003 000020 0000 000 000

7 050100 7 0110 0240 218 100003 000020 0000 000 000 152600 7 0152 0446 218 100002 000009 0000 000 000

APPROVAL SHEET

The smooth sheet has been inspected, is complete, and meets the requirements of the General Instructions for automated surveys and the Hydrographic Manual. (Note: All exceptions are listed in the Verifier's Report)

H-9227 was specifically accomplished so that visual launch hydrography from sheets H-9208 and H-9207 could junction with H-9227 Due to weather and survey progress complete survey junctions were not accomplished. This area was a priority survey to consider Katalla as an open roadstead other than Valdez.

Examined and approved,


James S. Green

Supervisory Cartographic Technician

Approved and forwarded,

Walter F. Forster, Cdr., NOAA Chief, Processing Division

Pacific Marine Center



NAUTICAL CHART DIVISION

RECORD OF APPLICATION TO CHARTS

FILE WITH DESCRIPTIVE REPORT OF SURVEY NO. __

U	02	27

INSTRUCTIONS

A basic hydrographic or topographic survey supersedes all information of like nature on the uncorrected chart.

1. Letter all information.

2. In "Remarks" column cross out words that do not apply.

3. Give seasons for deviations, if any, from recommendations made under "Comparison with Charts" in the Review.

CHART	DATE	CARTOGRAPHER	REMARKS
85/3	2/11/76	The Varia	Full Part Befese After Verification Review Inspective Signed Via
_	7		Drawing No. Examined for critical
see back —	page		Corrections - NO CORRECTIONS
531	8/6/79	Open 12. Stembel	Full Past Before After Verification Review Inspection Signed Via
	0/4/1	12.5	Drawing No. 16 (Cat I) Consider fully applied
-			Full Part Before After Verification Review Inspection Signed Via
		1	Drawing No.
			
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			
- , , , , , , , , , , , , , , , , , , ,			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			21
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
			Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
		,	Full Part Before After Verification Review Inspection Signed Via
			Drawing No.
	V 1 1. d. 1 11 11 11 11 11 11 11 11 11 11 11 11 11 11 11 11		
			

Chart 8502 Exam for crit. corr Thru 8502 - None apply N.g. Brundi 2-28-75