

## D.C. HORIZONTAL AND VERTICAL CONTROL

### *See also the H-Cell report.*

The NOAA tide station 8651370 in Duck, NC was the source of verified water level heights for determining correctors to soundings. The primary means for analyzing the adequacy of zoning was observing zone boundary crossings in the navigated swath editor, SAIC's **Multi View Editor (MVE)**. In addition, sun illuminated coverage plots were examined on screen for adequacy of zoning. Comparisons between overlapping cross line data and outer swath data (in deeper water) were also used to assess potential tidal zoning impacts. Sheet H11992 was covered in its entirety by one zone and the water level zoning parameters provided by NOS, Table C-1, were adequate for application of the observed verified water levels for that zone.

**Table C-1. Water Level Zoning Parameters Applied on Sheet H11992**

Zone	Time Corrector (minutes)	Range Ratio	Reference Station
SA45	0	1.05	8651370

The survey data for sheet H11992 were collected in horizontal datum NAD-83, using geodetic coordinates, while data display and products used the UTM Zone 18 projection. The following equipment was used for positioning on the *M/V Atlantic Surveyor*:

- TSS POS/MV, Serial Number 2575 with a Trimble Probeacon Differential Receiver (primary sensor)
- Trimble 4000 DSi GPS Receiver, Serial Number 3504A09516 with a Trimble Probeacon Differential Receiver (secondary sensor)

Differential correctors used for online data were from the U.S. Coast Guard Stations at Driver, VA, Annapolis, MD, and Reedy Point, DE. The differential receiver was programmed to only receive differential corrector data from these three stations.

Daily position confidence checks were conducted using the independent Trimble DGPS. A real-time **ISS-2000** survey monitor also raised an alarm to alert the survey watch if the position differences exceeded the maximum allowable distance. All positioning confidence checks were within an inverse distance of five meters.

Please refer to the Horizontal and Vertical Control Report for detailed descriptions of the procedures and systems used to attain hydrographic positioning. This report will be delivered with the Descriptive Report for the last sheet of this task order.