U.S. Department of Commerce
National Oceanic and Atmospheric Administration
National Ocean Service

DESCRIPTIVE REPORT

Type of Survey: Basic Hydrographic Survey

Registry Number: H13056

LOCALITY

State(s): Louisiana

General Locality: Northern Gulf of Mexico

Sub-locality: 33 NM Southeast of Sabine Bank

2017

CHIEF OF PARTY
Paul L. Donaldson

LIBRARY & ARCHIVES

Date:

U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION HYDROGRAPHIC TITLE SHEET H13056 INSTRUCTIONS: The Hydrographic Sheet should be accompanied by this form, filled in as completely as possible, when the sheet is forwarded to the Office.

State(s): Louisiana

General Locality: Northern Gulf of Mexico

Sub-Locality: 33 NM Southeast of Sabine Bank

Scale: 40000

Dates of Survey: 10/13/2017 to 12/04/2017

Instructions Dated: 06/28/2017

Project Number: **OPR-K371-KR-17**

Field Unit: Leidos

Chief of Party: Paul L. Donaldson

Soundings by: Multibeam Echo Sounder

Imagery by: Side Scan Sonar Multibeam Echo Sounder Backscatter

Verification by: Atlantic Hydrographic Branch

Soundings Acquired in: meters at Mean Lower Low Water

Remarks:

Contract: EA-133C-14-CQ-0033/T-0003.

Contractor: Leidos, 221 Third Street, Newport, RI 02840 USA.

Subcontractors: Divemasters, Inc., 15 Pumpshire Road, Toms River, NJ 08753; OARS, 8705 Shoal Creek Blvd, Suite 109, Austin, TX 78757.

Leidos Doc. 18-TR-014.

All times were recorded in UTC.

Data were collected in UTM Zone 15.

Any revisions to the Descriptive Report (DR) applied during office processing are shown in red italic text. The DR is maintained as a field unit product, therefore all information and recommendations within this report are considered preliminary unless otherwise noted. The final disposition of survey data is represented in the NOAA nautical chart products. All pertinent records for this survey are archived at the National Centers for Environmental Information (NCEI) and can be retrieved via https://www.ncei.noaa.gov/.

Products created during office processing were generated in NAD83 UTM 15N, MLLW. All references to other horizontal or vertical datums in this report are applicable to the processed hydrographic data provided by the field unit.

Table of Contents

A A G 1	4
A. Area Surveyed	
A.1 Survey Limits	_
A.2 Survey Purpose.	
A.3 Survey Quality	
A.4 Survey Coverage.	——————————————————————————————————————
A.5 Survey Statistics.	·
B. Data Acquisition and Processing.	
B.1 Equipment and Vessels.	
B.1.1 Vessels.	
B.1.2 Equipment	
B.2 Quality Control	
B.2.1 Crosslines.	<u>8</u>
B.2.2 Uncertainty	<u>9</u>
B.2.3 Junctions.	<u>10</u>
B.2.4 Sonar QC Checks.	<u>11</u>
B.2.5 Equipment Effectiveness.	<u>12</u>
B.2.6 Factors Affecting Soundings.	<u>12</u>
B.2.7 Sound Speed Methods	<u>12</u>
B.2.8 Coverage Equipment and Methods.	<u>13</u>
B.2.9 Multibeam Coverage Analysis	<u>13</u>
B.3 Echo Sounding Corrections.	<u>14</u>
B.3.1 Corrections to Echo Soundings.	
B.3.2 Calibrations	
B.4 Backscatter	
B.5 Data Processing.	15
B.5.1 Primary Data Processing Software.	
B.5.2 Surfaces	
C. Vertical and Horizontal Control.	
C.1 Vertical Control	
C.2 Horizontal Control.	
D. Results and Recommendations.	
D.1 Chart Comparison	
D.1.1 Electronic Navigational Charts.	
D.1.2 Maritime Boundary Points.	
D.1.3 Charted Features.	
D.1.4 Uncharted Features	
D.1.5 Shoal and Hazardous Features.	
D.1.6 Channels.	
D.1.7 Bottom Samples.	
D.2 Additional Results.	
D.2.1 Shoreline	
D.2.1 Snorenne. D.2.2 Prior Surveys.	
D.2.3 Aids to Navigation.	
ע.ש. Aius to Navigauon	

D.2.4 Overhead Features.	<u>20</u>
D.2.5 Submarine Features.	20
D.2.6 Platforms.	21
D.2.7 Ferry Routes and Terminals.	22
D.2.8 Abnormal Seafloor and/or Environmental Conditions.	<mark>22</mark>
D.2.9 Construction and Dredging.	
D.2.10 New Survey Recommendation.	<u>22</u>
D.2.11 Designated Soundings.	<u>22</u>
D.2.12 Final Feature S-57 File.	<u>22</u>
D.2.13 Side Scan Sonar Contacts S-57 File.	<u>23</u>
D.2.14 Coast Pilot Review Report.	<u>23</u>
D.2.15 Inset Recommendation.	<u>23</u>
E. Approval Sheet	<u>24</u>
List of Tables	
	4
<u>Table 1: Survey Limits</u> <u>Table 2: Hydrographic Survey Statistics</u>	
Table 3: Dates of Hydrography	
Table 4: Vessels Used	
Table 5: Major Systems Used.	
Table 6: Junctioning Surveys.	
Table 7: Submitted Surfaces.	
Table 8: NWLON Tide Stations.	
Table 9: Water Level Files (.tid).	
Table 10: Tide Correctors (.zdf or .tc).	
Table 11: USCG DGPS Stations.	
Table 12: Largest Scale ENCs.	
	<u></u>
List of Figures	
Figure 1: H13056 Survey Bounds.	
Figure 2: Final Bathymetry Coverage for H13056.	
Figure 3: M/V Atlantic Surveyor.	
Figure 4: Summary of Crossing Analysis.	
Figure 5: General Locality of H13056 with Junctioning Surveys.	
Figure 6: CUBE Depth Delta and Heave Artifacts Resulting from Local Weather Events	
Figure 7: Non-DTON Seep and Pipeline Reports.	<u>21</u>

Descriptive Report to Accompany Survey H13056

Project: OPR-K371-KR-17

Locality: Northern Gulf of Mexico

Sublocality: 33 NM Southeast of Sabine Bank

Scale: 1:40000

October 2017 - December 2017

Leidos

Chief of Party: Paul L. Donaldson

A. Area Surveyed

The area surveyed was a section of the Gulf of Mexico south of Calcasieu Pass, LA (Figure 1).

A.1 Survey Limits

Data were acquired within the following survey limits:

Northwest Limit	Southeast Limit
29° 00' 45.45" N	28° 54' 50.26 " N
093° 31' 21.93" W	093° 17' 42.19" W

Table 1: Survey Limits




Figure 1: H13056 Survey Bounds

Survey limits were acquired in accordance with the requirements in the Project Instructions and the Hydrographic Surveys Specifications and Deliverables (HSSD).

A.2 Survey Purpose

The purpose of this survey is to provide contemporary surveys to update National Ocean Service (NOS) nautical charting products. This survey will take place in the vicinity of Sabine, TX and Cameron, LA. This survey will help to complete the safe passage fairway of heavy traffic from Sabine Pass and Calcasieu Pass to safety offshore. Completion of charting in this area will allow many other lanes of traffic to become safe for navigation. The Calcasieu Shipping Channel connects Lake Charles, LA to the offshore areas of the Gulf of Mexico. This is a major shipping channel from the Gulf of Mexico to the Port of Lake Charles and extends over 30 miles. The size of ships using Calcasieu Channel has increased steadily from the 1920's

along with the amount of transportation of materials for processing by the large refinery in Lake Charles, such as gasoline, natural gas, and chemicals. Similarly, this survey would connect the Sabine Passageway to safety offshore in the Gulf of Mexico. Current charts indicate there is high vessel traffic along this route. This survey will allow this vessel traffic safe passage to offshore Gulf of Mexico. The project will also cover approximately 154 square nautical miles of high priority survey area identified in the 2017 Hydrographic Health model. The addition of a modern survey in this area will allow for the updating of modern charts and improve the hydro health of the area.

A.3 Survey Quality

The entire survey is adequate to supersede previous data.

Leidos warrants only that the survey data acquired by Leidos and delivered to NOAA under Contract EA-133C-14-CQ-0033 reflects the state of the sea floor in existence on the day and at the time the survey was conducted.

H13056 was surveyed in accordance with the following documents:

- 1. Project Instructions, OPR-K371-KR-17, dated 28 June 2017
- 2. Hydrographic Surveys Specifications and Deliverables (HSSD), April 2017
- 3. OPR-K371-KR-17 Statement of Work, dated 10 May 2017

A.4 Survey Coverage

The following table lists the coverage requirements for this survey as assigned in the project instructions:

Water Depth	Coverage Required
All waters in survey area	Complete Coverage (refer to HSSD Section 5.2.2.3).
All waters in survey area	All MBES acquisition requires backscatter acquisition (refer to HSSD Section 6.2).

Leidos chose to achieve the coverage requirement using Complete Coverage, Option B (100% side scan sonar coverage with concurrent multibeam). Survey coverage achieved was in accordance with the requirements in the Project Instructions and the HSSD (Figure 2).




Figure 2: Final Bathymetry Coverage for H13056

A.5 Survey Statistics

The following table lists the mainscheme and crossline acquisition mileage for this survey:

	HULL ID	M/V Atlantic Surveyor	Total
	SBES Mainscheme	0	0
	MBES Mainscheme	0	0
	Lidar Mainscheme	0	0
LNM	SSS Mainscheme	0	0
LINIVI	SBES/SSS Mainscheme	0	0
	MBES/SSS Mainscheme	1338.49	1338.49
	SBES/MBES Crosslines	104.12	104.12
	Lidar Crosslines	0	0
Numb Bottor	er of n Samples		2
	er Maritime lary Points igated		0
Numb	er of DPs		0
	er of Items igated by Ops		0
Total S	SNM		56

Table 2: Hydrographic Survey Statistics

The following table lists the specific dates of data acquisition for this survey:

Survey Dates	Day of the Year
10/13/2017	286
10/14/2017	287
10/15/2017	288
10/18/2017	291
10/19/2017	292
10/21/2017	294
10/22/2017	295
10/31/2017	304
11/01/2017	305
11/02/2017	306
11/03/2017	307
11/04/2017	308
11/05/2017	309
11/06/2017	310
11/07/2017	311
11/08/2017	312
12/03/2017	337
12/04/2017	338

Table 3: Dates of Hydrography

B. Data Acquisition and Processing

B.1 Equipment and Vessels

Leidos used their ISS-2000 software on a Windows 7 platform to acquire these survey data. Survey planning and data analysis were conducted using the Leidos SABER software on Red Hat Enterprise 6 Linux platforms. Klein 3000 side scan sonar (SSS) data were collected on a Windows 7 platform using Klein's SonarPro software. Subsequent processing and review of the SSS data, including the generation of coverage mosaics, were accomplished using SABER.

A detailed description of the systems and vessel used to acquire and process these data is included in the Data Acquisition and Processing Report (DAPR) for OPR-K371-KR-17, delivered previously with Data Report H13054 on 16 February 2018. There were no variations from the equipment configuration described in the DAPR.

B.1.1 Vessels

The following vessels were used for data acquisition during this survey:

Hull ID	M/V Atlantic Surveyor
LOA	110 feet
Draft	9 feet

Table 4: Vessels Used



Figure 3: M/V Atlantic Surveyor

The M/V Atlantic Surveyor (Figure 3) was used to collect multibeam echo sounder (MBES) (RESON SeaBat 7125 SV), side scan sonar (SSS) (Klein 3000), and sound speed data during twenty-four hours per day survey operations.

A detailed description of the vessel used is included in Section A of the DAPR.

B.1.2 Equipment

The following major systems were used for data acquisition during this survey:

Manufacturer	Model	Туре
Teledyne RESON (RESON)	SeaBat 7125 SV	MBES
Klein Marine Systems, Inc. (Klein)	3000	SSS
Applanix	POS/MV 320 V5	Positioning and Attitude System
Trimble	Probeacon	Positioning System
AML Oceanographic	MVP30	Sound Speed System

Table 5: Major Systems Used

A detailed description of the equipment installed is included in Section A of the DAPR.

B.2 Quality Control

B.2.1 Crosslines

Multibeam/single beam echo sounder/side scan sonar crosslines acquired for this survey totaled 7.78% of mainscheme acquisition.

There were 104.12 linear nautical miles of crosslines and 1338.49 linear nautical miles of mainscheme lines surveyed on H13056. This resulted in crossline mileage of approximately 7.78% of the mainscheme mileage, which meets the requirement to achieve approximately four percent of mainscheme mileage for a Complete Coverage multibeam survey (Section 5.2.4.3 of the HSSD). H13056 requirements were for Complete Coverage, Option B, based on the classifications defined in Section 5.2.2.3 of the HSSD.

The mainscheme lines were oriented 90°/270° and spaced 80 meters apart. Crosslines were oriented 0°/180° and spaced 1000 meters apart or less. Refer to the "Multibeam Processing Log" section within Separates I for information on the delineation of mainscheme and crossline data files.

Refer to Separates II for details about how the crossing analysis was performed and a complete discussion of the analysis and tabular results. Figure 4 summarizes the comparison results.

Difference Grid	Minimum and Maximum CUBE Depth (meters) of Crossline Grid	IHO Order 1A Maximum Allowable Uncertainty (meters) for the Range of Depths	Percentage of Depth Differences Less than IHO Order 1A Maximum Allowable Uncertainty	
M/V Atlantic Surveyor Multibeam Crossline (Class 1) to Mainscheme	20.707 - 24.825	0.568 - 0.595	100	

Figure 4: Summary of Crossing Analysis

B.2.2 Uncertainty

For specific details on the use and application of the SABER Total Propagated Uncertainty (TPU) model, see Section B.1 in the DAPR. Once the TPU model was applied to the GSF bathymetry data, each beam was attributed with the horizontal uncertainty and the vertical uncertainty at the 95% confidence level. The vertical and horizontal uncertainty values, estimated by the TPU model for individual multibeam soundings, varied little across the dataset, tending to be most affected by beam angle. Individual soundings that had vertical and horizontal uncertainty values above IHO S-44 5th Edition, Order 1a were flagged as invalid during the uncertainty attribution.

As discussed in Section B.2 of the DAPR, SABER generates two vertical uncertainty surfaces; the Hypothesis Standard Deviation (Hyp. StdDev) and the Hypothesis Average Total Propagated Uncertainty (Hyp. AvgTPU). A third vertical uncertainty surface is generated from the larger value of these two uncertainties at each node and is referred to as the Hypothesis Final Uncertainty (Hyp. Final Uncertainty).

The final H13056 two-meter PFM CUBE surface contained final vertical uncertainties that ranged from 0.470 to 0.704 meters. The IHO Order 1a maximum allowable vertical uncertainty was calculated to range between 0.561 to 0.601 meters, based on the minimum CUBE depth (20.114 meters) and maximum CUBE depth (25.541 meters). The SABER Check PFM Uncertainty function was used to highlight all instances in the Hyp. Final Uncertainty surface where a given node exceeded the IHO Order 1a allowable vertical uncertainty for the CUBE depth at that node. The final H13056 two-meter PFM CUBE surface contained eight individual CUBE nodes with final vertical uncertainties that exceeded IHO Order 1a allowable vertical uncertainty. Of the nodes that exceeded the IHO Order 1a allowable vertical uncertainty, all were associated with objects.

The SABER Frequency Distribution Tool was used to review the Hyp. Final Uncertainty surface within the final H13056 two-meter PFM grid. The results showed that in the final two-meter PFM grid, 99.75% of all nodes had final uncertainties less than or equal to 0.480 meters.

B.2.3 Junctions

As requested in the Project Instructions, analyses of the H13056 junctions with specified surveys were performed. Figure 5 shows the general locality of H13056 as it relates to the sheets to which junctions were performed. Details for each survey are listed in Table 6. For H10889 the final smooth sheet XYZ data (irregular spacing) were downloaded from the NCEI website, and a 50-meter average grid was generated and used for comparison in SABER to the final CUBE depths of H13056. For the H12187, H12188, H13054, and H13055 comparisons, the junction was performed against the final respective BAG file or a CUBE PFM grid for each sheet. Note that analysis of the junctions with sheet H13057 was not conducted, as processing efforts for that sheet were still ongoing.




Figure 5: General Locality of H13056 with Junctioning Surveys

The following junctions were made with this survey:

Registry Number	Scale	Year	Field Unit	Relative Location
H10889	1:20000	1999	C and C Technologies, Inc.	Е
H12187	1:40000	2010	NOAA	NW
H12188	1:40000	2010	NOAA	W
H13054	1:40000	2017	Leidos, Inc.	N
H13055	1:40000	2017	Leidos, Inc.	N

Table 6: Junctioning Surveys

H10889

H13056 junctions with H10889 to the east; 100.00% of the comparisons agreed within ± 0.894 meters.

<u>H12187</u>

H13056 junctions with H12187 to the northwest; 100.00% of the comparisons agreed within ± 0.810 meters.

H12188

H13056 junctions with H12188 to the west; 100.00% of the comparisons agreed within ± 2.130 meters.

H13054

H13056 junctions with H13054 to the north; 100.00% of the comparisons agreed within ± 0.347 meters.

H13055

H13056 junctions with H13055 to the north; 100.00% of the comparisons agreed within ± 0.352 meters.

B.2.4 Sonar QC Checks

Sonar system quality control checks were conducted as detailed in Section A.5 of the DAPR.

B.2.5 Equipment Effectiveness

There were no conditions or deficiencies that affected equipment operational effectiveness.

B.2.6 Factors Affecting Soundings

During data acquisition on H13056 there were intermittent local weather events producing increased winds and sea state. Occasionally during the localized weather events, the water levels within the survey area differed slightly from the water level gauge located at Calcasieu Pass, LA. The artifact was seen in the multibeam CUBE surface and generally ranged between 10 to 15 centimeters when present (Figure 6). In addition, during these intermittent weather events, some residual heave artifacts were visible in the data and ranged from 10 to 15 centimeters. However, these occasional vertical offsets and heave artifacts were within the IHO Order 1a allowable vertical uncertainty for the H13056 water depths.




Figure 6: CUBE Depth Delta and Heave Artifacts Resulting from Local Weather Events

B.2.7 Sound Speed Methods

Sound Speed Cast Frequency: On the M/V Atlantic Surveyor, the MVP30 was used to collect sound speed profile (SSP) data. SSP data were obtained at intervals frequent enough to meet depth accuracy

requirements. Section 5.2.3.3 of the HSSD requires that if the sound speed measured at the sonar head differs by more than two meters/second from the commensurate profile data, then another cast shall be acquired. There were times when the sound speed values exceeded the two meters/second threshold due to the local temporal and tidal variability. During these times, several profiles were acquired and reapplied in an effort to reduce these effects. The product of this effort resulted in the final data bearing no significant artifacts due to sound speed differences.

All sound speed profiles applied for online bathymetry data collection were acquired within the bounds of the survey area. Please refer to the DAPR for specific details regarding acquisition (Section A.7) and application (Section C.1.3) of sound speed profiles.

Confidence checks of the sound speed profile casts were conducted by comparing at least two consecutive casts taken with different SSP sensors. Six sound speed confidence checks were conducted during H13056 and the results can be found in Separates II within the "Comparison Cast Log" section.

All individual SSP files are delivered with the H13056 data and are broken out into sub-folders, which correspond to the purpose of each cast. Also, all individual SSP files for H13056 have been concatenated into four separate files based on the purpose of the cast, provided in CARIS format files (.svp), and delivered under (H13056/Data/Processed/SVP/CARIS_SSP) on the delivery drive. In addition sound speed data for the entire OPR-K371-KR-17 project were submitted to NCEI following the NetCDF template format as specified in Section 8.3.6 of the HSSD, refer to Separates II for more details.

B.2.8 Coverage Equipment and Methods

All equipment and survey methods are detailed in the DAPR.

B.2.9 Multibeam Coverage Analysis

Leidos chose to achieve the coverage requirement using 100% side scan sonar coverage with concurrent multibeam bathymetry. To achieve this coverage, the M/V Atlantic Surveyor used a towed Klein 3000 SSS set to a 50-meter range scale. Mainscheme line spacing was 80 meters, which ensured 100% SSS coverage.

The HSSD stated that 100% SSS coverage was insufficient to disprove a charted feature. Therefore, Leidos reviewed the Composite Source File (CSF), BSB charts, and ENC charts and completed an additional 100% SSS coverage, and resulting MBES coverage over charted objects not found during survey in order to verify disproval in accordance with Section 7.3.4 in the HSSD. A disproval search radius was determined from the investigation requirement attribute (invreq) in the OPR-K371-KR-17_CSF_final.000 CSF, or from additional correspondence between Leidos and NOAA as documented within Appendix II of this Data Report. For all charted objects within the assigned Survey Limits of H13056, each object's disproval data covered an area of at least the assigned disproval search radius.

The SABER Gapchecker routine was used to flag MBES data gaps within the CUBE surface. Additionally, the entire surface was visually scanned for holidays at various points during the data processing effort.

Additional survey lines were run to fill any holidays that were detected. A final review of the CUBE Depth surface of the H13056 two-meter PFM containing all MBES data showed that there were no three by three node gaps.

The final H13056 two-meter CUBE PFM was examined for the number of soundings contributing to the chosen CUBE hypotheses for each node by running SABER's Frequency Distribution Tool on the Hypothesis Number of Soundings (Hyp. # Soundings) surface. The Hyp. # Soundings surface reports the number of soundings that were used to compute the chosen hypothesis. Analysis of the H13056 final two-meter CUBE PFM grid revealed that 99.12% of all nodes contained five or more soundings; satisfying the requirements for complete coverage surveys, Option B, as specified in Section 5.2.2.3 of the HSSD.

B.3 Echo Sounding Corrections

B.3.1 Corrections to Echo Soundings

All data reduction procedures conform to those detailed in the DAPR.

B.3.2 Calibrations

All sounding systems were calibrated as detailed in the DAPR.

B.4 Backscatter

Side Scan Sonar (SSS) Coverage Analysis: For all details regarding SSS data processing, see Section B.3 of the DAPR. Leidos chose to adhere to the coverage requirements in the Project Instructions using Complete Coverage, Option B (100% side scan sonar coverage with concurrent multibeam). The HSSD stated that 100% SSS coverage was insufficient to disprove a charted feature. Therefore, 100% SSS coverage was collected and verified for the entire survey area, and an additional 100% SSS coverage was collected over CSF assigned objects, and charted objects that were not found, to verify disproval. Leidos generated two separate coverage mosaics at one-meter cell size resolution as specified in Section 8.2.1 of the HSSD. The first 100% and second 100% disproval coverage mosaics were independently reviewed using tools in SABER to verify data quality and swath coverage. The SABER Gapchecker routine was used to flag data gaps within each of the 100% SSS coverage mosaics. Additionally, the entirety of each SSS surface was visually scanned for holidays at various points during the data processing effort. Additional survey lines were run to fill any holidays that were detected. Both coverage mosaics are determined to be complete and sufficient to meet the requirements contained within the Project Instructions and HSSD. The mosaics are delivered as TIFF (.tif) images with accompanying world files (.tfw), refer to Table 7.

Multibeam Echo Sounder Seafloor Backscatter: In accordance with the HSSD and Project Instructions, Leidos collected MBES backscatter with all GSF data acquired by the RESON SeaBat 7125 SV. The MBES settings used were checked to ensure acceptable quality standards were met and to avoid any acoustic saturation of the backscatter data. The MBES backscatter data acquired were written to the GSF in real-time

by ISS-2000 and are delivered in the final GSF files for this sheet. Per the Project Instructions, backscatter data were not processed by Leidos and no additional products were produced.

B.5 Data Processing

B.5.1 Primary Data Processing Software

The following Feature Object Catalog was used: NOAA Extended Attribute File V5-4.

The primary data processing software used for both bathymetry and imagery was SABER. SABER version 5.2.0.19.02 was updated to version 5.2.0.19.04 for the generation of the S-57 FFF. There were no other software configuration changes after the DAPR was submitted.

B.5.2 Surfaces

The following surfaces and/or BAGs were submitted to the Processing Branch:

Surface Name	Surface Type	Resolution	Depth Range	Surface Parameter	Purpose
H13056_MB_2m_MLLW_Final	BAG	2 meters	20.114 meters - 25.541 meters	N/A	Complete Coverage, Option B (100% side scan sonar coverage with concurrent multibeam)
H13056_SSS_1m_100	SSS Mosaic (.tif;.tfw)	1 meters	0 meters - 0 meters	N/A	100% SSS
H13056_SSS_Disproval	SSS Mosaic (.tif;.tfw)	1 meters	0 meters - 0 meters	N/A	200% SSS Charted Object Disproval

Table 7: Submitted Surfaces

The CUBE Depth surface of the H13056 two-meter PFM was used to assess and document multibeam survey coverage. SABER populates the CUBE depth with either the node's chosen hypothesis or the depth of a feature or designated sounding set by the hydrographer, which overrides the chosen hypothesis. The range of CUBE depths in H13056 was from 20.114 meters (65.991 feet; 0.470 meters Total Vertical Uncertainty [TVU]) to 25.541 meters (83.796 feet; 0.470 meters TVU). Complete Coverage

Section 5.2.2.3 of the HSSD requires two-meter grid resolution for depths ranging from 18 meters to 40 meters, and therefore a two-meter PFM CUBE Depth grid was generated for the entire H13056 surface (H13056 MB 2m MLLW Final.bag).

The final gridded bathymetry data are delivered as a Bathymetric Attributed Grid (BAG). The BAG file was exported from the CUBE PFM grid as detailed in Section B.2.5 of the DAPR.

C. Vertical and Horizontal Control

No vertical or horizontal controls were established, recovered, or occupied during data acquisition for OPR-K371-KR-17, which includes H13056. Therefore, a Horizontal and Vertical Control Report was not required.

C.1 Vertical Control

The vertical datum for this project is Mean Lower Low Water.

Traditional Methods Used:

Discrete Zoning

The following National Water Level Observation Network (NWLON) stations served as datum control for this survey:

Station Name	Station ID
Calcasieu Pass, LA	8768094

Table 8: NWLON Tide Stations

File Name	Status	
8768094_verified_09012017_12042017.tid	Verified Observed	

Table 9: Water Level Files (.tid)

File Name	Status
K371KR2017CORP_Rev.zdf	Final

Table 10: Tide Correctors (.zdf or .tc)

No final tide note was provided by the NOAA Center for Operational Oceanographic Products and Services (CO-OPS). Leidos is not required to have a final tide note from CO-OPS for H13056 however, a final tide note has been provided by Leidos in Appendix I.

The Tides Statement of Work specified NOAA tide station 8768094 Calcasieu Pass, LA as the source for water level correctors for OPR-K371-KR-17. A full explanation of the tide zone assessment is detailed in Section C.4 of the DAPR. For H13056, 8768094 Calcasieu Pass, LA was the source of all final verified water level heights for determining correctors to soundings. All data for H13056 that contributed to the final CUBE surfaces were contained within two tide zones (WGM76 and WGM88) which were provided by NOAA.

Leidos did not revise the delivered tide zones for tide station 8768094 Calcasieu Pass, LA as the water level zoning parameters in the file K371KR2017CORP_Rev.zdf, provided by National Ocean Service (NOS) were deemed adequate for the application of observed verified water levels. As a result, they were accepted as final and applied to all H13056 bathymetry data.

C.2 Horizontal Control

The horizontal datum for this project is North American Datum of 1983 (NAD83) 2011 realization 2010 (NAD83(2011)2010.0).

The projection used for this project is UTM Zone 15, North.

Please refer to the DAPR for details regarding all antenna and transducer offsets.

During survey data acquisition, the ISS-2000 real-time system provided a continuous view and automatic monitoring of position accuracies. An alarm was triggered within ISS-2000 if any accuracy thresholds were not within a predefined range in accordance with specifications of the HSSD. Any soundings with total horizontal uncertainties exceeding the maximum allowable IHO S-44 5th Edition Order 1a specifications were flagged as invalid and therefore were not used in the CUBE depth calculations.

The following DGPS Stations were used for horizontal control:

DGPS Stations
English Turn, LA (293 kHz)
Angleton, TX (301 kHz)

Table 11: USCG DGPS Stations

D. Results and Recommendations

D.1 Chart Comparison

The chart comparisons were conducted using a combination of SABER and CARIS' EasyView. Charting recommendations for depths follow Section 5.1.2 of the HSSD where depths and uncertainties are to be rounded by standard arithmetic rounding (round half up).

United States Coast Guard (USCG) District 8 Local Notice to Mariners publications were reviewed for changes subsequent to the date of the Project Instructions and before the end of survey (as specified in Section 8.1.4 of the HSSD). The Notice to Mariners reviewed were from week 26/17 (28 June 2017) until week 49/17 (06 December 2017).

H13056 data met data accuracy standards and bottom coverage requirements. Recommend updating the common areas of all charts using data from this survey. Charting recommendations for all features found, and updates to charted features, are documented in the H13056 S-57 FFF. Additional charted objects such as submarine pipelines and platforms are discussed in later sections.

D.1.1 Electronic Navigational Charts

The following are the largest scale ENCs, which cover the survey area:

ENC	Scale	Edition	Update Application Date	Issue Date	Preliminary?
US3GC02M	1:250000	31	09/29/2017	02/09/2018	NO

Table 12: Largest Scale ENCs

US3GC02M

ENC US3GC02M covers the H13056 survey area in its entirety.

CUBE depths within sheet H13056 generally agreed with the charted depths across the survey area with observed depths generally within ± 0.5 m.

D.1.2 Maritime Boundary Points

No Maritime Boundary Points were assigned for this survey.

D.1.3 Charted Features

Two charted objects, a non-dangerous wreck with depth unknown and an obstruction with depth unknown, were charted within the survey bounds. This charted non-dangerous wreck was assigned in the CSF, OPR-K371-KR-17_CSF_final.000, and is charted on ENC US3GC02M and Raster 11330. This wreck was labeled as PA in the OPR-K371-KR-17_CSF_final.000 and on Raster chart 11330. No significant features were found within the assigned search radius for the charted dangerous wreck. The charted obstruction was not assigned in the CSF, OPR-K371-KR-17_CSF_final.000 but provided for information only. The obstruction is charted on ENC US3GC02M and Raster 11330. No significant features were found within a 250-meter search radius. The details resulting from final processing of the data and recommendations are captured in the H13056 S-57 FFF.

D.1.4 Uncharted Features

See the H13056 S-57 FFF for all the details and recommendations regarding new uncharted features investigated.

D.1.5 Shoal and Hazardous Features

There were no significant shoals or hazardous features within the area covered by this survey area other than those discussed in Section D.1.4.

D.1.6 Channels

There were no channels within the area covered by this survey.

D.1.7 Bottom Samples

In accordance with both the Project Instructions and Section 7.2.3 of the HSSD, bottom characteristics were obtained for H13056. Bottom characteristics were acquired at two locations, which were assigned in the Project Reference File (PRF) by NOAA. Leidos did not modify the bottom sample locations from the

location proposed by NOAA in the PRF. Bottom characteristics collected during H13056 are included in the H13056 S-57 FFF, named H13056_FFF.000, within the Seabed Area (SBDARE) object and are classified according to the requirements set forth in Appendix H of the HSSD. In addition to the still images of the seafloor and sediment obtained for each bottom sample, which are referenced in the H13056_FFF.000, short videos of the seafloor at each bottom sample location are included on the delivery drive under the folder H13056/Data/Processed/Multimedia.

D.2 Additional Results

D.2.1 Shoreline

All features in the CSF within the assigned Survey Limits of H13056 were resolved. There were no assigned features inshore of the NALL.

D.2.2 Prior Surveys

Junction analysis with prior surveys H10899, H12187, H12188, H13054, and H13055 (collected in 1999, 2010, 2010, 2017, and 2017 respectfully) were conducted, and the results are presented in Section B.2.3 of this Data Report and within Separates II.

D.2.3 Aids to Navigation

A white and orange general warning mark was assigned in the CSF, OPR-K371-KR-17_CSF_final.000, and is charted on ENC US3GC02M and Raster 11330. No buoy or significant features were found within the assigned search radius for the charted buoy. The details resulting from final processing of the data and recommendations are captured in the H13056 S-57 FFF

D.2.4 Overhead Features

There were no overhead features within this survey area.

D.2.5 Submarine Features

Nine pipeline (PIPSOL) objects (Features 05-13) are delivered in the S-57 FFF to represent sections of pipeline found within the bounds of H13056. Four pipeline objects (Features 05, 06, 08, and 12) are line objects depicting charted buried pipelines of which evidence of existence was observed in the side scan data only. One pipeline object (Feature 09) is delivered as a point object identified as exposed pipeline; observed in the side scan and multibeam data. Four pipeline objects (Features 07, 10, 11, and 13) are line objects depicting exposed pipelines of which evidence of existence was observed in the side scan data and multibeam data. Additional charted pipelines fall within the Survey Limits; however, the multibeam and side scan data do not show evidence of them.

In accordance with HSSD Section 1.7, all five exposed pipelines found within H13056 were submitted as Non-DTON Seep and Pipeline Reports. The email correspondence for Leidos' submission of the H13056 Non-DTON Seep and Pipeline Reports is included within Appendix II of this Data Report. Figure 7 provides details regarding the Non-DTON Seep and Pipeline Reports, including the associated Feature number and object class in the H13056 S-57 FFF.

Non-DTON Seep and Pipeline Report	Date Leidos submitted to AHB (COR)	Feature Number	S-57 Object Class
H13056_ExposedPipelines_01	2018-03-06	07	PIPSOL
H13056_ExposedPipelines 02	2018-03-06	09	PIPSOL
H13056_ExposedPipelines_03	2018-03-06	10	PIPSOL
H13056_ExposedPipelines 04	2018-03-06	11	PIPSOL
H13056_ExposedPipelines_05	2018-03-06	13	PIPSOL

Figure 7: Non-DTON Seep and Pipeline Reports

D.2.6 Platforms

There were two assigned offshore platform objects in the CSF, OPR-K371-KR-17_CSF_final.000, provided on 17 July 2017, which fell within the Survey Limits of H13056. All of the assigned platforms were charted on ENC US3GC02M and Raster 11330. There were no platforms visible above the waterline and the charted platforms were not found during survey operations so disproval surveys were conducted. The charted platforms were covered by 200% side scan and resulting multibeam over an area with a radius of at least 80 meters. There was no evidence of the platforms existence in the side scan or multibeam data. See the S-57 FFF, H13056_FFF.000, Offshore Platform (OFSPLF) objects, for details and charting recommendations on the charted platform.

One additional offshore platform (also assigned in the CSF, OPR-K371-KR-17_CSF_final.000, provided on 17 July 2017, and charted on ENC US3GC02M and Raster 11330) which is positioned within the assigned Survey Limits of H13057, also surveyed by Leidos as part of OPR-K371-KR-17, was covered by overlapping data in the southern extents of the H13056 coverage area. Data processing for H13057 is ongoing at the time of data submission for sheet H13056. No platform was visually observed and the disproval survey data were collected on H13057 and will be included with the final delivery of that sheet. This additional offshore platform is included in the S-57 FFF, H13056_FFF.000, Offshore Platform (OFSPLF) object, with remarks detailing the overlapping coverage of H13056 and H13057, and attributed as Retain as the disproval data and recommendation to delete the platform will be included in the H13057 S-57 FFF.

D.2.7 Ferry Routes and Terminals

No ferry routes or terminals exist within this survey area.

D.2.8 Abnormal Seafloor and/or Environmental Conditions

No abnormal seafloor or environmental conditions, as defined in Section 8.1.4 of the HSSD, exist within this survey area other than those discussed in Section D.1.4.

D.2.9 Construction and Dredging

No construction or dredging exists for this survey area.

D.2.10 New Survey Recommendation

No new survey recommendations are made for the area surrounding this survey area.

D.2.11 Designated Soundings

Designated soundings were used to help better preserve the shallowest sounding relative to the computed depth surface. Separate flags exist in the Generic Sensor Format (version 3.06) for designated soundings and features. All depths flagged as features and designated soundings override the CUBE best estimate of the depth in the final BAG files. Both the designated sounding and feature flags, as defined within GSF, are mapped to the same HDCS flag when ingested into CARIS (PD_DEPTH_DESIGNATED_MASK).

No GSF designated sounding flags were set for H13056. GSF feature flags were set on significant features within H13056, and all information is contained in the H13056 S-57 FFF.

D.2.12 Final Feature S-57 File

Included with H13056 delivery is the S-57 FFF, H13056_FFF.000. Details on how this file was generated and quality controlled can be found in Section B.2.6 of the DAPR. The S-57 FFF delivered for H13056 contains millimeter precision for the value of sounding (VALSOU) attribute. As specified in Section 2.2 of the HSSD, the S-57 FFF is in the WGS84 datum and is unprojected with all depth units in meters. All significant, and recommended for charting, features found in H13056 are included within the S-57 FFF.

In accordance with the HSSD, Leidos addressed all assigned objects within the bounds of H13056 from the provided CSF S-57 file in the S-57 FFF.

For each feature contained in the FFF (S-57), the Feature Correlator Sheet was exported as an image file (.jpg) and is included in the S-57 FFF under the NOAA Extended Attribute field "images".

D.2.13 Side Scan Sonar Contacts S-57 File

Included with the H13056 delivery is the Side Scan Sonar Contact S-57 File, H13056_SSCon.000. Details on how this file was generated and quality controlled can be found in Section B.3.5 of the DAPR. As specified in Section 2.2 of the HSSD, the S-57 file is in the WGS84 datum and is unprojected with all depth units in meters.

Side scan sonar contacts were investigated and confirmed using SABER Contact Review. All side scan contacts are retained within the Side Scan Sonar Contact S-57 File. For each contact included in this S-57 file, a JPEG image of the side scan contact is included under the NOAA Extended Attribute field "images".

D.2.14 Coast Pilot Review Report

In accordance with the Project Instructions and HSSD Section 8.1.3, a Coast Pilot Review was performed for OPR-K371-KR-17. Within the Coast Pilot Field Report (OPR-K371-KR-17CoastPilotReport.pdf) provided by NOAA to Leidos on 17 July 2017, there were no assigned investigation items or paragraphs affected. Therefore, Leidos reviewed and updated the actual Coast Pilot paragraphs as possible for the survey areas, port of call, and areas frequently transited. Updates were made to the Coast Pilot paragraphs as defined in the HSSD Section 8.1.3 and incorporated in to a consolidated Coast Pilot Review Report (OPR-K371-KR-17_Coast Pilot Review Report.pdf) which was submitted to NOAA on 09 February 2018. The email correspondence for Leidos' submission of the H13056 Coast Pilot Review Report is included within Appendix II of this Data Report.

D.2.15 Inset Recommendation

No inset recommendations are made for the area covered by this survey.

E. Approval Sheet

As Chief of Party, field operations for this hydrographic survey were conducted under my direct supervision, with frequent personal checks of progress and adequacy. I have reviewed the attached survey data and reports.

All BAG files, this Descriptive Report, and all accompanying records and data are approved. All records are forwarded for final review and processing to the Processing Branch.

The survey data meets or exceeds requirements as set forth in the Hydrographic Surveys Specifications and Deliverables, Project Instructions, and the OPR-K371-KR-17 Statement of Work. These data are adequate to supersede charted data in their common areas. This survey is complete and no additional work is required with the exception of deficiencies noted in the Descriptive Report. Previously, or concurrently, submitted deliverables for OPR-K371-KR-17 are provided in the table below.

Report Name	Report Date Sent
OPR-K371- KR-17_Marine_Species_Awareness_Training_Video_Log.pdf	2018-02-07
OPR-K371-KR-17_Coast Pilot Review Report.pdf	2018-02-09
OPR-K371-KR-17_DAPR.pdf	2018-02-16
H13054_DR.pdf	2018-02-16
H13055_DR.pdf	2018-02-27
OPR-K371- KR-17_Marine_Mammal_Observation_Log.pdf	2018-03-09
OPR-K371- KR-17_OCS_Sea_Turtle_Observation_Log.pdf	2018-03-09
OPR-K371-KR-17_20180309.zip (NCEI Sound Speed Data)	2018-03-09

Approver Name	Approver Title	Approval Date	Signature	
Paul L. Donaldson	Chief Hydrographer	03/20/2018	Paul L. Donaldson Date: 2018.03.15 10:09:25 -04'00'	

APPENDIX I. TIDES AND WATER LEVELS

Field Tide Note

A field tide note was not required for H13056.

Final Tide Note

Observed verified water levels for the station in Calcasieu Pass, LA (8768094) were downloaded from the <u>NOAA Tides and Currents</u> web site. Water Level correctors were prepared for each zone using the **SABER Create Water Level Files** software. The **SABER Apply Correctors** software applied the water level data to the multibeam data according to the zone containing the nadir beam of each ping.

Please refer to the H13056 Descriptive Report Section C.1 for details regarding final tides for H13056. The water level zoning correctors applied to all multibeam data for H13056 were based entirely on Calcasieu Pass, LA (8768094).

No final tide note was provided by NOAA Center for Operational Oceanographic Products and Services (CO-OPS), Leidos is not required to have a final tide note from CO-OPS.

The on-line times for acquisition of valid hydrographic data are presented in the Abstract Times of Hydrography, H13056 (Table A-1).

Abstract Times of Hydrography

Project: OPR-K371-KR-17 Registry No.: H13056 Contractor Name: Leidos Date: 20 March 2018 Sheet Designation: 3

Inclusive Dates: 13 October 2017 – 04 December 2017

Field work is complete.

Begin Date	Begin Julian Day	Begin Time	End Date	End Julian Day	End Time
10/13/2017	286	07:44:26	10/15/2017	288	18:33:44
10/18/2017	291	02:23:30	10/19/2017	292	18:48:35
10/21/2017	294	21:31:33	10/22/2017	295	14:14:34
10/31/2017	304	09:32:28	11/01/2017	305	02:13:15
11/02/2017	306	13:44:26	11/06/2017	310	02:32:17
11/07/2017	311	20:53:05	11/08/2017	312	13:24:41
12/03/2017	337	14:35:41	12/04/2017	338	15:56:12

Table A-1: Abstract Times of Hydrography, H13056

Transmittal Letter to CO-OPS

A transmittal letter to CO-OPS was not required for H13056.

Request for Approved Tides/Water Levels Letter

A Request for Approved Tides/Water Levels letter was not required for H13056.

Other Correspondence Relating to Tides

There is no other correspondence relating to tides and/or water levels.

APPENDIX II. SUPPLEMENTAL SURVEY RECORDS AND CORRESPONDENCE

This Appendix contains copies of email exchanges between Leidos and NOAA concerning various aspects of the survey, data processing, and submittal topics.

In addition, the following standalone files have been provided in the II_Supplemental_Survey_Records_&_Correspondence folder of Descriptive Report Appendices:

- Non-DTON Seep and Pipeline Reports, and overall image, for five exposed pipelines:
 - o H13056_ExposedPipelines_01.zip
 - o H13056_ExposedPipelines_02.zip
 - o H13056_ExposedPipelines_03.zip
 - o H13056_ExposedPipelines_04.zip
 - o H13056_ExposedPipelines_05.zip
 - o H13056_ExposedPipelines_ALL_Chart_11330.png
- OPR-K371-KR-17_Marine_Species_Awareness_Training_Video_Log.pdf

Note that this document includes correspondence through 1:00 PM on 09 March 2018.

CORRESPONDENCE

From: Kathryn Pridgen - NOAA Federal [mailto:kathryn.pridgen@noaa.gov]

Sent: Monday, May 15, 2017 12:40 PM

To: Evans, Rod E. <RHODRI.E.EVANS@leidos.com>

Cc: Emily Clark - NOAA Federal <emily.clark@noaa.gov>; Lepore, Christine A.

<Christine.A.Lepore@leidos.com>; Quintal, Rebecca T. <REBECCA.T.QUINTAL@leidos.com>

Subject: Re: EXTERNAL: Request for Task Order Quote, Sabine and Vicinity

Hi Rod,

I have some answers for the questions you sent us regarding some of the features assigned in the CSF for OPR-K371-KR-17 Sabine and Vicinity. My answers are in red.

Topic 1: Assigned Pipelines:

The pipelines provided in the CSF all had an assignment (asgnmt) attributed as "assigned". The investigation requirements (invreq) state: "See Section 1.6.2 for Elevated Pipeline guidance or Section 1.7 for Non-DTON Exposed Pipeline guidance. If pipeline is not elevated or exposed, include in FFF with descrp = retain."

Leidos referred to Sections 1.62 and 1.7 which do not reference any S-57 FFF attribution or multibeam coverage requirements, as they discuss the submittal of an exposed pipeline or gas seep.

The orange part: Only applies if the pipeline is exposed or elevated, then it qualifies as a DTON and then it should be disproved using the disproval coverage (200% SSS)

The yellow part: If the pipeline is unexposed (as I think the ones assigned in the CSF are), then include in FFF with descrp=retain, and use normal coverage as assigned by the rest of the sheet (in this case complete coverage: 100% SSS with multibeam or 100% MBES)

I am going to change the invreq in the final CSF to read: "If the pipeline is exposed or elevated See Section 1.6.2 for Elevated Pipeline guidance or Section 1.7 for Non-DTON Exposed Pipeline guidance. If pipeline is not exposed, then include in FFF with descrp=retain, coverage requirements are the same as the sheet."

For the pipelines assigned in the CSF, they are only applicable within the sheet limits and as long as it is not exposed it should be follow the coverage requirements of the sheet, not DTON disproval coverage requirements.

Note that several of the provided pipelines extend beyond the bounds of the OPR-K371-KR-17 project limits.

Question:

- 1. What are the coverage requirements for these assigned pipelines? 100% complete coverage if not exposed.
- a. Are we trying to prove or disprove the pipelines? Therefore needing 100% multibeam coverage or 200% SSS coverage? If yes, would we therefore need to perform a route survey over the pipeline within the PRF survey bounds? Would we need to extend the survey beyond the OPR-K371-KR-17 project limits? We are trying to prove unexposed pipelines within the sheet limits. We do not need to extend the survey beyond the sheet limits.
- b. Or is the complete coverage Option B (100% side scan coverage with concurrent multibeam) for the sheet as a whole sufficient "coverage" over these assigned items? Yes. Complete coverage.

Topic 2: Object disproval:

Platforms are also assigned in the provided CSF. The invreq states "If visually confirmed, include in FFF with descrp=retain. If not visible, conduct a feature disproval (Section 7.3.4) and if disproved, include in FFF with descrp = delete." Note that the HSSD 2017 does not provide a search radius for disproval, and one was not indicated in the CSF for platforms.

Question:

1. Is there a defined search radius for features that do not have a position qualifier? In the 2016 Project Instructions there was the following text, "..and all other features without a position qualifier will have a search radius of 80 meters."

For platforms the disproval radius is 80m. The PA radius is specified in the invreq and is different from the platform disproval radius.

I hope this answers your questions. I am available to answer any more that you have. I am in the office this week, but then going to sea for the next two weeks. I will not have phone access but should be able to answer emails.

Thank you, Katy

Kathryn "Katy" Pridgen Physical Scientist NOAA-HSD OPS 301-713-2702 ext 178 kathryn.pridgen@noaa.gov On Thu, May 4, 2017 at 9:20 AM, Evans, Rod E. < RHODRI.E.EVANS@leidos.com wrote:

Emily and Katy,

Thank you for granting an additional 2 weeks to the proposal deadline to now be through May 30, 2017.

Also, thanks for the CSF and PRF files for OPR-K371-KR-17 Sabine and Vicinity. We have the following questions regarding the CSF file sent for TO-03:

Topic 1: Assigned Pipelines:

The pipelines provided in the CSF all had an assignment (asgnmt) attributed as "assigned". The investigation requirements (invreq) state: "See Section 1.6.2 for Elevated Pipeline guidance or Section 1.7 for Non-DTON Exposed Pipeline guidance. If pipeline is not elevated or exposed, include in FFF with descrp = retain."

Leidos referred to Sections 1.62 and 1.7 which do not reference any S-57 FFF attribution or multibeam coverage requirements, as they discuss the submittal of an exposed pipeline or gas seep.

Note that several of the provided pipelines extend beyond the bounds of the OPR-K371-KR-17 project limits.

Question:

- 1. What are the coverage requirements for these assigned pipelines?
- a. Are we trying to prove or disprove the pipelines? Therefore needing 100% multibeam coverage or 200% SSS coverage? If yes, would we therefore need to perform a route survey over the pipeline within the PRF survey bounds? Would we need to extend the survey beyond the OPR-K371-KR-17 project limits?
- b. Or is the complete coverage Option B (100% side scan coverage with concurrent multibeam) for the sheet as a whole sufficient "coverage" over these assigned items?

Topic 2: Object disproval:

Platforms are also assigned in the provided CSF. The invreq states "If visually confirmed, include in FFF with descrp=retain. If not visible, conduct a feature disproval (Section 7.3.4) and if disproved, include in FFF with descrp = delete." Note that the HSSD 2017 does not provide a search radius for disproval, and one was not indicated in the CSF for platforms.

Question:

1. Is there a defined search radius for features that do not have a position qualifier? In the 2016 Project Instructions there was the following text, "..and all other features without a position qualifier will have a search radius of 80 meters."

Thanks, Rod.

Rod Evans Ph.D | Leidos

Branch Manager (Marine Survey and Engineering Solutions Branch)
Survey & Marine Operations Business Area Manager
Maritime Solutions Division
phone: 401.848.4783

evansrh@leidos.com | leidos.com/natsec

"What would an ocean be without a monster lurking in the dark? It would be like sleep without dreams."

Werner Herzog



This email and any attachments to it are intended only for the identified recipients. It may contain proprietary or otherwise legally protected information of Leidos. Any unauthorized use or disclosure of this communication is strictly prohibited. If you have received this communication in error, please notify the sender and delete or otherwise destroy the email and all attachments immediately.

From: Kathryn Pridgen - NOAA Federal [mailto:kathryn.pridgen@noaa.gov]

Sent: Wednesday, May 03, 2017 10:18 AM

To: Emily Clark - NOAA Federal

Cc: Lepore, Christine A.; Evans, Rod E.; Quintal, Rebecca T.

Subject: Re: EXTERNAL: Request for Task Order Quote, Sabine and Vicinity

Christine,

Here are the CSF and PRF files for OPR-K371-KR-17 Sabine and Vicinity.

Katy

Kathryn "Katy" Pridgen
Physical Scientist
NOAA-HSD OPS
301-713-2702 ext 178
kathryn.pridgen@noaa.gov

On Wed, May 3, 2017 at 9:36 AM, Emily Clark - NOAA Federal < emily.clark@noaa.gov > wrote:

Good Morning,

I know Katy sent some additional files yesterday afternoon, not sure if those are what you are requesting. For some reason I am unable to open the attachments. If you didn't receive or need additional information Katy will certainly be able to provide.

There is no issue in granting an extension through May 30 for receipt of your proposal. Just keep in mind that will push the award date out until sometime later in July.

Thanks v/r, Emily

On Wed, May 3, 2017 at 8:28 AM, Lepore, Christine A. Christine.A.Lepore@leidos.com> wrote:

Good morning Emily,

Thank you for forwarding the Request for Task Order Quote, Sabine and Vicinity. Leidos has reviewed the Request for Task Order and in order to build our survey plans for this proposal (i.e. exact survey bounds and assigned objects), Leidos respectfully requests that NOAA provide the Composite Source File (CSF) and Project Reference File (PRF). Leidos will propose an autonomous capability which will require additional time to create and review, therefore, we respectfully request a two (2) week extension to the proposal due date of 16 May 2017 to 30 May 2017.

Please let me know if you have questions or require additional information.

Thank you, Christine

From: Emily Clark - NOAA Federal [mailto:emily.clark@noaa.gov]

Sent: Tuesday, May 02, 2017 12:55 PM

To: Lepore, Christine A. < Christine. A. Lepore@leidos.com>

Cc: Kathryn Pridgen - NOAA Federal < <u>kathryn.pridgen@noaa.gov</u>> **Subject:** EXTERNAL: Request for Task Order Quote, Sabine and Vicinity

Good Afternoon,

Please see the attached Statement of Work and Project Instructions requesting a hydrographic survey of Sabine and Vicinity under contract EA-133C-14-CQ-0033.

Katy Pridgen will be acting as COR under the resulting Task Order.

Please submit your approach and pricing no later than 3:00 ET on May 16, 2017. Any discussions, questions, or communication necessary to reach a final proposal shall be inclusive of myself and the COR from this point forward.

Sent: Monday, July 17, 2017 10:37 AM

To: Evans, Rod E. <RHODRI.E.EVANS@leidos.com>

Cc: Quintal, Rebecca T. <REBECCA.T.QUINTAL@leidos.com>; Emily Clark - NOAA Federal

<emily.clark@noaa.gov>; Russell Quintero - NOAA Federal <russell.quintero@noaa.gov>; Corey

Allen - NOAA Federal <corey.allen@noaa.gov>

Subject: Re: EXTERNAL: Award EA-133C-14-CQ-0033 T-0003

Attachment: Package.zip

Rod,

Here is the package of the final files needed for Sabine.

Please let me know if you have any questions, Katy

Kathryn "Katy" Pridgen Physical Scientist NOAA-HSD OPS 240-533-0033

kathryn.pridgen@noaa.gov

On Fri, Jul 14, 2017 at 3:01 PM, Evans, Rod E. < RHODRI.E.EVANS@leidos.com > wrote:

Good afternoon Katy,

For TO03, please confirm or provide at your earliest convenience:

- Please confirm that the CSF and PRF files provided by Emily Clark on 23 June 2017 named OPR-K371-KR-17_CSF_new.000 and OPR-K371-KR-17_PRF_new.000 are the final CSF and PRF files. If not, can the final files please be provided?
 - Tides *.ZDF file (i.e. tide zone coordinates);
 - Coast Pilot report/excerpts to be updated.

Thanks again, Rod.

Rod Evans Ph.D | Leidos

Branch Manager (Marine Survey and Engineering Solutions Branch) Survey & Marine Operations Business Area Manager Maritime Solutions Division

phone: <u>401.848.4783</u>

evansrh@leidos.com | leidos.com/natsec

"What would an ocean be without a monster lurking in the dark? It would be like sleep without dreams."

Werner Herzog



This email and any attachments to it are intended only for the identified recipients. It may contain proprietary or otherwise legally protected information of Leidos. Any unauthorized use or disclosure of this communication is strictly prohibited. If you have received this communication in error, please notify the sender and delete or otherwise destroy the email and all attachments immediately.

From: Emily Clark - NOAA Federal [mailto:emily.clark@noaa.gov]

Sent: Friday, July 14, 2017 10:35 AM

To: Evans, Rod E.; Lepore, Christine A.; Wise, Michael J.; Kathryn Pridgen - NOAA Federal

Subject: EXTERNAL: Award EA-133C-14-CQ-0033 T-0003

Good Morning,

Attached is awarded task order EA-133C-14-CQ-0033 T-0003. COR designation MEMO is also attached for Katy's signature.

Please respond showing receipt of this award at your earliest convenience.

Thanks

--

v/r,

Emily Clark

Contract Specialist, NOAA AGO Eastern Region Acquisition Division Supporting National Ocean Service 200 Granby Street, Suite 815 Norfolk, VA 23510

Phone: 757-441-6875

Sent: Wednesday, November 29, 2017 3:33 PM

To: Evans, Rod E. [US-US]

Subject: EXTERNAL: New OCS website

Rod,

A new website has been published for the HSD Standards and Requirements webpage:

https://www.nauticalcharts.noaa.gov/publications/standards-and-requirements.html

On this webpage you will find the following downloads:

- NOAA Hydrographic Specifications and Deliverables
- XML Descriptive Report schema release package

Please refer to the documents on this webpage for your current 2018 task order.

Thanks, Katy

Kathryn "Katy" Pridgen Physical Scientist NOAA-HSD OPS 240-533-0033

kathryn.pridgen@noaa.gov

From: Quintal, Rebecca T. [US-US]

Sent: Thursday, December 21, 2017 10:33 AM

To: 'Kathryn Pridgen - NOAA Federal' <kathryn.pridgen@noaa.gov>;

'survey.outlines@noaa.gov' <survey.outlines@noaa.gov>; 'starla.robinson@noaa.gov' <starla.robinson@noaa.gov>

Cc: Rhodri E. Evans com; Paul Donaldson

<PAUL.L.DONALDSON@leidos.com>; Bridget Bernier
<bridget.w.bernier@leidos.com>; Bernier, Alex T. [US-US]

<ALEX.T.BERNIER@leidos.com>

Subject: Survey Outlines for final 2 Sheets on OPR-K371-KR-17 (H13056 and H13057)

Attachments: H13056_Survey_Outline.000, H13057_Survey_Outline.000

Katy,

Please find attached the Survey Outline files for H13056 (Sheet 3) and H13057 (Sheet 4), from OPR-K371-KR-17, Sabine, LA, Task Order-0003.

The survey outlines have been generated as S-57 Feature Object Class M_COVR in .000 format (WGS84 datum, un-projected) as specified in the April 2017 HSSD (Section 8.1.2).

Please let me know if you have any questions.

Thank you, -Rebecca

Rebecca T. Quintal | Leidos

Hydrographic Survey & Data Solutions Manager Marine Survey & Engineering Solutions

office: 401.848.4607 mobile: 401.829.6242

rebecca.t.quintal@leidos.com



Sent: Monday, January 29, 2018 2:15 PM

To: Evans, Rod E. [US-US] <RHODRI.E.EVANS@leidos.com>; Quintal, Rebecca T. [US-US]

<REBECCA.T.QUINTAL@leidos.com>

Subject: EXTERNAL: Follow up on some guestions on HSSD

Rod and Rebecca,

We have being working on addressing all the tickets submitted about the HSSD and updating the new version of the HSSD coming out soon. I wanted to follow up with you about some of the questions that you submitting that I can answer one on one that do not really warrant a change to the HSSD. See below, my answers are in bold:

- 1. Section 7.5.2, "NOAA Extended Attributes" (Pg. 98): Under "sftype" the option of CROWDSOURCE is not listed in the provided table.
 - a. [Note this was also the case in 2016, we found it by using the NOAA Extended Attribute library; all of the 2016 wellheads were CROWDSOURCE].

Please use to remarks section to explain the that these features are wellheads under the SORIND attribute. Wellheads do not need to be attributed in sftype as they are not ATONs, DTON, maritime boundary point, or LIDAR feature.

- 1. Section 8.1.4, "Descriptive Report (DR)" (Pg. 111): Abnormal Seafloor or Environmental Conditions section
 - a. Leidos observed in the 2016 Schema that the section header for this part of the DR had not been updated to reflect the change in HSSD. Is there going to be a new schema?

"Abnormal Seafloor or Environmental Conditions" section is not in HSSD online schema. It is in the zip file on this page: https://nauticalcharts.noaa.gov/publications/standards-and-requirements.html

- 1. Appendix J (Pg. 146): Under Processed/Sonar_Data/HXXXXX
- a. Please confirm this is where the multibeam, side scan, and delayed heave files would be delivered?

Delayed Heave is a raw .000 from the POS so it goes under preprocess

b. Is there a requirement on naming convention of sub-directories?

There is no naming convention for subdirectories.

c. Is there a requirement to separate out mainscheme and crossline data into sub-directories?

Crosslines and mainscheme don't need to be in different directories

T . 1 'C 1	1.11.1 1	T 1 .1			
Let me know if you have any	zaddifional dijestions i	I hone the proc	essing of	data is	oning well!

Katy

Sent: Friday, February 02, 2018 12:20 PM

To: Bernier, Bridget W. [US-US] < BRIDGET.W.BERNIER@leidos.com>

Cc: Quintal, Rebecca T. [US-US] <REBECCA.T.QUINTAL@leidos.com>; Evans, Rod E. [US-US]

<RHODRI.E.EVANS@leidos.com>; Donaldson, Paul L. [US-US]

<PAUL.L.DONALDSON@leidos.com>; Bernier, Alex T. [US-US] <ALEX.T.BERNIER@leidos.com>; Tiffany Squyres - NOAA Federal <Tiffany.Squyres@noaa.gov>; Christina Fandel - NOAA Federal

<christina.fandel@noaa.gov>; Corey Allen - NOAA Federal <corey.allen@noaa.gov>

Subject: Re: EXTERNAL: Re: Questions about XML schema

Bridget

It is fine to submit the survey with the PDF saying "A.Survey Coverage" instead of "A.4" Please include this email in your correspondence folder in the deliverable.

K	at	y

Kathryn "Katy" Pridgen
Physical Scientist
NOAA-HSD OPS
240-533-0033
kathryn.pridgen@noaa.gov

On Fri, Feb 2, 2018 at 12:08 PM, Bernier, Bridget W.

<BRIDGET.W.BERNIER@leidos.com> wrote:

Katy,

After we received your email, we downloaded the 2017 schema from the link you provided on 30 January.

We no longer receive the warning message about the Appendices.xsd (Question 3).

However, when we convert to PDF we are still seeing that the section Survey Coverage is listed as "A. Survey Coverage" not "A.4 Survey Coverage" (Question 2).

When we compared the DR_Stylesheet.xslt file between when we downloaded them, they are both dated 10/2/2017. All other files in the zip file we downloaded 30 January are dated 1/9/2018.

Again, this is really more bringing the item to your attention, but we are just confirming that this is okay to submit as is?

Thanks,
-Bridget

From: Quintal, Rebecca T. [US-US]

Sent: Wednesday, January 31, 2018 11:11 AM

To: Kathryn Pridgen - NOAA Federal <kathryn.pridgen@noaa.gov>

Cc: Evans, Rod E. [US-US] <RHODRI.E.EVANS@leidos.com>; Bernier, Bridget W. [US-US]

<BRIDGET.W.BERNIER@leidos.com>; Donaldson, Paul L. [US-US]

<PAUL.L.DONALDSON@leidos.com>; Bernier, Alex T. [US-US] <ALEX.T.BERNIER@leidos.com>; Tiffany Squyres - NOAA Federal <Tiffany.Squyres@noaa.gov>; Christina Fandel - NOAA Federal

<christina.fandel@noaa.gov>; Corey Allen - NOAA Federal <corey.allen@noaa.gov>

Subject: Re: EXTERNAL: Re: Questions about XML schema

Thank you Katy. We have downloaded the latest version of the schema and will use it with no further cost to NOAA.

Thank you!

-Rebecca

Sent from Email+ secured by MobileIron

From: "Kathryn Pridgen - NOAA Federal" <<u>kathryn.pridgen@noaa.gov</u>>

Date: Tuesday, January 30, 2018 at 4:06:22 PM

To: "Quintal, Rebecca T. [US-US]" < REBECCA.T.QUINTAL@leidos.com>

 $\textbf{Cc: "Evans, Rod E. [US-US]"} < \underline{\textbf{RHODRI.E.EVANS@leidos.com}} >, "Bernier, Bridget W.$

[US-US]" < BRIDGET.W.BERNIER@leidos.com >, "Donaldson, Paul L. [US-US]"

<PAUL.L.DONALDSON@leidos.com>, "Bernier, Alex T. [US-US]"

<a href="mailto:

<a href="mai

<a href="mailto: Tiffany.Squyres@noaa.gov, "Christina Fandel - NOAA Federal"

<christina.fandel@noaa.gov>, "Corey Allen - NOAA Federal" <corey.allen@noaa.gov>

Subject: EXTERNAL: Re: Questions about XML schema

Rebecca.

Following your request, Leidos may use the 2017_01 version of the schema. The 2017_01 schema was recently updated (Jan 29, 2018) to include the Appendices.xsd (Question 3) file as well as address the "Survey Coverage" text issue (Question 2). If Leidos chooses to use the 2017_01 schema, they must download the latest version of the schema from the OCS website. Otherwise, version 2016_01 should be referenced. Given this request to use the 2017_01 schema was issued by Leidos, it is the government's understanding use of the 2017_01 schema for OPR-K371-KR-17 will not result in any additional cost. If this is not the case, Leidos must use the 2016_01 version of the schema as originally required in the task order.

In response to question 4, given this project requires discrete tides, your solution for producing a valid XML file in light of the required ERS fields is acceptable. A dummy value may also be used for the final tides requested date. We have logged both of these issues in our help desk ticketing system and will resolve them as soon as possible.

Please include this email in the correspondence folder in the final deliverable to facilitate communications with AHB.

Thank you

Katy

Kathryn "Katy" Pridgen
Physical Scientist
NOAA-HSD OPS
240-533-0033
kathryn.pridgen@noaa.gov

On Mon, Jan 29, 2018 at 2:20 PM, Quintal, Rebecca T. < REBECCA.T.QUINTAL@leidos.com > wrote: Hello Katy,

We have started working with the XML Schema in preparation for our upcoming deliveries on OPR-K371-KR-17 and we have the following questions.

- 1. Our OPR-K371-KR-17 Project Instructions indicate that we are to use "NOAA XML Hydrographic Reports, Version 2016_1", however we took a look at the 2017 XML Schema (final_2017_01) and found that there were several fixes that we are hoping to take advantage of for our OPR-K371-KR-17 submittals.
 - a. Is it acceptable that we deliver the OPR-K371-KR-17 DRs using the 2017 XML Schema (final_2017_01)?
- 2. When the XML is converted using the provided stylesheet, there is a section that has an incomplete header
 - a. The Section is listed in the PDF as "A Survey Coverage" instead of "A.4 Survey Coverage"
 - b. This section is also incomplete in the Table of Contents
 - c. This is really more bringing the item to your attention, but we are just confirming that this is okay to submit as is?
- 3. Missing file
 - a. Upon creating the XML in Altova XMLSpy from the provided files in the final_2017_01 zip file, we receive the following error message:

The schemas referenced by xsi:schemaLocation or xsi:noNamespaceSchemaLocation attributes at element <dr:descriptiveReport> are valid with warnings.

Unable to load a schema from 'Appendices.xsd'.

I/O operation on file

'M:\charlie\NOAA_Louisiana_2017\XML_Schema\final_2017_01\Appendices.xsd' failed.

Details

System Error 2: The system cannot find the file specified.

i. Note within final_2017_01 zip file there was no Appendices.xsd file. (The schema files were downloaded from the NOAA website 22 January 2018)

- b. We would like to confirm that the XML we create is still valid for NOAA even with this warning message.
- 4. As in the XML Schema we used to deliver our OPR-K371-KR-16 surveys, we have found sections having to do with ERS surveys in the 2017 XML Schema that we are having trouble with;
 - a. The fields were under Vertical Control "VDATUM_or_constantSep" and under Horizontal Control "PPK", both of which are related to ERS surveys, and OPR-K371-KR-17 surveys used traditional tides (zoning).
 - b. The solution last year was the following, based on guidance received from Christina Fandal on 09 January 2017, Leidos was able to validate the XML by attributing the above fields as "False" for the "used" field, and attributing the "methodsUsed" with a "dummy" option from the dropdown.
 - i. Is this approach acceptable for the OPR-K371-KR-17 surveys as well, traditional tides (zoning) were also used.
- 5. An additional field in the 2017 schema, that we also encountered in the 2016, was the dates for the final tides submitted and received.
 - a. As Leidos does not submit a request for final tides, is it acceptable for Leidos to use a generic date of 1970-01-01?

Thank you, -Rebecca

Rebecca T. Quintal | Leidos

Hydrographic Survey & Data Solutions Manager Marine Survey & Engineering Solutions

office: 401.848.4607 mobile: 401.829.6242

rebecca.t.quintal@leidos.com



From: Bernier, Alex T. [US-US]

Sent: Wednesday, February 07, 2018 9:43 AM

To: ocs.ecc@noaa.gov

Cc: kathryn.pridgen@noaa.gov; starla.robinson@noaa.gov; Evans, Rod E. [US-US]

<RHODRI.E.EVANS@leidos.com>; Quintal, Rebecca T. [US-US]

<REBECCA.T.QUINTAL@leidos.com>; Donaldson, Paul L. [US-US]

<PAUL.L.DONALDSON@leidos.com>; Bernier, Bridget W. [US-US]

<BRIDGET.W.BERNIER@leidos.com>

Subject: OPR-K371-KR-17 Marine Species Awareness Training

Attachments: OPR-K371-KR-17_Marine_Species_Awareness_Training_Video_Log.pdf

Per section 1.5 of the April 2017 NOS Hydrographic Surveys Specifications and Deliverables, please find attached the Marine Species Awareness Training log. The attached log captures a list of trained marine mammal observers and the date each observer viewed the training video as required under NOAA hydrographic survey contract EA-133C-14-CQ-0033, project number OPR-K371-KR-17, Task Order 0003 (Sabine and Vicinity).

Please contact me if there are any questions or problems with the attached.

Alex Bernier | Leidos

Lead Hydrographer | Marine Scientist Marine Survey & Engineering Solutions office: 401.848.4726 mobile: 508.494.3485

alex.t.bernier@leidos.com | leidos.com



From: Bernier, Alex T. [US-US]

Sent: Friday, February 09, 2018 4:18 PM

To: OCS.NDB@NOAA.GOV; Coast.Pilot@NOAA.GOV

Cc: kathryn.pridgen@noaa.gov; starla.robinson@noaa.gov; Evans, Rod E. [US-US]

<RHODRI.E.EVANS@leidos.com>; Quintal, Rebecca T. [US-US]

<REBECCA.T.QUINTAL@leidos.com>; Donaldson, Paul L. [US-US]

<PAUL.L.DONALDSON@leidos.com>; Bernier, Bridget W. [US-US]

<BRIDGET.W.BERNIER@leidos.com>

Subject: OPR-K371-KR-17 Coast Pilot Review Report

Attachments: OPR-K371-KR-17_Coast Pilot Review Report.pdf

Please find attached the Coast Pilot Review Report for Contract: EA-133C-14-CQ-0033, Project Number OPR-K371-KR-17, Task Order 0003 (Sabine and Vicinity). The one attached .pdf file submitted addresses the Coast Pilot Field Report delivered to Leidos for OPR-K371-KR-17, and a separate review of the text of the actual Coast Pilot paragraphs.

Please contact me if there are any questions or problems with the attached.

Alex Bernier | Leidos

Lead Hydrographer | Marine Scientist Marine Survey & Engineering Solutions office: 401.848.4726

mobile: 508.494.3485

alex.t.bernier@leidos.com | leidos.com



Sent: Tuesday, February 13, 2018 10:17 AM

To: Quintal, Rebecca T. [US-US] <REBECCA.T.QUINTAL@leidos.com> **Subject:** EXTERNAL: Re: Horizontal and Vertical Control Report

Rebecca.

Yes this procedure will work just fine.

Katy

Kathryn "Katy" Pridgen
Physical Scientist
NOAA-HSD OPS
240-533-0033
kathryn.pridgen@noaa.gov

On Wed, Feb 7, 2018 at 1:33 PM, Quintal, Rebecca T. < REBECCA.T.QUINTAL@leidos.com> wrote:

Hello Katy,

Based on previous feedback, Leidos has not submitted a Horizontal and Vertical Control Report for surveys that did not require vertical control stations to be installed or recovered and/or horizontal control station installed. Instead we have included a Readme.txt file in the Horizontal_&_Vertical_Control_Report folder stating along the lines of: "No vertical or horizontal controls were established, recovered, or occupied during the survey. Vertical and horizontal control specifics are discussed in each sheet's DR."

For OPR-K371-KR-17 no vertical or horizontal control stations were installed, recovered or occupied. However, we wanted to confirm with you that this is still acceptable for OPR-K371-KR-17 to not deliver a HVCR.

Let us know if you would like to discuss.

Thank you, -Rebecca

Rebecca T. Quintal | Leidos

Hydrographic Survey & Data Solutions Manager Marine Survey & Engineering Solutions

office: <u>401.848.4607</u> mobile: <u>401.829.6242</u>

rebecca.t.quintal@leidos.com



From: Donaldson, Paul L. [US-US]

Sent: Tuesday, March 06, 2018 2:48 PM

To: kathryn.pridgen@noaa.gov; starla.robinson@noaa.gov

Cc: Evans, Rod E. [US-US] <RHODRI.E.EVANS@leidos.com>; Quintal, Rebecca T.

[US-US] <REBECCA.T.OUINTAL@leidos.com>; Bernier, Bridget W. [US-US]

<BRIDGET.W.BERNIER@leidos.com>; Bernier, Alex T. [US-US]

<ALEX.T.BERNIER@leidos.com>

Subject: OPR-K371-KR-17 Non-DTON Seep and Pipeline Report, Exposed Pipelines 1 – 5 for H13056

Attachments: H13056_ExposedPipelines_ALL_Chart_11330.png,

H13056_ExposedPipelines_01.zip, H13056_ExposedPipelines_02.zip,

H13056_ExposedPipelines_03.zip, H13056_ExposedPipelines_04.zip,

H13056_ExposedPipelines_05.zip

While surveying in the Gulf of Mexico on Project Number OPR-K371-KR-17 Leidos discovered five sections of exposed pipeline within the area of Registry Number H13056. The exposed pipelines were found through analysis of the MBES and SSS data and determined to have a signature discernibly consistent with that of an exposed pipeline. All five features are also within close proximity of currently charted pipelines. The details of each exposed pipeline are as follows and images of each are contained in the attached zip directories.

- H13056 Exposed Pipeline #1 consisted of 2 exposed sections of pipeline in 28° 59" 48.85'N, 093° 30" 00.64'W, and 28° 59" 49.02'N, 093° 30" 02.50'W. Each exposed section is approximately 7 to 10 meters in length and approximately 50 meters apart in a northwest/southeast orientation and is associated with a charted pipeline. The shoalest exposed section was observed on Julian Day 287 (14 October 2017) at 2157 UTC, and is 0.50m high in 23.81m of water (23.312m least depth).
- H13056 Exposed Pipeline #2 was found at 28° 55" 13.68'N, 093° 19" 31.48'W, on Julian Day 337 (03 December 2017) at 1745 UTC. This feature is a 7 meter long section of exposed pipeline found in a northwest/southeast orientation and is approximately 0.19m high in 22.76m of water (22.566m least depth). It is positioned at the junction of charted pipelines.
- H13056 Exposed Pipeline #3 consists of prolonged exposed sections of pipeline approximately 1000-meter long extending from approximately 28° 55" 25.60'N, 093° 17" 33.98'W to 28° 55" 01.13'N, 093° 17" 48.32'W. The shoalest depth in 28° 55" 11.80'N, 093° 17" 44.98'W was identified on Julian Day 337 (03 December 2017) at 1855 UTC and is approximately 0.18m high in 23.23m of water (23.052m least depth). The exposed section is associated with a charted pipeline.

- H13056 Exposed Pipeline #4 consists of multiple exposed sections of pipeline over approximately 130 meters from 29° 00" 15.57'N, 093° 29" 25.54'W, to 29° 00" 12.45'N, 093° 29" 23.73'W. This feature is in a northwest/southeast orientation with the shoalest depth identified on Julian Day 338 (04 December 2017) at 1136 UTC and approximately 0.69m high in 23.83m of water (23.14m least depth). It is positioned perpendicular to a charted pipeline.
- H13056 Exposed Pipeline #5 consists of multiple exposed sections over approximately 2700 meters from 29° 00" 27.59'N, 093° 29" 01.20'W, to 28° 59" 33.35'N, 093° 30" 16.09'W. This feature is in a northeast/southwest orientation with the shoalest depth identified on Julian Day 338 (04 December 2017) at 1252 UTC and is approximately 0.23m high in 23.47m of water (23.236m least depth). The exposed sections are associated with a charted pipeline.

Please feel free to contact us if there are any questions with the information above or attached image files.

Thank you,

-Paul Donaldson

Paul L. Donaldson CH (NSPS #241)|Leidos

Survey Operations Coordinator/Chief Hydrographer

Phone: 401.848.4757 Mobile: 860.857.8802 Fax: 401.849.1585

Email: paul.l.donaldson@leidos.com

221 Third Street, Building A Newport, RI 02840 USA Leidos.com From: Donaldson, Paul L. [US-US] Sent: Friday, March 09, 2018 11:30 AM To: NODC.submissions@noaa.gov

Cc: kathryn.pridgen@noaa.gov; starla.robinson@noaa.gov; Evans, Rod E. [US-US]

<RHODRI.E.EVANS@leidos.com>; Quintal, Rebecca T. [US-US]<REBECCA.T.QUINTAL@leidos.com>; Bernier, Bridget W. [US-US]<BRIDGET.W.BERNIER@leidos.com>; Bernier, Alex T. [US-US]

<ALEX.T.BERNIER@leidos.com>

Subject: OPR-K371-KR-17 NetCDF Sound Speed Data Files

Attachments: OPR-K371-KR-17_20180309.zip

In accordance with Section 8.3.6 of the Hydrographic Surveys Specifications and Deliverables, please find attached one zip file (OPR-K371-KR-17_20180309.zip) containing sound speed data in the NetCDF format used for Leidos hydrographic surveys under project number OPR-K371-KR-17 (Contract: EA-133C-14-CQ-0033 T- 0003, Sabine and Vicinity, Sheets 1-4).

All individual sound speed profile files are delivered with the required .nc file extension and fields are populated with the project, survey, survey unit, and instrument. In addition, sound speed data files are broken out into four sub-folders, which correspond to the purpose of each cast as indicated below

- · OPR-K371-KR-17 NCEI Used for Lead Line
- OPR-K371-KR-17_NCEI_Used_for_Final_Surfaces
- OPR-K371-KR-17 NCEI Used for Comparison
- · OPR-K371-KR-17_NCEI_Used_for_Closing

Please contact me if there are any questions or problems with the attached.

Thank you,

Paul Donaldson

Paul L. Donaldson CH (NSPS #241)|Leidos

Survey Operations Coordinator/Chief Hydrographer

Phone: 401.848.4757 Mobile: 860.857.8802 Fax: 401.849.1585

Email: paul.l.donaldson@leidos.com

221 Third Street, Building A Newport, RI 02840 USA Leidos.com From: Donaldson, Paul L. [US-US] Sent: Friday, March 09, 2018 11:33 AM

To: OCS.ECC@noaa.gov; larisa.avens@noaa.gov

Cc: kathryn.pridgen@noaa.gov; starla.robinson@noaa.gov; Evans, Rod E. [US-US]

<RHODRI.E.EVANS@leidos.com>; Quintal, Rebecca T. [US-US]
<REBECCA.T.QUINTAL@leidos.com>; Bernier, Bridget W. [US-US]

<BRIDGET.W.BERNIER@leidos.com>; Bernier, Alex T. [US-US]

<ALEX.T.BERNIER@leidos.com>

Subject: OPR-K371-KR-17 (Contract: EA-133C-14-CQ-0033 T- 0003, Sabine and

Vicinity, Sheets 1-4) Sea Turtle Observations

Attachments: OPR-K371-KR-17_OCS_Sea_Turtle_Observation_Log.pdf

In accordance with Section 1.5 of the Hydrographic Surveys Specifications and Deliverables, please find attached the Sea Turtle Observations Delivery for OPR-K371-KR-17 (Contract: EA-133C-14-CQ-0033 T- 0003, Sabine and Vicinity, Sheets 1-4).

The attached .pdf file submitted is of the individual Sea Turtle Observation Log generated throughout the duration of OPR-K371-KR-17.

Please contact me if there are any questions or problems with the attached.

Thank you,

-Paul Donaldson

Paul L. Donaldson CH (NSPS #241)|Leidos

Survey Operations Coordinator/Chief Hydrographer

Phone: 401.848.4757 Mobile: 860.857.8802 Fax: 401.849.1585

Email: paul.l.donaldson@leidos.com

221 Third Street, Building A Newport, RI 02840 USA Leidos.com From: Donaldson, Paul L. [US-US] Sent: Friday, March 09, 2018 11:34 AM

To: pop.information@noaa.gov

Cc: kathryn.pridgen@noaa.gov; starla.robinson@noaa.gov; Evans, Rod E. [US-US]

<RHODRI.E.EVANS@leidos.com>; Quintal, Rebecca T. [US-US]
<REBECCA.T.QUINTAL@leidos.com>; Bernier, Bridget W. [US-US]

<BRIDGET.W.BERNIER@leidos.com>; Bernier, Alex T. [US-US]

<ALEX.T.BERNIER@leidos.com>

Subject: OPR-K371-KR-17 (Contract: EA-133C-14-CQ-0033 T- 0003, Sabine and

Vicinity, Sheets 1-4) Marine Mammal Observations

Attachments: OPR-K371-KR-17_Marine_Mammal_Observation_Log.pdf

In accordance with Section 1.5 of the Hydrographic Surveys Specifications and Deliverables, please find attached the Marine Mammal Observations Delivery for OPR-K371-KR-17 (Contract: EA-133C-14-CQ-0033 T- 0003, Sabine and Vicinity, Sheets 1-4).

The attached .pdf file submitted is a compilation of the individual Marine Mammal Observation Logs generated throughout the duration of OPR-K371-KR-17.

Please contact me if there are any questions or problems with the attached.

Thank you,

-Paul Donaldson

Paul L. Donaldson CH (NSPS #241)|Leidos

Survey Operations Coordinator/Chief Hydrographer

Phone: 401.848.4757 Mobile: 860.857.8802 Fax: 401.849.1585

Email: paul.l.donaldson@leidos.com

221 Third Street, Building A Newport, RI 02840 USA Leidos.com

Project: OPR-K371-KR-17

APPROVAL PAGE

H13056

Data meet or exceed current specifications as certified by the OCS survey acceptance review process. Descriptive Report and survey data except where noted are adequate to supersede prior surveys and nautical charts in the common area.

The following products will be sent to NCEI for archive

- Descriptive Report
- Data Acquisition and Processing Report
- Collection of Bathymetric Attributed Grids (BAGs)
- Processed survey data and records
- GeoPDF of survey products
- Collection of Backscatter mosaics

The survey evaluation and verification has been conducted according current OCS Specifications, and the survey has been approved for dissemination and usage of updating NOAA's suite of nautical charts.

Approved:			
ADDIOVEG.			

Commander Meghan McGovern, NOAA

Chief, Atlantic Hydrographic Branch