

## C.1 Vertical Control

The vertical datum for this project is Mean Lower Low Water.

### ERS Datum Transformation

The following ellipsoid-to-chart vertical datum transformation was used:

Method	Ellipsoid to Chart Datum Separation File
ERS via VDATUM	OPR-K371-KR-19_NAD83_VDatum_MLLW.cov

*Table 13: ERS method and SEP file*

Refer to the DAPR for details regarding the application of VDatum to the MBES data files. No final tide note was provided from NOAA Center for Operational Oceanographic Products and Services (CO-OPS). While a final tide note was not required, a final tide note has been provided by Leidos in Appendix I.

## C.2 Horizontal Control

The horizontal datum for this project is North American Datum of 1983 (NAD 83).

The projection used for this project is Universal Transverse Mercator (UTM) Zone 15.

### PPP

The vessel kinematic data (POS/MV files) were post-processed in Applanix POSPac software using the Applanix PP-RTX solution to generate the Smoothed Best Estimate of Trajectory (SBET) solutions which were applied through SABER to the multibeam data. Refer to the DAPR for additional information and for details regarding all antenna and transducer offsets. Any soundings with total horizontal uncertainties exceeding the maximum allowable IHO S-44 5th Edition Order 1a specifications were flagged as invalid and therefore were not used in the CUBE depth calculations.