

U.S. Department of Commerce
National Oceanic and Atmospheric Administration
National Ocean Service

DESCRIPTIVE REPORT

Type of Survey: Basic Hydrographic Survey

Registry Number: H13772

LOCALITY

State(s): Virginia

General Locality: Southwest Chesapeake Bay

Sub-locality: Pamunkey and Mattaponi Rivers

2023

CHIEF OF PARTY
David Neff, C.H.

LIBRARY & ARCHIVES

Date:

H13772

HYDROGRAPHIC TITLE SHEET

H13772

INSTRUCTIONS: The Hydrographic Sheet should be accompanied by this form, filled in as completely as possible, when the sheet is forwarded to the Office.

State(s): **Virginia**

General Locality: **Southwest Chesapeake Bay**

Sub-Locality: **Pamunkey and Mattaponi Rivers**

Scale: **10000**

Dates of Survey: **06/05/2023 to 12/14/2023**

Instructions Dated: **03/08/2023**

Project Number: **OPR-E351-KR-22**

Field Unit: **eTrac**

Chief of Party: **David Neff, C.H.**

Soundings by: **Multibeam Echo Sounder**

Imagery by: **Multibeam Echo Sounder Backscatter Side Scan Sonar**

Verification by: **Atlantic Hydrographic Branch**

Soundings Acquired in: **meters at Mean Lower Low Water**

Remarks:

All times are UTC. The purpose of this survey is to update existing NOS nautical charts. H13772 covers approximately 9 square nautical miles of the Pamunkey and Mattaponi Rivers, Virginia.

Any revisions to the Descriptive Report (DR) applied during office processing are shown in red italic text. The DR is maintained as a field unit product, therefore all information and recommendations within this report are considered preliminary unless otherwise noted. The final disposition of survey data is represented in the NOAA nautical chart products. All pertinent records for this survey are archived at the National Centers for Environmental Information (NCEI) and can be retrieved via <https://www.ncei.noaa.gov/>. Products created during office processing were generated in NAD83 UTM 18N, Mean Lower Low Water. All references to other horizontal or vertical datums in this report are applicable to the processed hydrographic data provided by the field unit.

Table of Contents

A. Area Surveyed	1
A.1 Survey Limits.....	1
A.2 Survey Purpose.....	3
A.3 Survey Quality.....	3
A.4 Survey Coverage.....	4
A.6 Survey Statistics.....	6
B. Data Acquisition and Processing	9
B.1 Equipment and Vessels.....	9
B.1.1 Vessels.....	9
B.1.2 Equipment.....	10
B.2 Quality Control.....	10
B.2.1 Crosslines.....	10
B.2.2 Uncertainty.....	11
B.2.3 Junctions.....	12
B.2.4 Sonar QC Checks.....	14
B.2.5 Equipment Effectiveness.....	14
B.2.6 Factors Affecting Soundings.....	14
B.2.7 Sound Speed Methods.....	14
B.2.8 Coverage Equipment and Methods.....	15
B.2.9 Data Density Evaluation.....	15
B.3 Echo Sounding Corrections.....	16
B.3.1 Corrections to Echo Soundings.....	16
B.3.2 Calibrations.....	16
B.4 Backscatter.....	16
B.5 Data Processing.....	17
B.5.1 Primary Data Processing Software.....	17
B.5.2 Surfaces.....	17
B.5.3 Additional Task: Final Data Submission - Grids.....	20
C. Vertical and Horizontal Control	21
C.1 Vertical Control.....	21
C.2 Horizontal Control.....	21
C.3 Additional Horizontal or Vertical Control Issues.....	22
C.3.1 Additional Task: Final Data Submission - Grids.....	22
D. Results and Recommendations	22
D.1 Chart Comparison.....	22
D.1.1 Electronic Navigational Charts.....	23
D.1.2 Shoal and Hazardous Features.....	23
D.1.3 Charted Features.....	24
D.1.4 Uncharted Features.....	24
D.1.5 Channels.....	24
D.2 Additional Results.....	24
D.2.1 Aids to Navigation.....	24
D.2.2 Maritime Boundary Points.....	24

D.2.3 Bottom Samples.....	25
D.2.4 Overhead Features.....	25
D.2.5 Submarine Features.....	25
D.2.6 Platforms.....	25
D.2.7 Ferry Routes and Terminals.....	25
D.2.8 Abnormal Seafloor or Environmental Conditions.....	25
D.2.9 Construction and Dredging.....	26
D.2.10 New Survey Recommendations.....	26
D.2.11 ENC Scale Recommendations.....	27
E. Approval Sheet.....	28
F. Table of Acronyms.....	29

List of Tables

Table 1: Survey Limits.....	1
Table 2: Survey Coverage.....	4
Table 3: Hydrographic Survey Statistics.....	7
Table 4: Dates of Hydrography.....	8
Table 5: Vessels Used.....	9
Table 6: Major Systems Used.....	10
Table 7: Survey Specific Tide TPU Values.....	11
Table 8: Survey Specific Sound Speed TPU Values.....	11
Table 9: Junctioning Surveys.....	13
Table 10: Submitted Surfaces.....	17
Table 11: ERS method and SEP file.....	21
Table 12: Largest Scale ENCs.....	23

List of Figures

Figure 1: Survey Limits Overview (light blue area).....	2
Figure 2: Survey Limits (black line).....	3
Figure 3: Survey Coverage with combined MBES and SSS.....	5
Figure 4: Coverage gap due to low bridge clearance.....	6
Figure 5: H13772 Crossline Comparison.....	11
Figure 6: H13772 Finalized 1m MBES TVU Statistics.....	12
Figure 7: H13772 - H13773 Junction Comparison.....	13
Figure 8: H13772 - H13773 Difference Statistics.....	14
Figure 9: H13772 Finalized 1m Set Line Spacing MBES Density Distribution.....	16
Figure 10: H13772 Finalized 1m CUBE Weighted Dynamic Surface Coverage.....	18
Figure 11: H13772 Finalized 2m MBAB mosaics.....	19
Figure 12: H13772 Finalized 1m SSS mosaics.....	20
Figure 13: Generated Soundings used for Chart Comparison (US5VA62M).....	23
Figure 14: Abnormal Seafloor Condition observed in Pamunkey River.....	26

Descriptive Report to Accompany Survey H13772

Project: OPR-E351-KR-22

Locality: Southwest Chesapeake Bay

Sublocality: Pamunkey and Mattaponi Rivers

Scale: 1:10000

June 2023 - December 2023

eTrac

Chief of Party: David Neff, C.H.

A. Area Surveyed

eTrac conducted hydrographic survey operations in the Pamunkey and Mattaponi Rivers, Virginia. H13772 covers approximately 9 square nautical miles of survey area. 306.83 linear nautical miles were acquired during the survey.

Survey was conducted within these limits between June 05, 2023 (DN156) and December 14, 2023 (DN348).

A.1 Survey Limits

Data were acquired within the following survey limits:

Northwest Limit	Southeast Limit
37° 45' 0.76" N 77° 4' 14.4" W	37° 31' 21.42" N 76° 46' 21.91" W

Table 1: Survey Limits

All data were acquired in accordance with the requirements in the Hydrographic Survey Project Instructions and specifications set forth in the Hydrographic Survey Specifications and Deliverables 2022 Edition (HSSD 2022).




Figure 1: Survey Limits Overview (light blue area)




Figure 2: Survey Limits (black line)

A.2 Survey Purpose

The principal objective of the Southwest Chesapeake Bay Rivers project is manifold. This survey will supply forecasters and decision makers at the NOAA National Water Center with bathymetric data for critical hydrodynamic modeling. This data is necessary to understand the timing of rapid river stage increases and decreases, the duration of high water, inundation, or drought. This survey will emphasize features that effect safe navigation and update the Office of Coast Survey Nautical charts and services.

A.3 Survey Quality

The entire survey is adequate to supersede previous data.

Survey H13772 is accurate to International Hydrographic Organization (IHO) Order 1a as required per the HSSD 2022.

A.4 Survey Coverage

The following table lists the coverage requirements for this survey as assigned in the project instructions:

Water Depth	Coverage Required
All waters in survey area	Complete Coverage Option B
All waters in survey area 2 to 8 m water depth	Sidescan Sonar Data may be aquired at an altitude of 6-20% of the range-scale

Table 2: Survey Coverage

Survey coverage was in accordance with the requirements listed above and in the HSSD 2022.

Note: Survey coverage did not extend to the entire survey boundary as the Navigable Area Limit Line (NALL) was reached. However there are occasionally small gaps in the side side scan mosaic along the NALL due to the inability to safely tow the side scan up to the NALL which would require operating the vessel beyond the NALL.

Gaps in complete survey coverage exist due to the presence of low clearance bridges. An example of a coverage gap due to low clearance bridges is presented below.




Figure 3: Survey Coverage with combined MBES and SSS




Figure 4: Coverage gap due to low bridge clearance

A.6 Survey Statistics

The following table lists the mainscheme and crossline acquisition mileage for this survey:

	HULL ID	<i>R/V Pulse</i>	<i>R/V 505</i>	<i>Total</i>
LNM	SBES Mainscheme	0.0	0.0	0.0
	MBES Mainscheme	0.0	0.0	0.0
	Lidar Mainscheme	0.0	0.0	0.0
	SSS Mainscheme	0.0	0.0	0.0
	SBES/SSS Mainscheme	0.0	0.0	0.0
	MBES/SSS Mainscheme	41.29	244.68	285.97
	SBES/MBES Crosslines	0.0	20.86	20.86
	Lidar Crosslines	0.0	0.0	0.0
Number of Bottom Samples				17
Number Maritime Boundary Points Investigated				0
Number of DPs				0
Number of Items Investigated by Dive Ops				0
Total SNM				9.65

Table 3: Hydrographic Survey Statistics

The following table lists the specific dates of data acquisition for this survey:

Survey Dates	Day of the Year
06/05/2023	156

Survey Dates	Day of the Year
06/06/2023	157
06/07/2023	158
06/09/2023	160
06/10/2023	161
06/11/2023	162
06/13/2023	164
06/14/2023	165
06/15/2023	166
06/24/2023	175
06/25/2023	176
06/26/2023	177
06/29/2023	180
09/02/2023	245
09/03/2023	246
09/04/2023	247
09/06/2023	249
09/08/2023	251
09/09/2023	252
09/10/2023	253
09/11/2023	254
09/12/2023	255
09/13/2023	256
09/20/2023	263
12/14/2023	348

Table 4: Dates of Hydrography

On 6/29/2023 assigned shoreline features were found using a hand held range finder, no MBES data was collected.

B. Data Acquisition and Processing

B.1 Equipment and Vessels

Refer to the Data Acquisition and Processing Report (DAPR) for a complete description of data acquisition and processing systems, survey vessels, quality control procedures and data processing methods. Additional information to supplement sounding and survey data are discussed in the following sections.

B.1.1 Vessels

The following vessels were used for data acquisition during this survey:

Hull ID	<i>R/V Pulse</i>	<i>R/V 505</i>
LOA	7.3 meters	10.0 meters
Draft	0.6 meters	0.6 meters

Table 5: Vessels Used

The R/V Pulse is a 7.3 aluminum monohull equipped with a Universal Sonar Mount (USM) starboard multibeam pole mount and davit.

The R/V 505 is a 10 meter aluminum catamaran equipped with a Universal Sonar Mount (USM) starboard multibeam pole mount and davit.

B.1.2 Equipment

The following major systems were used for data acquisition during this survey:

Manufacturer	Model	Type
R2Sonic	2022	MBES
R2Sonic	2024	MBES
AML Oceanographic	AML-3 LGR	Sound Speed System
AML Oceanographic	MicroX SV	Sound Speed System
AML Oceanographic	BaseX2	Sound Speed System
Applanix	POS MV OceanMaster	Positioning and Attitude System
Applanix	POS MV WaveMaster	Positioning and Attitude System
EdgeTech	4125	SSS

Table 6: Major Systems Used

R/V Pulse utilized a single head R2Sonic 2024 multibeam echosounder system (MBES), an AML 3-RT for the surface sound speed system, an AML-3 LGR for the sound speed system, an Applanix POSMV WaveMaster for the positioning and attitude system, and an EdgeTech 4125 side scan sonar (SSS).

R/V 505 utilized a single head R2Sonic 2022 multibeam echosounder system (MBES), an AML Micro.X for the surface sound speed system, an AML Base.X2 for the sound speed system, an Applanix POSMV OceanMaster for the positioning and attitude system, and an EdgeTech 4125 side scan sonar (SSS).

B.2 Quality Control

B.2.1 Crosslines

A beam-to-beam statistical analysis was performed using the Cross Check tool in Qimera. A 1 meter Combined Uncertainty and Bathymetric Estimator (CUBE) weighted dynamic surface was created incorporating only the mainscheme lines and excluded crosslines. The Cross Check tool was used to perform the beam-by-beam comparison of the crossline data to the mainscheme surface. Comparisons showed excellent agreement, well above 95% of the allowable TVU.

The percentage of crossline miles as compared to main scheme miles was 7.29%

Note: This surface was created for QC only and is not submitted as a surface deliverable.

Below is a histogram of the crossline comparison statistics showing IHO Order 1a compliance per beam.




Figure 5: H13772 Crossline Comparison

B.2.2 Uncertainty

The following survey specific parameters were used for this survey:

Method	Measured	Zoning
ERS via ERTDM	0.1 meters	N/A

Table 7: Survey Specific Tide TPU Values.

Hull ID	Measured - CTD	Measured - MVP	Measured - XBT	Surface
R/V Pulse	0.05 meters/second	N/A	N/A	0.2 meters/second
R/V 505	0.05 meters/second	N/A	N/A	0.2 meters/second

Table 8: Survey Specific Sound Speed TPU Values.

The standard deviation uncertainty and the total vertical uncertainty (TVU) layers of the Dynamic Surface were utilized during data processing to search for features, water column noise, and systematic errors.

IHO Order 1a uncertainty specification was met by 100% of the nodes.

In Qimera versions beginning in 2.5.1 and beyond, the user has the ability to export the Dynamic Surface to a Bathymetric Attributed Grid (BAG) with the TVU layer.

Using this BAG, the percentage of nodes that fell within the TVU specification for each Dynamic Surface was calculated using the NOAA QC tools program. These results are shown in an image below.

Complete Coverage Option B MBES (Finalized 1m CUBE weighted Dynamic Surface in NOAA QC Tools) = 100% of nodes are within the allowable TVU.




Figure 6: H13772 Finalized 1m MBES TVU Statistics

B.2.3 Junctions

Depth differences between junctioning surveys were evaluated using the JunctionTrac program, developed in-house by eTrac. For each junction, each CUBE weighted dynamic surface's nodes were exported to an ASCII CSV file where the fields were (Easting, Northing, Depth) for each node. A 1 meter difference surface between the junctioning datasets was also created and exported to an ASCII CSV file where the fields were (Easting, Northing, Diff) for each node. The three ASCII CSV files were then loaded into the JunctionTrac program and junction statistics were computed. A file was also created in this process to locate any nodes from the difference surface that exceed the allowable TVU, which was imported into Qimera

and any identified points from JunctionTrac were analyzed. Note: the difference surfaces were created for comparison efforts only and are not submitted as surface deliverables.

The following junctions were made with this survey:

Registry Number	Scale	Year	Field Unit	Relative Location
H13773	1:10000	2023	eTrac	S

Table 9: Junctioning Surveys

H13773

The junction comparison was performed using all overlapping data between H13772 and H13773. Below is a histogram of junction comparison statistics showing the difference between the junctioning surfaces and allowable TVU as well as difference statistics. 99.9695% of nodes were within allowable TVU.

Note: Spikes above allowable TVU were caused by overlapping data on features where there is slight variation in the coordinates of each surface's node for the least depth of the feature.




Figure 7: H13772 - H13773 Junction Comparison

Criteria	Number of Nodes	Resulting %
DIFF < 10cm	20366	88.63%
10cm < DIFF < 20cm	2334	10.16%
20cm < DIFF < 30cm	261	1.14%
30cm < DIFF < 50cm	11	0.05%
DIFF > 50cm	7	0.03%
Total	22979	100.00%

Figure 8: H13772 - H13773 Difference Statistics

B.2.4 Sonar QC Checks

Sonar system quality control checks were conducted as detailed in the quality control section of the DAPR.

B.2.5 Equipment Effectiveness

There were no conditions or deficiencies that affected equipment operational effectiveness.

B.2.6 Factors Affecting Soundings

There were no other factors that affected corrections to soundings.

B.2.7 Sound Speed Methods

Sound Speed Cast Frequency: SVP casts were generally taken every 2 hours. Occasionally casts would exceed a 2 hour frequency, however would never exceed a 4 hour frequency.

On R/V Pulse and R/V 505 casts were applied in QPS Qinsy acquisition software at the time of the cast. Surface SVP measured at 1Hz was compared to surface speed from the current profile in real-time. If the surface velocity comparison was in excess of 2m/s at any time during survey operations, a new cast was taken.

Surface sound speeds were compared in real-time and profile to profile for each cast on the vessel. Additionally, the processor reviewed profiles in Qimera to remove spurious readings within a cast, compare day-to-day casts, and to check distribution over the surveyed area, in order to better understand trends for efficient acquisition planning.

B.2.8 Coverage Equipment and Methods

All equipment and survey methods were used as detailed in the DAPR.

B.2.9 Data Density Evaluation

In order to determine if the density of the data met the specified 5 soundings per node, data density was evaluated using DensityTrac in the AmiTrac program, developed in-house by eTrac. Each finalized CUBE weighted dynamic surface's nodes were exported to a BBH file. The BBH file was then loaded into the DensityTrac program and density statistics were computed.

For H13772 the following percentages represent the results of the density query:

Set Line Spacing MBES (Finalized 1m CUBE weighted Dynamic Surface) = 98.814% of nodes are composed from at least 5 soundings.




Figure 9: H13772 Finalized 1m Set Line Spacing MBES Density Distribution

B.3 Echo Sounding Corrections

B.3.1 Corrections to Echo Soundings

All data reduction procedures conform to those detailed in the DAPR.

B.3.2 Calibrations

All sounding systems were calibrated as detailed in the DAPR.

B.4 Backscatter

Backscatter data were collected throughout the survey and are retained in the raw DB files. Every effort was made in the field to collect quality backscatter data while maintaining the primary mandate of high quality bathymetric data. eTrac verified coverage and general quality of the backscatter data collected daily. A beam intensity window was monitored in Qinsy during acquisition to ensure backscatter data collection. Raw backscatter data were viewed in QPS FMGeocoder (FMGT) to further confirm collection criteria had been met. After MBES data was fully processed and cleaned in Qimera, GSF files were exported and brought into FMGT and processed into backscatter mosaics.

B.5 Data Processing

B.5.1 Primary Data Processing Software

The following Feature Object Catalog was used: NOAA Profile Version 2022.

Feature Object Catalog, NOAA Profile Version 2022 was used only in CARIS. Qimera was used as the primary processing software.

B.5.2 Surfaces

The following surfaces and/or BAGs were submitted to the Processing Branch:

Surface Name	Surface Type	Resolution	Depth Range	Surface Parameter	Purpose
H13772_MB_1m_MLLW_Final	BAG	1 meters	0.39 meters - 19.09 meters	NOAA_1m	Complete MBES
H13772_MBAB_2m_FF_400kHz_1of2	MB Backscatter Mosaic	2 meters	-	N/A	Complete MBES
H13772_MBAB_2m_PU_400kHz_2of2	MB Backscatter Mosaic	2 meters	-	N/A	Complete MBES
H13772_SSSAB_1m_400kHz_1of2	SSS Mosaic	1 meters	-	N/A	100% SSS
H13772_SSSAB_1m_400kHz_2of2	SSS Mosaic	1 meters	-	N/A	200% SSS

Table 10: Submitted Surfaces

A 1m surface is provided meeting complete coverage MBES with backscatter specifications for H13772.

A 1m mosaic is provided meeting complete coverage with 100% SSS specifications for H13772.

A separate 1m mosaic is also provided meeting specifications for the 200% disapproval radii.




Figure 10: H13772 Finalized 1m CUBE Weighted Dynamic Surface Coverage




Figure 11: H13772 Finalized 2m MBAB mosaics




Figure 12: H13772 Finalized 1m SSS mosaics

B.5.3 Additional Task: Final Data Submission - Grids

An additional assigned task for this sheet was to include interpolated grids in Mean Lower Low Water (MLLW) and North American Vertical Datum of 1988 (NAVD88) datum.

C. Vertical and Horizontal Control

Additional information discussing the vertical or horizontal control for this survey can be found in the accompanying HVCR and DAPR.

C.1 Vertical Control

The vertical datum for this project is Mean Lower Low Water.

ERS Datum Transformation

The following ellipsoid-to-chart vertical datum transformation was used:

Method	Ellipsoid to Chart Datum Separation File
ERS via ERTDM	OPR-R351-KR-22_NAD83-MLLW.bin

Table 11: ERS method and SEP file

In order to reference soundings to Mean Lower Low Water Datum, a separation model was provided by NOAA and was applied to the Qinsy DB files via a .qgfvom separation file in the acquisition software.

C.2 Horizontal Control

The horizontal datum for this project is North American Datum 1983 (2011).

The projection used for this project is Universal Transverse Mercator (UTM) Zone 18.

The following PPK methods were used for horizontal control:

- RTX

Applanix PosPac MMS was utilized to post process real time positioning data utilizing Trimble's PP-RTX implementation of Trimble CenterPoint RTX to create a Smoothed Best Estimate of Trajectory (SBET).

RTK

GNSS satellite corrections were received on each vessel using the G2+ and G4+ carrier signal from the Marinestar Global Correction System maintained by Fugro.

C.3 Additional Horizontal or Vertical Control Issues

C.3.1 Additional Task: Final Data Submission - Grids

An additional assigned task for this sheet was to include interpolated grids in the North American Vertical Datum of 1988 (NAVD88) datum. In order to reference soundings to NAVD88 datum, a separation model was provided by NOAA and was applied to the gridded MLLW data in QGIS.

D. Results and Recommendations

D.1 Chart Comparison

A chart comparison was conducted for H13772 using Pydro CA tools, Qimera, and Caris HIPS and SIPS. Survey data were compared against the largest scale ENC to accomplish the chart comparison. Details of the ENC used are listed below.

US5VA62M, scale: 40000, edition: 8, update application date: 11/01/2017, issue date: 11/01/2017

Throughout survey operations sounding comparisons between the charted depths and the surveyed depths were analyzed to identify depth discrepancies. Using 1 meter CUBE weighted Dynamic surfaces, soundings were generated in the "Sounding Selection" tab of Pydro CA tools. Soundings were displayed against the charted soundings and a visual comparison was made in Caris HIPS and SIPS. Additionally, potential DtoNs and discrepancies were generated using the "DTM vs Chart" tab of Pydro CA tools. The results were displayed through CA tools and investigated in CARIS HIPS and SIPS and Qimera.

An overview image of the generated soundings on each chart is included below.

Results of the chart comparison are included in the following sections.




Figure 13: Generated Soundings used for Chart Comparison (US5VA62M)

D.1.1 Electronic Navigational Charts

The following are the largest scale ENC's, which cover the survey area:

ENC	Scale	Edition	Update Application Date	Issue Date
US5VA62M	1:40000	8	11/01/2017	11/01/2017

Table 12: Largest Scale ENC's

D.1.2 Shoal and Hazardous Features

There were 3 DtoNs found in H13772, and added to the Final Feature File (FFF). Each feature in the FFF has been given a unique identifier in the ""userid"" field of the .000 S-57 file (format 8XXXXXX). Refer to the

FFF for determinations and recommendations of each feature. The DtoNs were submitted in the following Danger to navigation reports:

H13772_DtoN_01-03.

D.1.3 Charted Features

There were 77 charted features assigned to H13772 that are included in the Final Feature File (FFF). Each feature in the FFF has been given a unique identifier in the "userid" field of the .000 S-57 file (format 8XXXXXX). Refer to the FFF for determinations and recommendations of each feature.

D.1.4 Uncharted Features

41 new features were found in H13772. Each feature in the FFF has been given a unique identifier in the "userid" field of the .000 S-57 file (format 8XXXXXX). Refer to the FFF for determinations and recommendations of each feature.

Note: DtoNs are not included in the number of new features in this section. DtoNs can be found separately in section D.1.2.

Note: Throughout H13772 there were temporary aids for fishing gear. These aids were not included in the FFF due to their temporary nature.

D.1.5 Channels

West Point Bar Channel was assigned as a dredge area in H13772. No discrepancies were found within our survey extents. The dredge area was not included in the FFF following investigation requirements.

D.2 Additional Results

D.2.1 Aids to Navigation

Throughout H13772 there were temporary aids for fishing gear. These aids were not included in the FFF due to their temporary nature.

All charted AtoNs within the survey area were found to be on station. No AtoNs were reported to the U.S. Coast Guard.

D.2.2 Maritime Boundary Points

No Maritime Boundary Points were assigned for this survey.

D.2.3 Bottom Samples

17 bottom samples were obtained in accordance with section 7.1 of the HSSD 2022 in areas designated by the field through discussions with our COR. Detailed information and images of the bottom samples are located in the Final Feature File (FFF). Each bottom sample has been given a unique identifier in the "userid" field of the .000 S-57 file (format HX).

D.2.4 Overhead Features

There were 16 overhead features assigned to H13772. Assigned overhead features were visually confirmed and no discrepancies were found. The overhead features were not included in the FFF following investigation requirements.

D.2.5 Submarine Features

There was 1 submarine feature assigned to H13772 that is included in the Final Feature File (FFF). Each feature in the FFF has been given a unique identifier in the "userid" field of the .000 S-57 file (format 8XXXXX). Refer to the FFF for determinations and recommendations of each feature.

D.2.6 Platforms

No platforms exist for this survey.

D.2.7 Ferry Routes and Terminals

No ferry routes or terminals exist for this survey.

D.2.8 Abnormal Seafloor or Environmental Conditions

Where one of the tributaries meets the Pamunkey River, a steep escarpment was observed. The riverbed at the bottom of this escarpment is approximately 10 meters deeper than the surrounding area.




Figure 14: Abnormal Seafloor Condition observed in Pamunkey River

D.2.9 Construction and Dredging

There were 10 shoreline construction features assigned to H13772 that are included in the Final Feature File (FFF). Each feature in the FFF has been given a unique identifier in the "userid" field of the .000 S-57 file (format 8XXXXXX). Refer to the FFF for determinations and recommendations of each feature.

1 dredge area was assigned to H13772. No discrepancies were found within our survey extents. The dredge area was not included in the FFF following investigation requirements.

D.2.10 New Survey Recommendations

No new surveys or further investigations are recommended for this area.

D.2.11 ENC Scale Recommendations


No new ENC scales are recommended for this area.

E. Approval Sheet

As Chief of Party, field operations for this hydrographic survey were conducted under my direct supervision, with frequent personal checks of progress and adequacy. I have reviewed the attached survey data and reports.

All CUBE surfaces, this Descriptive Report, and all accompanying records and data are approved. All records are forwarded for final review and processing to the Processing Branch.

The survey data meets or exceeds requirements as set forth in the NOS Hydrographic Surveys and Specifications Deliverables Manual, Field Procedures Manual, Letter Instructions, and all HSD Technical Directives. These data are adequate to supersede charted data in their common areas. This survey is complete and no additional work is required with the exception of deficiencies noted in the Descriptive Report.

Approver Name	Approver Title	Approval Date	Signature
David Neff	Chief of Party	02/15/2024	David Neff, CH  <small>Digitally signed by David Neff, CH DN: cn=US, email=neff@woolpert.com, o="eTrac, A Woolpert Company", ou="eTrac, A Woolpert Company", cn="David Neff, CH" Date: 2024.02.17 00:16:17-08'00'</small>

F. Table of Acronyms

Acronym	Definition
AHB	Atlantic Hydrographic Branch
AST	Assistant Survey Technician
ATON	Aid to Navigation
AWOIS	Automated Wreck and Obstruction Information System
BAG	Bathymetric Attributed Grid
BASE	Bathymetry Associated with Statistical Error
CO	Commanding Officer
CO-OPS	Center for Operational Products and Services
CORS	Continuously Operating Reference Station
CTD	Conductivity Temperature Depth
CEF	Chart Evaluation File
CSF	Composite Source File
CST	Chief Survey Technician
CUBE	Combined Uncertainty and Bathymetry Estimator
DAPR	Data Acquisition and Processing Report
DGPS	Differential Global Positioning System
DP	Detached Position
DR	Descriptive Report
DTON	Danger to Navigation
ENC	Electronic Navigational Chart
ERS	Ellipsoidal Referenced Survey
ERTDM	Ellipsoidally Referenced Tidal Datum Model
ERZT	Ellipsoidally Referenced Zoned Tides
FFF	Final Feature File
FOO	Field Operations Officer
FPM	Field Procedures Manual
GAMS	GPS Azimuth Measurement Subsystem
GC	Geographic Cell
GPS	Global Positioning System
HIPS	Hydrographic Information Processing System
HSD	Hydrographic Surveys Division

Acronym	Definition
HSSD	Hydrographic Survey Specifications and Deliverables
HSTB	Hydrographic Systems Technology Branch
HSX	Hypack Hysweep File Format
HTD	Hydrographic Surveys Technical Directive
HVCR	Horizontal and Vertical Control Report
HVF	HIPS Vessel File
IHO	International Hydrographic Organization
IMU	Inertial Motion Unit
ITRF	International Terrestrial Reference Frame
LNM	Linear Nautical Miles
MBAB	Multibeam Echosounder Acoustic Backscatter
MCD	Marine Chart Division
MHW	Mean High Water
MLLW	Mean Lower Low Water
NAD 83	North American Datum of 1983
NALL	Navigable Area Limit Line
NTM	Notice to Mariners
NMEA	National Marine Electronics Association
NOAA	National Oceanic and Atmospheric Administration
NOS	National Ocean Service
NRT	Navigation Response Team
NSD	Navigation Services Division
OCS	Office of Coast Survey
OMAO	Office of Marine and Aviation Operations (NOAA)
OPS	Operations Branch
MBES	Multibeam Echosounder
NWLON	National Water Level Observation Network
PDBS	Phase Differencing Bathymetric Sonar
PHB	Pacific Hydrographic Branch
POS/MV	Position and Orientation System for Marine Vessels
PPK	Post Processed Kinematic
PPP	Precise Point Positioning
PPS	Pulse per second

Acronym	Definition
PRF	Project Reference File
PS	Physical Scientist
RNC	Raster Navigational Chart
RTK	Real Time Kinematic
RTX	Real Time Extended
SBES	Singlebeam Echosounder
SBET	Smooth Best Estimate and Trajectory
SNM	Square Nautical Miles
SSS	Side Scan Sonar
SSSAB	Side Scan Sonar Acoustic Backscatter
ST	Survey Technician
SVP	Sound Velocity Profiler
TCARI	Tidal Constituent And Residual Interpolation
TPU	Total Propagated Uncertainty
USACE	United States Army Corps of Engineers
USCG	United States Coast Guard
UTM	Universal Transverse Mercator
XO	Executive Officer
ZDF	Zone Definition File