

## **6.0 Tides and Water Levels.**

6.1 **General Requirements.** Tidal zoning shall be constructed and tidal data observed and recorded such that derived tidal corrections to the sounding data meet 0.5 meter accuracy standards. The survey area shall be sufficiently zoned and tide gauges strategically located to ensure tidal corrections meet accuracy requirements.

## **6.2 Tidal Data Collection, Scope of Work.**

6.2.1 The primary NOAA tide Gauges. Also NOAA CO-OPS was responsible for posting preliminary unverified tidal data on the CO-OPS web site, tidal data processing and verification, posting of verified data to the web site and tidal zoning.

## **6.3 Tide Gauges**

NOAA-maintained automatic tide gauges are at the following locations:

Honolulu Harbor, Oahu  
Mokuoloe, Oahu (northern Kaneohe Bay)  
Nawilili, Kauai  
Kawaihae, Hawaii

6.2.3 **Additional Gauges.** NAVOCEANO installed backup gauges on Oahu at the Barbers Pt. Harbor and the Waianae small craft harbor. On Kauai NAVOCEANO installed a tide gauge at a small craft harbor just south of PMRF between Kekaha and Waimea. NOAA gauges supporting the zoning were located on the windward side of the islands, well away from much of the survey area. The NAVOCEANO installed gauges were installed as a backup to the NOAA gauges. Furthermore, the data from the NAVOCEANO installed gauges were used to confirm the NOAA tide-zoning scheme.

## **6.4 Preliminary Tidal Zoning.**

6.4.1 Tide zones were developed by NOAA CO-OPS based on historical data from the above mentioned gauges.

## **6.5 Tide Zone Accuracy**

6.5.1 Results of comparing zone HAW213 (Oahu west coast from Barbers Pt. harbor to Kepuhi Pt. and including Waianae) referenced to NOAA's Honolulu gauge and the installed Waianae gauge are as follows:

Maximum difference:	0.35 meters
Mean difference:	0.15 meters
Standard Deviation:	0.179 meters

## 6.6 **Final Tidal Zoning.**

6.6.1 Tidal No adjustment was made to the NOAA CO-OPS zone scheme. Tidal time series from the NAVOCEANO gauges and tidal time series for the appropriate NOAA tide zone agreed very well. No adjustment to the NOAA zones was necessary.

## 6.7 **Application of Tides.**

6.7.1 The NAVOCEANO processing system does not utilize “tide correctors”, per se. The NOAA CO-OPS zoning scheme partitioned the survey areas into zones referenced to a reference tide gauge. For each zone there is a phase and amplitude correction, also referenced to the reference tide gauge. NAVOCEANO’s processing system handles tide correction by creating a tide file for each zone by applying zonal corrections to the reference gauge tides. The processing software identifies in which zone a sounding falls and applies that zone’s tide to the sounding. Tide correctors are applied during post processing, just prior to data editing and validation.