

W00252

NOAA FORM 76-35A

U.S. DEPARTMENT OF COMMERCE
NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION
NATIONAL OCEAN SURVEY

DESCRIPTIVE REPORT

Type of Survey **Hydrographic Multibeam Survey**
Project No. **AHI-07-03**
Registry No. **W00252**

LOCALITY

State **Northern Mariana Islands**
General Locality **North Pacific Ocean**
Sub-locality **Sarigan Island and Vicinity**

2007

CHIEF OF PARTY
N/A
HYDROGRAPHER
N/A

LIBRARY & ARCHIVES

DATE **June 08, 2007**

HYDROGRAPHIC TITLE SHEET

W00252

INSTRUCTIONS: The Hydrographic Sheet should be accompanied by this form, filled in as completely as possible, when the sheet is forwarded to the Office.

Territory: **Northern Mariana Islands**

General Locality: **North Pacific Ocean**

Sub-Locality: **Sarigan Island and Vicinity**

Scale: **N/A**

Dates of Survey: **05/23/2007 to 06/08/2007**

Instructions Dated: **N/A**

Project Number: **AHI-07-03**

Field Unit: **NOAA R/V AHI**

Chief of Party: **N/A**

Soundings by: **Reson 8101 ER Multibeam Echo Sounder**

Imagery by: **N/A**

Verification by: **Atlantic Hydrographic Branch**

Soundings Acquired in: **meters at Mean Lower Low Water**

Remarks: **Multibeam Hydrographic Survey**
Data collection in meters, referenced to MLLW
UTM Zone 55N

The purpose of this survey is to provide contemporary surveys to update National Ocean Service (NOS) nautical charts. All separates are filed with the hydrographic data. Revisions and Red notes were generated during office processing. The processing branch concurs with all information and recommendations in the DR unless otherwise noted. The final disposition of features is addressed in the Appendix III Feature Report. The discussion of surveyed features in the body of the Descriptive Report are a record of the field unit's report and were not edited for content during AHB processing. Page numbering may be interrupted or non-sequential. All pertinent records for this survey, including the Descriptive Report, are archived at the National Geophysical Data Center (NGDC) and can be retrieved via <http://www.ngdc.noaa.gov/>.

Outside source survey W00252 was submitted without a formal report. The following was included as the body of the Descriptive Report and contains the metadata for this survey.

Identification_Information:

Citation:

Citation_Information:

Originator: National Oceanic and Atmospheric Administration

Pacific Islands Fisheries Science Center Coral Reef

Ecosystem Division Pacific Islands Benthic Habitat

Mapping Center

Publication_Date: 20070824

Title: Reson 8101ER Multibeam Sonar Data from Cruise

AHI0703

Geospatial_Data_Presentation_Form:

Generic Sensor Format (GSF) digital data

Description:

Abstract: Reson 8101ER multibeam Data were collected between

23 May - 9 June 2007 aboard NOAA Survey Launch Acoustic

Habitat Investigator (AHI) at Maug Islands, Pagan Island,

Saipan Island, Tinian Island, Aguijan Island, Anatahan

Island, Sarigan Island, Zealandia Bank, Guguan Island,

Alamagan Island, Agrihan Island, Asuncion Island, Supply

Reef, and Uracus Island, Western Pacific during cruise

AHI0703. These multibeam data were collected using SAIC ISS-2000

software in the Generic Sensor Format and processed using SABER

editing software. Sound velocity corrections from a Seabird SBE19

CTD sensor and motion corrections from a POS-MV vertical

reference were applied to the data in real time.

Predicted tides were applied to the data in real time using predicted tides downloaded from NOAA's National Ocean Service Center for Operational Oceanographic Products and Services (CO-OPS) website.

Horizontal accuracy is ~5m, DGPS from NavCom sensor from C&C Technologies was used, vertical accuracy is depth dependent (~1% of water depth), WGS84 datum. These data are not to be used for navigation. Depths mapped range from 5 - 350 m. The AHI was deployed from the NOAA Ship Hi'ialakai and concurrent mapping was done using the Simrad EM300 sonar aboard the ship; metadata for HI0703 are submitted separately.

Purpose: The data were collected in support of Coral Reef Conservation Program goals to map all shallow (0-30 m) coral reefs in US Pacific waters and priority moderate (> 30 m) depth areas by 2009. The data are being used to provide bathymetric and backscatter data for previously unmapped areas; in support of ecosystem management requirements for benthic habitat mapping and location of Essential Fish Habitat; and to study the geologic features of the area.

Supplemental_Information:

Data were collected aboard the R/V AHI (Acoustic Habitat

Investigator), a 8 m (25') survey launch owned and operated by the NOAA Pacific Islands Fisheries Science Center in Honolulu, HI. The R/V AHI's survey sensors include a 240 kHz RESON 8101-ER sonar which measures bathymetry and acoustic backscatter imagery, a TSS/Applanix POS/MV Model 320 which measures time, position, velocity, attitude and heading, and a Seabird SBE 19 CTD used to measure sound velocity profiles. A C&C Technologies NavCom sensor and the C-NAV RTG network, which is a global system for the distribution of differential GPS corrections, was used for navigation.

The AHI's equipment serial numbers, software versions and sensor configuration settings are as follows:

RESON 8101-ER multibeam echosounder

Transducer serial #: 201004

Firmware, dry: 8101-2.07-2D4D

Firmware, wet: 8101-1.06-2F6B

R/V AHI POS/MV Model 320, version 4.0000

PCS serial #: 2514

IMU serial #: 203

Controller software: v 3.4.0.0

PCS Firmware: 3.41

Seabird SBE19 CTD:

Serial #: 3029

Calibrated 12/28/2006

C&C Technologies NavCom Serial #5111

R/V AHI Lever Arm Distances and Alignment Offsets: The R/V AHI Reference Point (RP) is defined to be the intersection of the vessel's centerline, the cabin deck and the bulkhead immediately aft of the transducer. This is marked by a punch in the deck weld at that location. Positive X means the point is forward of the RP, positive Y means the point is to starboard of the RP, positive Z means the point is below the RP. The loaded waterline is defined as the intersection of the vessel's performance wing with the hull at the transom. A vessel offset survey and patch test were performed in March 2007 and the settings shown here reflect these data.

POS/MV Settings:

RP to IMU, m	0.796	0.001	0.078
RP to Primary GPS(port),m	0.869	-0.472	-2.284
RP to Vessel, m	0.144	0.009	0.786
IMU w.r.t. Ref. Frame, deg	0.000	0.000	0.000
RP to Heave lever arm, m	-0.670	0.000	0.000

RP to Sensor 1(MB transducer), m 0.144 0.009 0.786

RP to Sensor 2 0 0 0

Sensor 1 rotation Ref. Frame, deg 0 0 0

Sensor 2 rotation Ref. Frame, deg 0 0 0

Antenna Baseline Distance: 1.229

ISS2000 Settings for RESON DTC:

Roll Bias, deg 0.15

Pitch Bias, deg 0.0

Gyro Bias, deg 0.0

Transducer depth, m 0.62

Time_Period_of_Content:

Time_Period_Information:

Range_of_Dates/Times:

Beginning_Date: 20070523

Ending_Date: 20070608

Currentness_Reference: ground condition

Status:

Progress: In Work

Maintenance_and_Update_Frequency: As needed

Spatial_Domain:

Bounding_Coordinates:

West_Bounding_Coordinate: 144.8798

East_Bounding_Coordinate: 146.5000

North_Bounding_Coordinate: 20.5518

South_Bounding_Coordinate: 14.9000

Keywords:

Theme:

Theme_Keyword_Thesaurus: CoRIS Theme Thesaurus Version 1.0

Theme_Keyword: EARTH SCIENCE > Oceans > Bathymetry/Seafloor Topography > Bathymetry

Theme:

Theme_Keyword_Thesaurus: None

Theme_Keyword: Bathymetry

Theme_Keyword: Multibeam sonar

Place:

Place_Keyword_Thesaurus: None

Place_Keyword: Maug Islands

Place_Keyword: Pagan Island

Place_Keyword: Saipan Island

Place_Keyword: Tinian Island

Place_Keyword: Aguijan Island

Place_Keyword: Anatahan Island

Place_Keyword: Sarigan Island

Place_Keyword: Zealandia Bank

Place_Keyword: Guguan Island

Place_Keyword: Alamagan Island

Place_Keyword: Agrihan Island

Place_Keyword: Asuncion Island

Place_Keyword: Supply Reef

Place_Keyword: Uracus Island

Place:

Place_Keyword_Thesaurus: CoRIS Place Thesaurus Version 1.0

Place_Keyword: OCEAN BASIN > Pacific Ocean > Northwest Pacific Ocean > Maug Islands,

Pagan Island, Saipan Island, Tinian Island, Aguijan Island, Anatahan Island, Sarigan

Island, Zealandia Bank, Guguan Island, Alamagan Island, Agrihan Island, Asuncion Island,

Supply Reef, Uracus Island

Place_Keyword: COUNTRY/TERRITORY > United States of America > Hawaii > Honolulu

Access_Constraints: None.

Use_Constraints: These data are NOT TO BE USED FOR NAVIGATION

Point_of_Contact:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Joyce E. Miller

Contact_Organization: National Oceanic and Atmospheric Administration

(NOAA) Pacific Islands Fisheries Science Center (PIFSC)

Coral Reef Ecosystem Division (CRED) Pacific Islands Benthic

Habitat Mapping Center (PIBHMC) and the Joint Institute for

Marine and Atmospheric Research (JIMAR)

Contact_Position: Oceanographer

Contact_Address:

Address_Type: mailing and physical address

Address: 1680 East-West Road, POST Bldg, Rm 833

City: Honolulu

State_or_Province: Hawaii

Postal_Code: 96822

Country: USA

Contact_Voice_Telephone: (808) 956-5239

Contact_Facsimile_Telephone: (808) 956-6530

Contact_Electronic_Mail_Address: Joyce.Miller@noaa.gov

Browse_Graphic:

Browse_Graphic_File_Name: None

Browse_Graphic_File_Description: None

Browse_Graphic_File_Type: None

Data_Set_Credit: NOAA PIFSC CRED PIBHMC and JIMAR

Native_Data_Set_Environment: Generic Sensor Format multibeam
data processed with SAIC SABER processing software on LINUX
operating system computers

Data_Quality_Information:

Attribute_Accuracy:

Attribute_Accuracy_Report: Horizontal accuracy is ~5 m as
data were collected using DGPS using C-NAV satellite
correctors. Vertical accuracy of multibeam data is
estimated at 1% of water depth; predicted tidal corrections
were applied.

Logical_Consistency_Report: These data are believed to be
logically consistent though no tests were performed

Completeness_Report: Varies

Positional_Accuracy:

Horizontal_Positional_Accuracy:

Horizontal_Positional_Accuracy_Report: Variable

Quantitative_Horizontal_Positional_Accuracy_Assessment:

Horizontal_Positional_Accuracy_Value: 20

Horizontal_Positional_Accuracy_Explanation: Multibeam
sonar data. No DGPS corrections applied; 20 m accuracy

Vertical_Positional_Accuracy:

Vertical_Positional_Accuracy_Report: Variable

Quantitative_Vertical_Positional_Accuracy_Assessment:

Vertical_Positional_Accuracy_Value: 1

Vertical_Positional_Accuracy_Explanation: Accuracy
varies with water depth. Predicted tide correctors applied
using data supplied by the NOAA CO-OPs program;
multibeam data vertical accuracy is ~1% of water depth.

Lineage:

Source_Information:

Source_Citation:

Citation_Information:

Originator: NOAA PIFSC CRED PIBHMC and JIMAR

Publication_Date: 20070824

Title: Reson 8101ER multibeam bathymetric data

Type_of_Source_Media: Digital data

Source_Time_Period_of_Content:

Time_Period_Information:

Single_Date/Time:

Calendar_Date: 2007

Source_Currentness_Reference: ground condition

Source_Citation_Abbreviation: Reson 8101ER

Source_Contribution: Reson 8101ER (240 kHz) bathymetry and
imagery data were collected in depths of ~10-350 m.

Distribution_Information:

Distributor:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Joyce E. Miller

Contact_Organization: NOAA PIFSC CRED PIBHMC and JIMAR

Contact_Position: Oceanographer

Contact_Address:

Address_Type: mailing and physical address

Address: 1680 East-West Road, POST Bldg, Rm 833

City: Honolulu

State_or_Province: Hawaii

Postal_Code: 96822

Country: USA

Contact_Voice_Telephone: (808) 956-5239

Contact_Facsimile_Telephone: (808) 956-6530

Contact_Electronic_Mail_Address: Joyce.Miller@noaa.gov

Resource_Description: Reson 8101ER Multibeam Sonar Data from
Cruise AH10701 (R/V AHI)

Distribution_Liability: These data are not to be used for
navigational purposes. NOAA makes no warranty regarding these

data, expressed or implied, nor does the fact of distribution constitute such a warranty. NOAA cannot assume liability for any damages caused by any errors or omissions in these data, nor as a result of the failure of these data to function on a particular system.

Standard_Order_Process:

Digital_Form:

Digital_Transfer_Information:

Format_Name: Generic Sensor Format, as described in

http://www.ldeo.columbia.edu/res/pi/MB-System/formatdoc/gsf_spec.pdf

Transfer_Size:

Digital_Transfer_Option:

Online_Option:

Computer_Contact_Information:

Network_Address:

Network_Resource_Name:

Fees: None

Metadata_Reference_Information:

Metadata_Date: 20070824

Metadata_Contact:

Contact_Information:

Contact_Person_Primary:

Contact_Person: Joyce E. Miller

Contact_Organization: NOAA PIFSC CRED PIBHMC and JIMAR

Contact_Position: Oceanographer

Contact_Address:

Address_Type: mailing and physical address

Address: 1680 East-West Road, POST Bldg, Rm 833

City: Honolulu

State_or_Province: Hawaii

Postal_Code: 96822

Country: USA

Contact_Voice_Telephone: (808) 956-5239

Contact_Facsimile_Telephone: (808) 956-6530

Contact_Electronic_Mail_Address: Joyce.Miller@noaa.gov

Metadata_Standard_Name: FGDC Content Standards for Digital

Geospatial Metadata

Metadata_Standard_Version: FGDC-STD-001-1998

Metadata_Time_Convention: Universal Time

APPENDIX I
TIDES AND WATER LEVELS

-NONE

APPENDIX II

SUPPLEMENTAL SURVEY RECORDS AND CORRESPONDENCE

-None

APPENDIX III

SURVEY FEATURES REPORT

-None

APPROVAL PAGE

W00252

Data meet or exceed current specifications as certified by the OCS survey acceptance review process. Descriptive Report and survey data except where noted are adequate to supersede prior surveys and nautical charts in the common area.

The following products will be sent to NGDC for archive

- W00252_DR.pdf
- Collection of depth varied resolution BAGS
- Processed survey data and records
- W00252_GeoImage.pdf

The survey evaluation and verification has been conducted according to current OCS Specifications, and the survey has been approved for dissemination and usage of updating NOAA's suite of nautical charts.

Approved: _____

LT Abigail Higgins
Chief, Atlantic Hydrographic Branch